

# CIVIL / TRACK / STRUCTURAL STANDARD DRAWINGS

**MARCH 2024**

STANDARD DRAWINGS ENSURE THE APPLICATION OF UNIFORM STANDARDS FOR THE DESIGN, FABRICATION, INSTALLATION, AND CONSTRUCTION OF SPECIFIC ITEMS OF WORK FOR THE SOUND TRANSIT LINK LIGHT RAIL, SOUNDER COMMUTER RAIL, REGIONAL EXPRESS BUS, AND STRIDE BUS RAPID TRANSIT SYSTEMS. STANDARD DRAWINGS ARE PRESCRIPTIVE DOCUMENTS FOR ALL PROJECTS.

STANDARD DRAWINGS SHALL BE USED IN THE DESIGN OF INTERFACE POINTS, PROJECT SPECIFIC ITEMS OF WORK OR AS A BASIS FOR PRESENTATION OF DESIGN INFORMATION. THE DESIGNER OF RECORD SHALL REVIEW THE STANDARD DRAWINGS IN CONJUNCTION WITH OTHER CONTRACT DOCUMENTS, AND VALIDATE, FINALIZE, STAMP, AND SIGN THESE DRAWINGS FOR INCLUSION INTO THE PROJECT CONTRACT DOCUMENTS.

IF THE DESIGNER RECOMMENDS THAT AN ASPECT OR ASPECTS OF THESE STANDARD DRAWINGS BE MODIFIED, THE DESIGNER SHALL INFORM THE DESIGN MANAGER ON THE PROJECT AND SECURE CONCURRENCE FROM ENGINEERING FOLLOWING MODIFICATION PROCESS IDENTIFIED IN ENGINEERING PROCEDURES.

THE STANDARD DRAWINGS DO NOT SUBSTITUTE FOR THE DESIGNER'S USE OF INDEPENDENT ENGINEERING JUDGEMENT AND SOUND ENGINEERING PRACTICE, NOR DO THEY RELIEVE THE DESIGN CONSULTANT FROM THE PROFESSIONAL RESPONSIBILITY OF DEVELOPING AN APPROPRIATE DESIGN AND COMPLYING WITH THE STANDARD OF CARE.

**CIVIL / TRACK / STRUCTURAL STANDARD DRAWINGS**

APPLICABILITY OF CURRENT VERSION

SUPERSEDES AUGUST 2019 VERSION

FOR PROJECTS THAT ARE BASELINED AFTER MARCH 29, 2024



**DISCLAIMER FOR  
Design and Engineering Design Standards Documents**

Sound Transit makes these documents available on an "as is" basis. By accepting receipt of the documents, the receiver agrees to the following:

- The documents are provided for information only;
- The receiver will not utilize the documents in any way that violates or infringes on Sound Transit's intellectual property rights in such documents;
- The provided documents should not be construed to represent formal design guidance and/or direction for any project;
- Sound Transit makes no representation or warranty that the provided data is complete, appropriate, or fit for any particular purpose, stated or otherwise;
- All documents provided by Sound Transit, including any revisions, shall remain the personal and intellectual property of Sound Transit; and
- To indemnify, defend, and hold harmless Sound Transit, its consultants, and agent(s) from any and all damages and claims arising from the receiver's use of these documents.

**APPLICABILITY FOR  
Design and Engineering Design Standards Documents**

Project teams shall refer to their executed project contracts for applicable document versions/revisions.

INDEX OF DRAWINGS

DWG. No.	REV	TITLE
<b>GENERAL</b>		
STD-GZT001	1	COVER SHEET
STD-GZI001	1	INDEX OF DRAWINGS
<b>TRACKWORK</b>		
STD-KAD002	2	CURVE SYMBOLS AND SUPERELEVATION TRANSITION
STD-KAD010	2	115RE RAIL AND WHEEL POSITION DETAILS
STD-KAD011	0	11'-5" 115RE GUARD RAIL ASSEMBLY
STD-KAD015	2	PRECURVED RAILS TYPICAL DETAILS
STD-KAD050	1	CONCRETE TIE DETAILS 1 OF 2
STD-KAD051	1	CONCRETE TIE DETAILS 2 OF 2
STD-KAD055	1	BALLASTED GUARD RAIL FLARE LAYOUT AND DETAILS
STD-KAD066	2	BALLASTED TRACK CONSTRUCTION WALKWAY DETAIL AND BALLAST LIMITS AT TURNOUT AREA
STD-KAD070	2	BALLASTED TRACK CONSTRUCTION AT-GRADE ROAD CROSSING PRECAST MODULAR CONCRETE PANEL
STD-KAD071	2	BALLASTED TRACK CONSTRUCTION AT-GRADE ROAD CROSSING PRECAST MODULAR CONCRETE PANEL
STD-KAD075	2	BALLASTED TRACK CONSTRUCTION PEDESTRIAN & MAINTENANCE ACCESS CROSSING PRECAST CONC PANEL ON CONC TIES
STD-KAD090	0	BALLASTED TRACK CONSTRUCTION 115 RE CONCRETE TIE AND FASTENINGS DETAILS
STD-KAD100	1	DIRECT FIXATION STANDARD FASTENER DETAILS
STD-KAD101	1	DIRECT FIXATION STANDARD RESTRAINING RAIL FASTENER DETAILS
STD-KAD102	1	DIRECT FIXATION HIGH RESILIENT FASTENER DETAILS
STD-KAD103	1	DIRECT FIXATION HIGH RESILIENT RESTRAINING RAIL FASTENER DETAILS
STD-KAD105	1	DIRECT FIXATION PLINTH ANCHOR INSERT DETAILS
STD-KAD110	2	DIRECT FIXATION TRACK INSTALLATION PROCEDURES QUALITY CHECKS
STD-KAD120	2	DIRECT FIXATION TRACK INSTALLATION SLAB OR INVERT TANGENT TRACK PLAN AND TYPICAL SECTIONS
STD-KAD121	2	DIRECT FIXATION TRACK INSTALLATION SLAB OR INVERT CURVED TRACK PLAN TYPICAL SECTIONS
STD-KAD125	2	DIRECT FIXATION TRACK AERIAL GUIDEWAY PLINTH REINFORCING FASTENER SPACING LAYOUT
STD-KAD126	2	DIRECT FIXATION TRACK AERIAL GUIDEWAY PLINTH REINFORCING DETAILS
STD-KAD127	2	DIRECT FIXATION NON-AERIAL GUIDEWAY PLINTH REINFORCING FASTENER SPACING LAYOUT
STD-KAD128	2	DIRECT FIXATION TRACK NON-AERIAL GUIDEWAY PLINTH REINFORCING DETAILS
STD-KAD130	0	ELEVATED GUIDEWAY CENTER MAINTENANCE WALKWAY STRIPING
STD-KAD145	2	DIRECT FIXATION EMERGENCY GUARD RAIL INSTALLATION FLARE LAYOUT AND DETAILS
STD-KAD251	0	UNDERDRAIN DETAILS
STD-KAD252	2	EMBEDDED TRACK CONSTRUCTION ROAD INTERSECTIONS TRACK SLAB TRACK DRAIN (115RE)
STD-KAD255	2	EMBEDDED TRACK CONSTRUCTION TRACK SLAB DRAINAGE DETAILS DOUBLE MAINLINE TRACKS (115 RE)
STD-KAD260	2	EMBEDDED TRACK CONSTRUCTION SYSTEM RAIL CONNECTION BLOCKOUTS SECTIONS AND DETAILS (115RE)
STD-KAD300	2	TURNOUT AND CROSSOVER DATA
STD-KAD305	1	SPECIAL TRACKWORK GAUGE PLATES BALLASTED
STD-KAD306	2	SPECIAL TRACKWORK RAIL FASTENER DETAILS DIRECT FIXATION
STD-KAD310	2	9'-5" ADJUSTABLE GUARD RAIL
STD-KAD311	2	13'-0" ADJUSTABLE GUARD RAIL
STD-KAD312	2	16'-6" ADJUSTABLE GUARD RAIL
STD-KAD315	2	13'-0" CURVED SPLIT SWITCH BALLASTED
STD-KAD316	2	13'-0" CURVED SPLIT SWITCH DIRECT FIXATION TRACK
STD-KAD320	2	19'-6" CURVED SPLIT SWITCH
STD-KAD321	2	19'-6" CURVED SPLIT SWITCH DIRECT FIXATION TRACK
STD-KAD325	2	MISCELLANEOUS SWITCH DETAILS
STD-KAD350	2	NO. 5 TURNOUT BALLASTED 13'-0" CURVED SPLIT SWITCH
STD-KAD351	2	NO. 5 RAILBOUND MANGANESE FROG BALLASTED
STD-KAD355	2	NO. 5 EQUILATERAL TURNOUT BALLASTED 13'-0" CURVED EQUILATERAL SPLIT SWITCH
STD-KAD356	1	NO. 5 EQUILATERAL TURNOUT 13'-0" CURVED EQUILATERAL SPLIT SWITCH DIRECT FIXATION
STD-KAD357	2	NO. 5 EQUILATERAL SWITCH 13'-0" CURVED SPLIT SWITCH BALLASTED
STD-KAD358	2	NO. 5 EQUILATERAL RBM FROG BALLASTED
STD-KAD360	2	NO. 6 DOUBLE CROSSOVER 13'-0" CURVED SPLIT SWITCH 15'-9" TRACK CENTERS - DIRECT FIXATION
STD-KAD361	2	NO. 6 RAILBOUND MANGANESE FROG ASSEMBLY FOR 15'-9" TC DOUBLE CROSSOVER DIRECT FIXATION
STD-KAD365	2	NO. 6 DIAMOND CROSSING DIRECT FIXATION FOR 15'-9" DOUBLE CROSSOVER
STD-KAD370	2	NO. 8 TURNOUT BALLASTED AND WELDED WITH 19'-6" CURVED SWITCH
STD-KAD371	2	NO. 8 TURNOUT DIRECT FIXATION WITH 19'-6" CURVED SWITCH
STD-KAD372	2	NO. 8 DOUBLE CROSSOVER DIRECT FIXATION 15'-9" TRACK CENTERS
STD-KAD373	2	NO. 8 DIAMOND CROSSING DIRECT FIXATION
STD-KAD374	2	NO. 8 RAILBOUND MANGANESE FROG
STD-KAD375	2	NO. 8 RAILBOUND MANGANESE FROG DIRECT FIXATION
STD-KAD376	1	NO. 8 RAILBOUND MANGANESE FROG DIRECT FIXATION TRACK
STD-KAD400	2	NO. 10 TURNOUT WITH 19'-6" CURVED SWITCH BALLASTED AND WELDED

DWG. No.	REV	TITLE
<b>TRACKWORK CONT.</b>		
STD-KAD401	2	NO. 10 TURNOUT WITH 19'-6" CURVED DIRECT FIXATION
STD-KAD402	1	NO. 10 TURNOUT DIRECT FIXATION 19'-6" CURVED SPLIT SWITCH
STD-KAD404	2	NO. 10 DOUBLE CROSSOVER DIRECT FIXATION 15'-9" TRACK CENTERS
STD-KAD405	2	NO. 10 DIAMOND CROSSING DIRECT FIXATION
STD-KAD406	2	NO. 10 RAILBOUND MANGANESE FROG
STD-KAD407	2	NO. 10 RAILBOUND MANGANESE FROG DIRECT FIXATION TRACK
STD-KAD415	0	NO. 10 TURNOUT DIRECT FIXATION WITH 19'-6" CURVED SWITCH
STD-KAD416	0	NO. 10 DIRECT FIXATION WELDED BOLTLESS MANGANESE FROG DETAILS
STD-KAD500	2	TRANSITION SLAB EMBEDDED TRACK TO BALLASTED TRACK (115RE)
STD-KAD501	2	TRANSITION SLAB DETAILS BALLASTED TRACK TO DIRECT FIXATION TRACK
STD-KAD503	2	TRANSITION SLAB DIRECT FIXATION TRACK TO EMBEDDED TRACK (115RE)
STD-KAD505	2	RESTRAINING RAIL DETAILS
STD-KAD506	2	INSULATED AND STANDARD JOINT DETAILS
STD-KAD510	2	BUMPING POST BALLASTED TRACK (115RE)
STD-KAD511	2	BUMPING POST DIRECT FIXATION TRACK (115RE TEE RAIL)
STD-KAD520	2	COMPROMISE RAIL 115RE / RI 59N
STD-KAD550	0	PAVING AND PAD DETAILS CONCRETE SLAB FOR LRV UNLOADING SUPPORT

<b>CIVIL</b>		
STD-CMD001	1	PROJECT CONSTRUCTION SITE PROJECT SIGN
STD-CSD101	0	STANDARD FENCE CHAIN LINK MESH
STD-CSD102	0	STANDARD FENCE CHAIN LINK FENCE GATES
STD-CSD103	0	STANDARD FENCE STEEL PICKET FENCE AND SWING GATE
STD-CSD104	0	SECURITY FENCE CHAIN LINK MESH
STD-CSD105	0	SECURITY FENCE CHAIN LINK FENCE GATES
STD-CSD106	0	SECURITY FENCE STEEL PICKET FENCE GATES
STD-CSD107	0	HIGH SECURITY FENCE STEEL PICKET FENCE
STD-CSD108	0	HIGH SECURITY FENCE WELDED MESH FENCE
STD-CSD109	0	PEDESTRIAN FENCING STEEL PICKET FENCE
STD-CSD110	0	THROW PROTECTION FENCING DETAILS
STD-CSD111	0	INTER-TRACK FENCE LINK LIGHT RAIL
STD-CSD112	0	INTER-TRACK FENCE SOUNDER
STD-CSD113	0	SIGNAGE MOUNTING ON CHAINLINK FENCE & GATE
STD-CSD201	1	PEDESTRIAN CROSSING SWING GATE DETAILS
STD-CSD202	0	PEDESTRIAN ESCAPE ROUTE SWING GATE DETAILS
STD-CSD203	0	PAVEMENT MARKING DETAILS
STD-CSD204	0	AT-GRADE CROSSING SIGNAGE LINK & SOUNDER
STD-CSD205	0	TRAIN DYNAMIC SIGN DETAILS
STD-CSD206	0	SIGNAL ASSEMBLY ON OCS POLES DETAILS
STD-CSD301	0	BOLLARDS DETAILS

<b>STRUCTURE</b>		
DRAWING NUMBER	REV	TITLE
STD-SWD100	1	AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM
STD-SWD101	1	AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM
STD-SWD102	1	AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM
STD-SWD103	1	AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM
STD-SWD104	1	AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM
STD-SWD200	0	BALLAST BARRIER DETAILS
STD-SVD101	0	AERIAL GUIDEWAY STRUCTURE COLUMN INSPECTION SILO DETAILS 1 OF 2
STD-SVD102	0	AERIAL GUIDEWAY STRUCTURE COLUMN INSPECTION SILO DETAILS 2 OF 2

03/29/24 | 10:22 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-GZI001.DWG


Uncontrolled document from soundtransit.org

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				REVISED STANDARD DRAWINGS
0	8/2019				CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: NTS
FILENAME: STD-GZI001
CONTRACT No.: RTA/LR -
DATE: 2/2024




**SOUND TRANSIT**  
STANDARD DRAWINGS  
CIVIL  
INDEX OF DRAWINGS

DRAWING No.:	<b>STD-GZI001</b>
FACILITY ID:	
SHEET No.:	REV:
	1




**SIMPLE CIRCULAR CURVE**

NTS




**CIRCULAR CURVE WITH SPIRAL**

NTS




**COMPOUND CURVE WITH JOINING SPIRALS**

NTS




**STATION EQUATION DEVELOPMENT**

NTS




**SIMPLE SPIRAL**

NTS




**SAG VERTICAL CURVE**

NTS



**CREST VERTICAL CURVE**

NTS



**SUPERELEVATION DEVELOPMENT**

NTS

**GENERAL NOTES:**

1. ALL HORIZONTAL AND VERTICAL DISTANCES ARE IN FEET AND/ OR DECIMALS OF A FOOT EXCEPT AS NOTED OTHERWISE ON PLANS.
2. LENGTH OF CURVES AND STATIONING SHOULD BE COMPUTED BASED ON THE ARCH DEFINITION.

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD002.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL ARCH SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD002
CONTRACT No.:	RTA/LR -
DATE:	2/2024


<b>SOUND TRANSIT STANDARD DRAWINGS TRACKWORK</b>	
CURVE SYMBOLS AND SUPERELEVATION TRANSITION	

DRAWING No.:	<b>STD-KAD002</b>
FACILITY ID:	
SHEET No.:	REV:
	2


03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD010.DWG

uncontrolled document from soundtransit.org


- GENERAL NOTES:**
1. TRACK RAILS AND CONTRACT DOCUMENTS ARE PREPARED WITH 115 RE RAIL SECTION.
  2. DETAILS SHOW NEW WHEEL AND STANDARD 115 RE TRACK RAILS.
  3. 1/4" NOMINAL DIMENSION, BUT DIMENSION VARIES WITH ALTERNATIVE RAIL PROFILES.



**TRACK RAILS - 115 RE**  
SCALE: 12" = 1'-0"



**LRV WHEEL AND FLANGE PROFILE**  
SCALE: 12" = 1'-0"



**TRACK GAUGE, RAIL AND WHEELS POSITION**  
SCALE: 3" = 1'-0"

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE


SCALE: AS NOTED  
FILENAME: STD-KAD010  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK  
115RE RAIL AND WHEEL POSITION  
DETAILS


DRAWING No.:	STD-KAD010
FACILITY ID:	
SHEET No.:	REV: 2




**11' 5" GURARD RAIL ASSEMBLY DETAIL**  
NTS



**SECTION A**  
NTS



**SECTION B**  
NTS



**SECTION C**  
NTS

03/26/24 | 7:15 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD011.DWG


No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

	SCALE:	AS NOTED
	FILENAME:	STD-KAD011
	CONTRACT No.:	RTA/LR -
	DATE:	2/2024


<b>SOUND TRANSIT STANDARD DRAWINGS</b> TRACKWORK 11'-5" 115RE GUARD RAIL ASSEMBLY	
DRAWING No.:	STD-KAD011
FACILITY ID:	
SHEET No.:	REV: 0



**115RE RUNNING RAIL AND RESTRAINING RAIL  
TYPICAL PRECURVING DETAIL**  
NTS

**GENERAL NOTES:**

- REFER TO HORIZONTAL ALIGNMENT DRAWINGS AND TRACK CHART FOR CURVED TRACKS THAT NEEDS PRECURVED RAILS.
- TYPICAL MARKINGS OF PRECURVED RAILS.



- FOR 115RE RESTRAINING RAIL DETAILS SEE DWG STD-KAD430.

**LEGEND:**

- BOLTED JOINT
- ⊗ WELDED JOINT


03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD015.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-




LINE IS 1" AT FULL SCALE



SCALE: NTS  
FILENAME: STD-KAD015  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK  
PRECURVED RAILS  
TYPICAL DETAILS**

DRAWING No.:	<b>STD-KAD015</b>
FACILITY ID:	
SHEET No.:	REV: 2



**GENERAL NOTES:**


1. TIE TO BE SYMMETRICAL ABOUT THE CENTERLINE OF TRACK.
2. SHOULDERS SHOULD BE POSITIONED ON LONGITUDINAL CENTERLINE OF TIE.
3. REINFORCEMENT ARE NOT SHOWN LOCATION SIZE NUMBER AND STRENGTH OF PRESTRESSED REINFORCEMENT STRANDS REQUIRED TO MEET SPECIFICATIONS SHALL BE BY THE CONTRACTOR.
4. LOCATIONS AND SPACING OF TIE INSTALLATIONS ARE GIVEN IN THE TRACK CHART DRAWINGS.
5. TIE SPACING ON CURVES SHALL BE MEASURED AT THE CENTERLINE OF THE OUTSIDE RAIL.

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD050.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:



SCALE:	NTS
FILENAME:	STD-KAD050
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

**CONCRETE TIE  
DETAILS**


1 OF 2

DRAWING No.:	<b>STD-KAD050</b>
FACILITY ID:	
SHEET No.:	REV: 1







**PLAN VIEW**




**ELEVATION VIEW**




**END VIEW**  
NTS




**SECTION A**  
NTS




**SHOULDER LOCATION DETAIL 1**  
NTS




**GUARDRAIL FASTENING DETAIL 2**  
NTS



**SECTION THROUGH RESTRAINING RAIL SEAT CENTERLINE B**  
NTS



**PLAN VIEW**



**ELEVATION VIEW**

**8'-3\"/>**

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD051.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	4/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


SCALE:	NTS
FILENAME:	STD-KAD051
CONTRACT No.:	RTA/LR -
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS</b>	
TRACKWORK	
CONCRETE TIE DETAILS	
2 OF 2	

DRAWING No.:	STD-KAD051
FACILITY ID:	
SHEET No.:	REV:
	1


**GENERAL NOTES:**

1. FOR LIMITS OF EMERGENCY GUARD RAILS. SEE TRACK CHART DRAWINGS.
2. FOR CONCRETE TIE DETAILS SEE DWGS. STD-KAD050 AND STD-KAD051
3. WITH IN THE FLARED END, THE EMERGENCY GUARD RAIL SHALL BE FASTENED IN SPACING OF 30" OR LESS. OTHER THAN THE FLARED END, THE EMERGENCY GUARD RAIL SHALL BE FASTENED IN FIVE FEET OR LESS.



**EMERGENCY GUARD RAIL INSTALLATION PLAN**

NTS



**SECTION**

NTS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:

DATE:


REVIEWED BY:

DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD055
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK  
BALLASTED GUARD RAIL FLARE  
LAYOUT AND DETAILS

DRAWING No.:	<b>STD-KAD055</b>
FACILITY ID:	
SHEET No.:	REV: 1



**BALLAST LIMITS AT TURNOUT AREA**  
NTS

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD066.DWG


					<b>AHJ:</b>			<b>PACKAGE #</b>						
					DESIGNED BY: DRAWN BY: CHECKED BY: APPROVED BY:			SCALE: NTS FILENAME: STD-KAD066 CONTRACT No.: RTA/LR -			<b>SOUND TRANSIT</b> <b>STANDARD DRAWINGS</b> TRACKWORK BALLASTED TRACK CONSTRUCTION WALKWAY DETAIL AND BALLAST LIMITS AT TURNOUT AREA		DRAWING No.:	
					SUBMITTED BY: DATE: REVIEWED BY: DATE:			DATE: 2/2024			FACILITY ID:			
											SHEET No.:			
											REV: 2			
No.	DATE	DSN	CHK	APP	REVISION									
2	2/2024				2024 REVISED STANDARD DRAWINGS									
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS									
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS									

LINE IS 1" AT FULL SCALE




**GENERAL NOTES:**


1. THIS DRAWING DEPICTS TYPICAL AND MINIMUM SPECIFICATIONS. MODULAR CROSSING PANELS TO BE INSTALLED ACCORDING TO MANUFACTURER'S RECOMMENDATION.
2. DESIGN LOADING: COOPER E-80, 60% IMPACT FACTOR. H-20 WHEEL LOAD.
3. CROSSING MODULES MUST PASS LONGITUDINAL RESTRAINT TEST PER AREMA CHAPTER 30.
4. CONCRETE GRADE CROSSING PANELS TO BE 6000 PSI MINIMUM AT 28 DAYS.
5. MODULES TO HAVE 4 LIFTING ANCORS EMBEDDED IN CONCRETE.
6. APPROXIMATE WEIGHT IS 1,275 LBS PER TRACK FOOT.
7. ON STREETS WITH CURBS OR PAVED SHOULDERS, THE CROSSING SHALL BE EXTENDED TO BE 3 FEET BEYOND THE BACK OF CURB. THE CROSSING SURFACE SHALL EXTEND 2 FEET BEYOND THE SIDEWALK LINE FOR STREET CROSSING WITH SIDEWALK.
8. CROSSING MODULES TO BE CAST TO MATCH CURVATURE FOR CURVED TRACK.
9. SIZE OF PANELS SHOWN ON THIS DRAWING ARE 5'-0" x 8'-0", ACTUAL PANEL WIDTH MAY VARY.
10. MODULE WIDTHS MAY BE UP TO 17'-6" IN AREAS OF TANGENT TRACK
11. MODULES TO HAVE 3 EACH 1-1/4" PVC GROUT INJECTION PORTS.



**ROAD CROSSING - PLAN VIEW**  
NTS



**ROAD CROSSING - SECTION A**  
SCALE: 1/2" = 1'-0"



**END PANEL DETAIL**  
SCALE: 1" = 1'-0"

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD070.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY: DATE: REVIEWED BY: DATE:	- - - -
---	------------------


	SCALE: AS NOTED
	FILENAME: STD-KAD070
	CONTRACT No.: RTA/LR -
	DATE: 2/2024

<b>SOUND TRANSIT</b> <b>STANDARD DRAWINGS</b> TRACKWORK	
BALLASTED TRACK CONSTRUCTION AT-GRADE ROAD CROSSING PRECAST MODULAR CONCRETE PANEL	


DRAWING No.:	STD-KAD070
FACILITY ID:	
SHEET No.:	REV: 2

**GENERAL NOTES:**


1. STANDARD RUBBER GAUGE INSERTS SHALL BE INSTALLED AT ROADWAY WIDTH OF CROSSING. MODIFIED RUBBER GAUGE INSERTS SHALL BE INSTALLED AT PEDESTRIAN /SIDEWALK WIDTH WITHIN THE ROAD CROSSING.
2. FLANGEWAY WIDTH SHALL BE 2 1/2" AT ROAD CROSSING AND SHALL BE 2 1/4" MAXIMUM AT PEDESTRIAN/ SIDEWALK CROSSING.
3. DESIGN ALL CROSSINGS TO PROVIDE 1:40 RAIL CANT THROUGHOUT.
4. RUBBER FLANGEWAY INSERTS AND RAIL FASTENERS MUST BE REMOVABLE AND REUSABLE TO FACILITATE RAIL ACCESS OR REPLACEMENT.
5. CROSSING TO INCLUDE GALVANIZED "E" CLIPS.
6. GRIND BASE OF RAIL SMOOTH AT WELDS
7. END MODULES TO HAVE 45 DEGREE SLOPE FROM BOTTOM OF RAIL TO TOP OF MODULE AND 1" TAPPER UNDER RAIL.




**STANDARD RUBBER GAUGE 2 1/2" FLANGEWAY**  
NTS




**ROAD CROSSING - SECTION A**  
NTS



**STANDARD RUBBER GAUGE 2 1/2" FLANGEWAY**  
NTS



**CONNECTION DETAIL**  
NTS



**END PANEL DETAIL**  
NTS

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD071.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	NTS
FILENAME:	STD-KAD071
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

BALLASTED TRACK CONSTRUCTION  
AT-GRADE ROAD CROSSING PRECAST  
MODULAR CONCRETE PANEL


DRAWING No.:	<b>STD-KAD071</b>
FACILITY ID:	
SHEET No.:	REV: 2




**PLAN PEDESTRIAN CROSSING**  
SCALE: 3/4" = 1'-0"

- GENERAL NOTES:**
1. PEDESTRIAN AND MAINTENANCE ACCESS CROSSING PANELS TO BE INSTALLED ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
  2. SIZE OF PANELS SHOWN ON THIS DRAWING ARE FOR ILLUSTRATION ONLY. ACTUAL SIZE VARY DEPENDING ON MANUFACTURER.
  3. FLANGWAY FILLERS SHALL BE FURNISHED ON ALL PEDESTRIAN AND MAINTENANCE ACCESS CROSSINGS.
  4. A FILLER RAMP SHALL BE SHAPED OUT OF ASPHALT TO REDUCE POSSIBLE DAMAGE FROM DRAGGING EQUIPMENT AND TO PREVENT SHIFTING. ASPHALT FILLER SHALL BE INSTALLED PRIOR TO RAIL TRAFFIC IMPROVEMENT AND SHOULD NOT BE PLACED IN CLOSE CONTACT WITH RAILS AND FASTENERS.
  5. PRECAST CONCRETE PANELS SURFACE SHALL BE MATCHING FINISHED AND COLOR OF STATION WALKWAY AREA. SEE CONTRACT DRAWINGS FOR ADDITIONAL SURFACE FINISHING REQUIREMENTS.
  6. NEOPRENE PADS SHALL BE ADHERED TO CONCRETE TIES WITH AREMA SC-200 CEMENT WITH HARDENER ADDITIVE, OR APPROVED EQUIVALENT.
  7. FOR LIMITS OF CROSSING SEE TRACK CHART DRAWING.
  8. 10'-0" LENGTH CONCRETE TIES CAN BE USED AS AN ALTERNATIVE.


BILL OF MATERIALS 14' CROSSING PANEL UNIT	
QTY	DESCRIPTION
2	FIELD BLOCK SECTION WITH LIFTING INSERT
1	CENTER BLOCK SECTION WITH LIFTING INSERT
12	1/2" FIELD BLOCK NEOPRENE PAD
6	3/4" CENTER BLOCK NEOPRENE PAD
30 TF	FIELD SIDE RUBBER FLANGWAY INSERT
30 TF	GAUGE SIDE RUBBER FLANGWAY INSERT
A/R	ASPHALT FILLER



**SECTION A**  
SCALE: 1 1/2" = 1'-0"



**SECTION B**  
SCALE: 1 1/2" = 1'-0"



**DETAIL 1**  
SCALE: 3" = 1'-0"

03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD075.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:




SCALE:	AS NOTED
FILENAME:	STD-KAD075
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

BALLASTED TRACK CONSTRUCTION  
PEDESTRIAN & MAINTENANCE ACCESS CROSSING  
PRECAST CONC PANEL ON CONC TIES

DRAWING No.:	<b>STD-KAD075</b>
FACILITY ID:	
SHEET No.:	REV: 2




**BLOCKING EXTENSION AT PLATFORM** 1  
NTS



**PLAN VIEW**

**SIDE VIEW**



**FRONT VIEW**

**PRESSURE TREATED BLOCK DETAIL** 2  
SCALE: 2"=1'-0"

**GENERAL NOTES:**

1. CONCRETE TIE TIMBER BLOCKING SHALL BE INSTALLED AT EACH END OF THE STATION PLATFORMS AND AT EVERY TEN CONCRETE TIE LOCATION WITHIN THE LIMITS OF THE STATION PLATFORMS.
2. ALL STEEL ANGLES SHALL CONFORM TO ASTM A36 AND BE HOT DIP GALVANIZED PER ASTM A123.
3. EXPANSION ANCHORS SHALL BE STUD TYPE WITH A SINGLE PIECE THREE SECTION WEDGE AND ZINC PLATED IN ACCORDANCE WITH ASTM B633. THE ANCHORS MUST MEET THE DESCRIPTION IN FEDERAL SPECIFICATION FF-S-325, GROUP 11, TYPE 4, CLASS 1 FOR CONCRETE EXPANSION ANCHORS.
4. WASHERS SHALL BE HARDENED STEEL WASHERS CONFORMING TO ASTM F436-TYPE 1.
5. LAG SCREWS SHALL BE ASTM A307 GRADE A AND BE HOT DIP GALVANIZED PER ASTM A123.
6. CARE AND ATTENTION SHALL BE TAKEN TO ELIMINATE VOIDS BENEATH THE WOOD BLOCKING.
7. VERIFY PLATFORM WALL LOCATION AND CONCRETE TIE LENGTH PRIOR TO CUTTING WOOD BLOCKS. BLOCKS SHALL BE SIZED TO FIT BETWEEN THE PLATFORM WALL AND CONCRETE TIE WITH THE SPECIFIED TRACK CL/PLATFORM EDGE DISTANCE.


03/21/24 | 8:47 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD090.DWG

DESIGNED BY:					
DRAWN BY:					
CHECKED BY:					
APPROVED BY:					
0	2/2024				2024 NEW STANDARD DRAWING
No.	DATE	DSN	CHK	APP	REVISION


SUBMITTED BY:		DATE:	REVIEWED BY:	DATE:	 <b>SOUND TRANSIT</b> STANDARD DRAWINGS TRACKWORK BALLASTED TRACK CONSTRUCTION 115 RE CONCRETE TIE AND FASTENINGS DETAILS	DRAWING No.:	<b>STD-KAD090</b>
						FACILITY ID:	
				2/2024		SHEET No.:	0

**GENERAL NOTES:**

1. EACH FASTENER SHALL BE INSTALLED WITH AT LEAST ONE 1/8" THICK HDPE SHIM,
2. TOTAL NUMBER OF SHIMS PLACED UNDER RAIL FASTENER BODY FOR HEIGHT ADJUSTMENT SHALL BE LIMITED TO A MAXIMUM OF TWO SHIMS AND A MAXIMUM TOTAL THICKNESS OF 1/2"
3. STANDARD DIRECT FIXATION FASTENER SHOULD BE SUPPLIED WITH TWO TYPES OF CONFIGURATIONS:
  - 3.1. STANDARD FASTENERS WITH RAIL SEAT CANTED 1:40 FOR FASTENING RAIL ON MAINLINE PRIMARY TRACK. H=1 7/8"
  - 3.2. STANDARD SPECIAL TRACKWORK FASTENERS WITH RAIL SEAT NON CANTED FOR FASTENING SINGLE RAIL WITHIN THE LIMIT OF TURNOUT AND CROSSOVER. H=1 1/2"
4. AT LOCATIONS WHERE DF FASTENERS ARE UNDER RAIL JOINTS, INSTALL PANDROL TYPE C-2063 RAIL CLIPS OR APPROVED EQUALS.




**PLAN**




**NOTE:**  
SHIM SHAPE AND HOLES SHALL BE COMPATIBLE WITH FASTENER SHAPE, SIZE & ANCHOR BOLT LOCATION.  
MATERIAL: HIGH DENSITY POLYETHYLENE (HDPE)


**SHIM CONFIGURATION THICKNESSES: 1/16", 1/8", 3/16", 1/4"**




**FRONT**



**SIDE (NO RAIL OR CLIPS)**



**PLAN**



**ELEVATION**

**INSERT VERTICAL TOLERANCE**

NTS

**STANDARD DIRECT FIXATION RAIL FASTENER**

SCALE: 3" = 1'-0"

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD100.DWG



DESIGNED BY:		SCALE:	AS NOTED	DRAWING No.: <b>STD-KAD100</b>	
DRAWN BY:		FILENAME:	STD-KAD100		
CHECKED BY:		CONTRACT No.:	RTA/LR -	FACILITY ID:	
APPROVED BY:		DATE:	2/2024	SHEET No.: REV: 1	
1	2/2024		2024 REVISED STANDARD DRAWINGS		
0	8/2019		NEW - CIVIL DIRECTIVE AND STANDARD DWGS		
No.	DATE	DSN	CHK	APP	REVISION







03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\CIVIL-STRUCT\STD-KAD101.DWG

**GENERAL NOTES:**

1. EACH FASTENER SHALL BE INSTALLED WITH AT LEAST ONE 1/8" THICK HDPE SHIM,
2. TOTAL NUMBER OF SHIMS PLACED UNDER RAIL FASTENER BODY FOR HEIGHT ADJUSTMENT SHALL BE LIMITED TO A MAXIMUM OF TWO SHIMS AND A MAXIMUM TOTAL THICKNESS OF 1/2"
3. STANDARD DIRECT FIXATION FASTENER SHOULD BE SUPPLIED WITH TWO TYPES OF CONFIGURATIONS:
  - 3.1. STANDARD FASTENERS WITH RAIL SEAT CANTED 1:40 FOR FASTENING RAIL ON MAINLINE PRIMARY TRACK. H=1 7/8"
  - 3.1. STANDARD SPECIAL TRACKWORK FASTENERS WITH RAIL SEAT NON CANTED FOR FASTENING SINGLE RAIL WITHIN THE LIMIT OF TURNOUT AND CROSSOVER. H=1 1/2"
4. AT LOCATIONS WHERE DF FASTENERS ARE UNDER RAIL JOINTS, INSTALL PANDROL TYPE C-2063 RAIL CLIPS OR APPROVED EQUALS.



**NOTE:**  
 SHIM SHAPE AND HOLES SHALL BE COMPATIBLE WITH FASTENER SHAPE, SIZE & ANCHOR BOLT LOCATION. MATERIAL: HIGH DENSITY POLYETHYLENE (HDPE)




**INSERT VERTICAL TOLERANCE**  
 NTS

**STANDARD DIRECT FIXATION RAIL FASTENER**  
 SCALE: 3" = 1'-0"


DESIGNED BY:		SCALE: AS NOTED	<b>SOUND TRANSIT</b> STANDARD DRAWINGS TRACKWORK DIRECT FIXATION STANDARD RESTRAINING RAIL FASTENER DETAILS	DRAWING No.: <b>STD-KAD101</b>	
DRAWN BY:		FILENAME: STD-KAD101		FACILITY ID:	
CHECKED BY:		CONTRACT No.: RTA/LR -	SHEET No.: 1	REV: 1	
APPROVED BY:		DATE: 2/2024			
1	2/2024	2024 REVISED STANDARD DWGS			
0	8/2019	NEW - CIVIL DIRECTIVE AND STANDARD DWGS			
No.	DATE	DSN	CHK	APP	REVISION

**GENERAL NOTES:**

1. EACH FASTENER SHALL BE INSTALLED WITH AT LEAST ONE 1/8" THICK HDPE SHIM.
2. TOTAL NUMBER OF SHIMS PLACED UNDER RAIL FASTENER BODY FOR HEIGHT ADJUSTMENT SHALL BE LIMITED TO A MAXIMUM OF TWO SHIMS AND A MAXIMUM TOTAL THICKNESS OF 1/2".
3. FASTENER HEIGHT WITH RAIL SEAT CANTED 1:40 FOR FASTENING RAIL ON MAINLINE PRIMARY TRACK. H=2 3/4"
4. AT LOCATIONS WHERE DF FASTENERS ARE UNDER RAIL JOINTS, INSTALL PANDROL TYPE "C-2063" RAIL CLIPS OR APPROVED EQUALS.




**PLAN**




**NOTE:**

SHIM SHAPE AND HOLES SHALL BE COMPATIBLE WITH FASTENER SHAPE, SIZE & ANCHOR BOLT LOCATION. MATERIAL: HIGH DENSITY POLYETHYLENE (HDPE)


**SHIM CONFIGURATION THICKNESSES: 1/16", 1/8", 3/16", 1/4"**




**PLAN**



**ELEVATION**



**SIDE (NO RAIL OR CLIPS)**



**ELEVATION**

**INSERT VERTICAL TOLERANCE NTS**

**HIGH RESILIENT FASTENER**

SCALE: 3" = 1'-0"

03/21/24 | 8:48 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD102.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


LINE IS 1" AT FULL SCALE	
SCALE: AS NOTED	
FILENAME: STD-KAD102	
CONTRACT No.: RTA/LR -	

<b>SOUND TRANSIT</b> <b>STANDARD DRAWINGS</b> TRACKWORK DIRECT FIXATION HIGH RESILIENT FASTENER DETAILS	DRAWING No.: <b>STD-KAD102</b>
	FACILITY ID:
	SHEET No.: 1 REV: 1


DRAWING No.: STD-KAD102
FACILITY ID:
SHEET No.: 1 REV: 1

03/21/24 | 8:48 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD103.DWG

uncontrolled document from soundtransit.org




**PLAN**



**NOTE:**

SHIM SHAPE AND HOLES SHALL BE COMPATIBLE WITH FASTENER SHAPE, SIZE & ANCHOR BOLT LOCATION. MATERIAL: HIGH DENSITY POLYETHYLENE (HDPE)


**SHIM CONFIGURATION THICKNESSES: 1/16", 1/8", 3/16", 1/4"**




**PLAN**

**ELEVATION**

**INSERT VERTICAL TOLERANCE**  
NTS



**FRONT**



**SIDE (NO RAIL OR CLIPS)**

**RESTRAINING RAIL DF RAIL FASTENER**  
SCALE: 3" = 1'-0"

**GENERAL NOTES:**

1. EACH FASTENER SHALL BE INSTALLED WITH AT LEAST ONE 1/8" THICK HDPE SHIM.
2. TOTAL NUMBER OF SHIMS PLACED UNDER RAIL FASTENER BODY FOR HEIGHT ADJUSTMENT SHALL BE LIMITED TO A MAXIMUM OF TWO SHIMS AND A MAXIMUM TOTAL THICKNESS OF 1/2".
3. FASTENER HEIGHT WITH RAIL SEAT CANTED 1:40 FOR FASTENING RAIL ON MAINLINE PRIMARY TRACK. H=2 3/4"
4. AT LOCATIONS WHERE DF FASTENERS ARE UNDER RAIL JOINTS, INSTALL PANDROL TYPE "C-2063" RAIL CLIPS OR APPROVED EQUALS.

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

SCALE:	AS NOTED
FILENAME:	STD-KAD103
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

DIRECT FIXATION  
HIGH RESILIENT RESTRAINING RAIL FASTENER  
DETAILS


DRAWING No.:	STD-KAD103
FACILITY ID:	
SHEET No.:	REV: 1

**GENERAL NOTES:**


1. INSTALL PLUG INSERTS DURING CONSTRUCTION TO KEEP THE INSERTS CLEAN AND FREE OF FOREIGN MATERIAL.
2. THIN PLASTIC PUSH-IN THIMBLE TYPE PLUGS MAY BE USED FOR TEMPORARY PROTECTION OF THE THREADS AT THE CONTRACTORS OPTION. HOWEVER, THIN PLASTIC PUSH-IN THIMBLE TYPE PLUGS MAY NOT BE USED AS PERMANENT PLUGS ON INSERTS THAT ARE LEFT OPEN.
3. INSERTS THAT ARE LEFT OPEN AT THE CONCLUSION OF THE PROJECT SHALL BE PLUGGED WITH A REMOVABLE THREADED PLUG THAT IS FLUSH TO THE ADJACENT CONCRETE SURFACE.
4. PLUGS TO HAVE EITHER HEX OR SQUARE RECESS FOR WRENCH.
5. ANCHOR BOLTS SHALL BE CENTERED ON THEIR LOCKING WASHER +/- 1/8"
6. TYPE I INSERTS TO BE USED FOR ALL FASTENERS EXCEPT WHERE NOTED IN THE CONTRACT DRAWINGS.



**TYPE I INSERT**  
SCALE: 1'-0"=1'-0"



**TYPE II INSERT**  
SCALE: 1'-0"=1'-0"




**THREADED PLUG**  
SCALE: 1'-0"=1'-0"

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD105.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:


SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_  
REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_



SCALE: 1'-0" = 1'-0"  
FILENAME: STD-KAD105  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK  
DIRECT FIXATION  
PLINTH ANCHOR INSERT  
DETAILS

DRAWING No.: **STD-KAD105**  
FACILITY ID:  
SHEET No.: 1 REV: 1



**LIGHT RAIL QUALITY CHECK ON SURFACE INSTALLATION TYPICAL STRINGLINE DIRECT FIXATION FASTENER**  
SCALE: 1" = 1'-0"

**DIRECT FIXATION TRACK INSTALLATION PROCEDURES:**

THESE PROCEDURES ARE PROVIDED AS A REFERENCE GUIDE ONLY, AND BEGIN WITH ACCEPTANCE OF THE BASE (INVERT, AERIAL, OR SLAB) CONCRETE IN PLACE. ALTERNATE INSTALLATION PROCEDURES ACHIEVING EQUAL RESULTS MAY BE SUBMITTED BY CONTRACTOR FOR CONSTRUCTION RESIDENT ENGINEER'S APPROVAL.

DIRECT FIXATION TRACK CONSTRUCTION PERTAINS TO THE FOLLOWING TYPES OF TRACK INSTALLATIONS:

- A. DIRECT FIXATION TRACK ON TUNNEL INVERT.
- B. DIRECT FIXATION TRACK ON AERIAL STRUCTURES.
- C. DIRECT FIXATION TRACK ON AT-GRADE SLAB TRACK.

THE FOLLOWING PROCEDURES OUTLINE THE SEQUENCE OF THE INSTALLATION FOR THE ABOVE TYPES OF TRACK CONSTRUCTION.

1. SURVEY CENTER LINE OF TRACK, ESTABLISHING SURVEY POINTS (HORIZ & VERT) EVERY 10 FEET ON TANGENTS AND 5 FEET ON CURVES.
2. PREPARE CUT SHEETS BASED ON EXISTING BASE CONCRETE ELEVATIONS TO ESTABLISH TOP OF RAIL AND PLINTH CONCRETE ELEVATIONS.
3. ROUGHENED BASE CONCRETE SHALL BE CLEAN AND FREE OF LAITANCE TO PROVIDE A ROUGH SURFACE FOR INTERLOCKING OF PLINTH CONCRETE TO PARENT BASE CONCRETE.
- 4a. INSPECT AND CONFIRM POSITION OF EXISTING EPOXY-COATED REINFORCING BAR DOWELS TO SUIT PROPOSED PLINTH CONCRETE PAD LENGTHS, WIDTHS AND LAYOUTS.
- 4b. ALTER BY REMOVAL OR BENDING EXISTING DOWELS TO SUIT PLINTH PAD CONCRETE DIMENSIONS AND LAYOUT
- 4c. ADD ADDITIONAL DOWELS, WHERE REQUIRED, TO SUPPLEMENT REMOVED DOWELS.
- 4d. PLACE REINFORCING BARS, FORMING CAGES, WITHIN THE PLINTH CONCRETE ENVELOPE PROVIDING THE STATED SIDE CLEARANCE TO THE CONCRETE SURFACE

- 5a. POSITION FORMWORK TO GENERATE PLINTH CONCRETE SHAPE, LENGTH, AND OPENING IN ACCORDANCE WITH STANDARD DRAWINGS AND APPROVED CONTRACTOR SHOP DRAWINGS.
- 5b. FORMS OR SCREEDS SHALL BE POSITIONED TO PROVIDE PLINTH CONCRETE TOP ELEVATION ACCURATE TO THE TOLERANCES STATED IN THE SPECIFICATIONS AND AS SHOWN ON THE STANDARD DRAWINGS.
- 6a. USING CUT SHEETS AND ESTABLISHED SURVEY POINTS, POSITION, LOCATE AND JIG ANCHOR BOLT INSERTS FOR DIRECT FIXATION FASTENERS.
- 6b. ON CURVES REQUIRING EMERGENCY GUARD RAIL, POSITION, LOCATE AND JIG ANCHOR BOLT INSERTS FOR DIRECT FIXATION FASTENERS.
7. CLEAN BASE CONCRETE OF ALL OILS, CONTAMINATES AND DIRT FOR APPLICATION OF BONDING AGENT, AS REQUIRED.
8. PRIOR TO BONDING AGENT APPLICATION, INSPECTION AND APPROVAL MUST BE OBTAINED FROM THE CONSTRUCTION RESIDENT ENGINEER.
9. APPLY BONDING AGENT TO BASE CONCRETE SURFACES IN THE AREAS OF PLINTH CONCRETE CONSTRUCTION.
- 10a. PLACE PLINTH CONCRETE WITH APPROPRAITE VIBRATION TO FILL ALL CORNERS, AND GAPS AROUND REINFORCING BARS AND EMBEDDED ANCHOR INSERTS.
- 10b. CONCRETE SHALL BE PLACED AND FINISHED TO GENERATE A SMOOTH VOID FREE CONCRETE PLINTH SURFACE IN ACCORDANCE WITH THE SPECIFICATIONS.
11. AFTER PLINTH CONCRETE HAS REACHED SUFFICIENT STRENGTH TO RETAIN EMBEDDED ANCHOR INSERTS, REMOVE ANCHOR BOLTS AND FRAMEWORK AND PATCH SURFACE VOIDS AS REQUIRED USING EPOXY GROUT.

**QUALITY CHECKS:**

1. ALL DIRECT FIXATION FASTENER PLINTH CONCRETE TOP SURFACE SHALL BE :
  - LEVEL WITH A TOLERANCE OF 1/8" OVER 24" Laterally.
  - SLOPED FOR SUPERELEVATION WITH A TOLERANCE OF 1/8" OVER 24" Laterally.
  - LEVEL (OR TANGENT GRADE LINE) WITH A TOLERANCE OF:
    - 1/8" OVER 80" LONGITUDINALLY.
    - 1/4" OVER 160" INCHES LONGITUDINALLY.
  - FASTENERS IN VERTICAL CURVE TRACK SHALL BE CHECKED BY SIMILAR PROCEDURE USING VERTICAL OFFSETS BETWEEN FASTENERS AS COMPARISON.
2. ADJACENT PLINTH CONCRETE PADS SHALL BE WITHIN THE ABOVE TOLERANCES. ADJACENT FASTENER LEVELS SHALL BE WITHIN 1/16" OF EACH OTHER.
3. PLINTH CONCRETE SHALL BE QUALITY CHECKED PRIOR TO PLACEMENT OF FASTENERS. PLINTH CONCRETE SURFACE SHALL BE UNIFORM, NO SAGS OR CROWNS IN FASTENER SEAT AREA AND EMERGENCY GUARD RAIL BASE PLATE AREA.
4. DIRECT FIXATION FASTENER POSITION SHALL BE QUALITY CHECKED PRIOR TO PLACEMENT OF RAIL BY THE STRING LINE METHOD. HIGH OUT OF TOLERANCE FASTENERS SHALL BE CORRECTED BY SHIM CHANGEOUTS OR GRINDING OF CONCRETE PLINTH SURFACE WHERE IT IS APPARENT THAT ONE OR TWO ISOLATED FASTENERS ARE HIGH. IN THIS QUALITY CHECK PROCEDURE, ALL FASTENERS SHALL BE TIGHTLY BOLTED TO THE PLINTH CONCRETE SURFACE DURING THIS TEST.
5. A MINIMUM OF ONE 1/8" THICK SHIM SHALL BE INSTALLED UNDER EACH FASTENER, A MAXIMUM OF 1/2" THICK SHIM SHALL BE INSTALLED UNDER FASTENERS AS A CORRECTIVE PROCEDURE. HOWEVER, ONLY 3 FASTENERS CONSECUTIVELY MAXIMUM SHALL BE ALLOWED 1/2" THICK SHIMS. FASTENERS REQUIRING 3/4" AND HIGHER SHIM HEIGHT SHALL BE LIMITED TO SIX CONSECUTIVE FASTENERS. THE NOMINAL FASTENER SHIM HEIGHT SHALL BE 1/8" AT ALL LOCATIONS EXCEPT DIRECT FIXATION TRACK IN STATION AREAS WHERE THE NOMINAL SHIM HEIGHT SHALL BE 1/4"
6. QUALITY CHECK DETAIL IS SHOWN FOR 30" FASTENER SPACING. SEE DRAWING NOS STD-KAD120 TO STD-KAD128 INCLUSIVE FOR FASTENER SPACING CRITERIA.
7. QUALITY CHECK FOR TESTING ELECTRICAL ISOLATION SHALL BE AS SPECIFIED IN THE STANDARD SPECIFICATIONS.

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD110.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DWGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE


SCALE: 1" = 1'-0"  
FILENAME: STD-KAD110  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**


DIRECT FIXATION TRACK  
INSTALLATION PROCEDURES  
QUALITY CHECKS

DRAWING No.:	<b>STD-KAD110</b>
FACILITY ID:	
SHEET No.:	REV: 2

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\CIVIL-STRUCTURE\STANDARD DRAWINGS\CIVIL-STRUCTURE\STD-KAD120.DWG




**PLAN**



**PLAN**

**GENERAL NOTES:**


1. PLINTH CONCRETE SHALL BE PLACED IN SEGMENTS. SEGMENTS SHALL BETWEEN 2 AND 4 FASTENER LENGTHS.
2. PLINTH GAPS SHALL BE LOCATED AS REQUIRED FOR STRUCTURAL JOINTS, DRAINAGE, AND PASSAGE OF SIGNAL OR OTHER CABLES.
3. PLINTH SURFACE SHOWN DOES NOT INCLUDE APPLICABLE CROSS SLOPE OR CONSTRUCTION TOLERANCES. THE CONTRACTOR IS RESPONSIBLE TO FIELD VERIFY ABILITY TO PLACE MINIMUM REQUIRED DIRECT FIXATION HEIGHTS AS SHOWN AND ANY NECESSARY MODIFICATIONS TO THE PLINTH SURFACE TO MAINTAIN THE PGL.
4. FOR FASTENER SPACING IN CURVES, SEE DWG STD-KAD121.
5. FOR STANDARD FASTENER DETAILS SEE DWG STD-KAD100. FOR STANDARD RESTRAINING RAIL DETAILS SEE DWG STD-KAD101.
6. GUARDRAIL CLIP COMPONENT INCLUDES HEAVY HEX BOLT, COVER PLATE ANCHOR, AND SPRING LOCK WASHER.
7. U-BOLT FOR EMERGENCY GUARD RAIL SHALL BE TIED TO PLINTH REINFORCEMENT FOR ELECTRICAL CONTINUITY OR, ALTERNATIVELY SHALL BE EPOXY COATED.
8. THE TOP LEVEL OF THE EMERGENCY GUARD RAIL MUST BE THE SAME LEVEL OF THE RUNNING RAIL WITH TOLERANCE OF -1" WHEN GROUT PAD IS USED AND 1-1/4" WHEN SHIMS ARE USED.
9. WHERE REQUIRED FOR PASSAGE OF SIGNAL OR OTHER CABLES AND STRUCTURAL JOINTS, THE PLINTH GAP CAN BE INCREASED BY UP TO 4". THE CENTER OF FASTENER TO THE END OF THE PLINTH MUST NOT BE LESS THAN 8".



**ELEVATION**

**DIRECT FIXATION TANGENT WITHOUT EMERGENCY GUARD RAIL INSTALLATION**


SCALE: 1 1/2" = 1'-0"




**ELEVATION**

**DIRECT FIXATION WITH EMERGENCY GUARDRAIL**


SCALE: 1" = 1'-0"




**PLAN**



**ELEVATION**



**BASE PLATE PLAN**



**GROUT PAD ELEVATION**

**EMERGENCY GUARDRAIL PLINTH DETAIL**  
NTS

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - C&A GUIDANCE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-


LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD120  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**


DIRECT FIXATION TRACK INSTALLATION SLAB OR INVERT TANGENT TRACK PLAN AND TYPICAL SECTIONS

DRAWING No.:	STD-KAD120
FACILITY ID:	
SHEET No.:	REV: 2



**DIRECT FIXATION CURVED AND SUPERELEVATED TRACK WITH RADIUS > 500 FT WITHOUT EMERGENCY GUARD RAIL INSTALLATION**

SCALE: 1"=1'-0"



**DIRECT FIXATION CURVED AND SUPERELEVATED TRACK WITH RADIUS > 500 FT WITH EMERGENCY GUARD RAIL INSTALLATION**


SCALE: 1"=1'-0"

**GENERAL NOTES:**

- FASTENER SPACING APPLIES FROM TS TO ST OF CURVES AND 100' OR SHORTER TANGENT SECTIONS BETWEEN CURVES. FASTENERS SPACING AT CENTERLINE OF OUTER RAIL FOR CURVES LESS THAN OR EQUAL TO 500' VARY AS PER FOLLOWING CURVE RADII.
 


CURVE RADIUS	FASTENERS SPACING
500' ≤ R < 500'	27"
300' < R < 500'	27"
R ≤ 300'	24"
- PLINTH LENGTHS AND NUMBER OF FASTENERS PER PLINTH VARY (DUE TO SEGMENTAL CONSTRUCTION) AS PER THE FOLLOWING CURVE RADII.
 

CURVE RADIUS	NO FASTENERS PER PLINTH
R ≤ 200'	2
200' < R ≤ 300'	2OR 3
300' < R ≤ 500'	2, 3, 4
500' ≤ R	BETWEEN 2 AND 8 AS REQUIRED
- PLINTH GAPS SHALL BE LOCATED AS REQUIRED FOR STRUCTURAL JOINTS, DRAINAGE AND PASSAGE OF SIGNAL OR OTHER CABLES.
- ON CURVED TRACKS DISTANCES SHOWN BETWEEN FASTENERS AND/OR PLINTH ENDS SHALL BE MADE AT THE CENTERLINE OF OUTSIDE RAIL. RAIL FASTENERS ON INSIDE RAIL OF CURVE SHALL BE PLACED RADIAL FROM OUTSIDE RAIL FASTENERS.
- PLINTH SURFACE SHOWN DOES NOT INCLUDE APPLICABLE CROSS SLOPE OR CONSTRUCTION TOLERANCES. THE CONTRACTOR IS RESPONSIBLE TO FIELD VERIFY ABILITY TO PLACE MINIMUM REQUIRED DIRECT FIXATION HEIGHTS AS SHOWN AND ANY NECESSARY MODIFICATIONS TO THE PLINTH SURFACE TO MAINTAIN THE PGL.
- FOR FASTENER DETAILS SEE DWGS STD-KAD100 TO STD-KAD103.
- CLIP COMPONENT INCLUDES HEAVY HEX BOLT, COVER PLATE ANCHOR, AND SPRING LOCK WASHER.
- EMERGENCY GUARDRAIL FASTENERS SHALL BE SPACED SUCH THAT THEY ARE MIDWAY BETWEEN ADJACENT RUNNING RAIL FASTENERS. SPACING IS SUBJECT TO ADJUSTMENT TO ACCOMMODATE ADJACENT RUNNING RAIL FASTENER SPACING ADJUSTMENT, WHERE APPLICABLE, WITH A MINIMUM SPACING OF 5'-3".
- U-BOLT FOR EMERGENCY GUARD RAIL SHALL BE TIED TO PLINTH REINFORCEMENT FOR ELECTRICAL CONTINUITY OR, ALTERNATIVELY SHALL BE EPOXY COATED.
- THE TOP LEVEL OF THE EMERGENCY GUARD RAIL MUST BE THE SAME LEVEL OF THE RUNNING RAIL WITH TOLERANCE OF -1" WHEN GROUT PAD IS USED AND 1-1/4" WHEN SHIMS ARE USED.
- WHERE REQUIRED FOR PASSAGE OF SIGNAL OR OTHER CABLES AND STRUCTURAL JOINTS, THE PLINTH GAP CAN BE INCREASED BY UP TO 4". THE CENTER OF FASTENER TO THE END OF THE PLINTH MUST NOT BE LESS THAN 8".



**ELEVATION**

SCALE: 1"=1'-0"



**ELEVATION**

SCALE: 1"=1'-0"

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD121.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE

SCALE: 1"=1'-0"  
 FILENAME: STD-KAD121  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

DIRECT FIXATION TRACK  
INSTALLATION SLAB OR INVERT  
CURVED TRACK PLAN TYPICAL SECTIONS


DRAWING No.:	<b>STD-KAD121</b>
FACILITY ID:	
SHEET No.:	REV:
	2

**GENERAL NOTES:**


1. PLACEMENT OF THE BARS TO BE CLEAR OF FASTENER INSERT ANCHORS.
2. FOR EMERGENCY GUARD RAIL (EGR) LOCATION SEE TRACK CHARTS.
3. PLINTHS SHALL NOT OVERLAP ANY STRUCTURE JOINTS.
4. WHERE FASTENER SPACING ADJUSTMENT IS REQUIRED, REFER TO THE CONTRACT DOCUMENTS.
5. WHERE REQUIRED FOR PASSAGE OF SIGNAL OR OTHER CABLES AND STRUCTURAL JOINTS, THE PLINTH GAP CAN BE INCREASED BY UP TO 4". THE CENTER OF FASTENER TO END OF THE PLINTH MUST NOT BE LESS THAN 8".
6. 1/2" TOOLED EDGE CAN BE USED IN PLACE OF 1" CHAMFERED EDGE.



**4 FASTENER LONGITUDINAL PLINTH LAYOUT**  
SCALE: 1" = 1'-0"



**2 FASTENER LONGITUDINAL PLINTH LAYOUT**  
SCALE: 1" = 1'-0"



**DETAIL - STIRRUPS**  
SCALE: NTS

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD125.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	4/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


SCALE:	AS NOTED
FILENAME:	STD-KAD125
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK

DIRECT FIXATION TRACK  
AERIAL GUIDEWAY PLINTH REINFORCING FASTENER  
SPACING LAYOUT


DRAWING No.:	STD-KAD125
FACILITY ID:	
SHEET No.:	2






**MAXIMUM SUPERELEVATION (Ea = 4")**

SCALE: 1 1/2"=1'-0"




**TIE BAR DETAIL**

SCALE: 1 1/2"=1'-0"




**MINIMUM SUPERELEVATION (Ea = 1/2")**

SCALE: 1 1/2"=1'-0"




**EGR WITH SUPERELEVATION**

SCALE: 1 1/2"=1'-0"




**RESTRAINING RAIL WITH SUPERELEVATION**

SCALE: 1 1/2"=1'-0"




**TANGENT NO SUPERELEVATION**

SCALE: 1 1/2"=1'-0"



**EGR TANGENT NO SUPERELEVATION**

SCALE: 1 1/2"=1'-0"



**RESTRAINING RAIL NO SUPERELEVATION**

SCALE: 1 1/2"=1'-0"

**GENERAL NOTES:**

1. TIE WIRES TO BE INSULATED.
2. PLINTH THICKNESSES SHOWN DO NOT CONSIDER SLAB CROSS SLOPE AND DO NOT ACCOUNT FOR SLAB CONSTRUCTION TOLERANCES.
3. PLINTH HEIGHT IS SUBJECT TO INCREASE OR DECREASE BASED ON AS-BUILT STRUCTURE SURFACE AND RETAINING DESIGNED PROFILE GRADE LINE.
4. PLINTHS SHALL NOT OVERLAP ANY STRUCTURE JOINTS.
5. REBAR MUST BE A MINIMUM OF 3/4" CLEAR OF ANCHOR INSERT.
6. CLEARANCE FROM THE TIE BAR TO THE BOTTOM OF INVERT SLAB MUST BE A MINIMUM OF 1 1/2".
7. 1/2" TOOLED EDGE CAN BE USED IN PLACE OF 1" CHAMFER EDGE

03/22/24 | 11:16 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD126.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED- C&A GUIDANCE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE


SCALE: 1 1/2" = 1'-0"  
 FILENAME: STD-KAD126  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024

**SOUND TRANSIT  
 STANDARD DRAWINGS  
 TRACKWORK**


DIRECT FIXATION TRACK  
 AERIAL GUIDEWAY PLINTH REINFORCING  
 DETAILS

DRAWING No.:	<b>STD-KAD126</b>
FACILITY ID:	
SHEET No.:	REV: 2


- GENERAL NOTES:**
1. PLACEMENT OF TIE BARS TO BE CLEAR OF FASTENER INSERT ANCHORS.
  2. FOR EMERGENCY GUARD RAIL (EGR) LOCATIONS SEE TRACK CHARTS.
  3. PLINTH GAP SHALL BE LOCATED AS REQUIRED FOR STRUCTURE JOINTS, DRAINAGE AND PASSAGE OF SIGNAL OR OTHER CABLES.
  4. U SHAPED STIRRUP BAR CAN BE USED IN LIEU OF 2 LAPPED STIRRUP BARS.
  5. WHERE FASTENER SPACING ADJUSTMENT IS REQUIRED REFER TO THE CONTRACT DOCUMENT.
  6. WHERE REQUIRED FOR PASSAGE OF SIGNAL OR OTHER CABLES AND STRUCTURAL JOINTS, THE PLINTH GAP CAN BE INCREASED BY UP TO 4". THE CENTER OF FASTER TO END OF THE PLINTH MUST NOT BE LESS THAN 8".
  7. 1/2" TOOLED EDGE CAN BE USED IN PLACE OF 1" CHAMFER EDGE



**4 FASTENER LONGITUDINAL PLINTH LAYOUT**  
SCALE: 1" = 1'-0"



**2 FASTENER LONGITUDINAL PLINTH LAYOUT**  
SCALE: 1" = 1'-0"



**DETAIL - STIRRUPS**  
SCALE: NTS

03/21/24 | 8:48 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD127.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 UPDATES
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARDS DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD127
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK


DIRECT FIXATION  
NON-AERIAL GUIDEWAY PLINTH REINFORCING  
FASTENER SPACING LAYOUT

DRAWING No.:	STD-KAD127
FACILITY ID:	
SHEET No.:	2




**MAXIMUM SUPERELEVATION (Ea = 4")**

SCALE: 1 1/2"=1'-0"




**TIE BAR DETAIL**

SCALE: NTS




**MINIMUM SUPERELEVATION (Ea = 1/2")**

SCALE: 1 1/2"=1'-0"




**EGR WITH SUPERELEVATION**

SCALE: 1 1/2"=1'-0"




**RESTRAINING RAIL WITH SUPERELEVATION**

SCALE: 1 1/2"=1'-0"




**TANGENT NO SUPERELEVATION**

SCALE: 1 1/2"=1'-0"



**EGR TANGENT NO SUPERELEVATION**

SCALE: 1 1/2"=1'-0"



**RESTRAINING RAIL NO SUPER ELEVATION**

SCALE: 1 1/2"=1'-0"

**GENERAL NOTES:**

1. TIE WIRES TO BE INSULATED.
2. PLINTH THICKNESS SHOWN DO NOT CONSIDER SLAB CROSS SLOPE AND DO NOT ACCOUNT FOR SLAB CONSTRUCTION TOLERANCES.
3. PLINTH HEIGHT IS SUBJECT TO INCREASE OR DECREASE BASED ON AS-BUILT STRUCTURE SURFACE AND RETAINING DESIGNED PROFILE GRADE LINE.
4. PLINTHS SHALL NOT OVERLAP ANY STRUCTURE JOINTS.
5. REBAR MUST BE A MINIMUM OF 3/4" CLEAR OF ANCHOR INSERTS.
6. CLEARANCE FROM THE TIE BAR TO THE BOTTOM OF INVERT SLAB MUST BE A MINIMUM OF 1 1/2".

03/21/24 | 8:48 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD128.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	4/2019				REVISED - C&A GUIDANCE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	1 1/2" = 1'-0"
FILENAME:	STD-KAD128
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

DIRECT FIXATION TRACK  
NON-AERIAL GUIDEWAY PLINTH REINFORCING  
DETAILS

DRAWING No.:	<b>STD-KAD128</b>
FACILITY ID:	
SHEET No.:	REV:
	2

**NOTES:**

1. PAINT STRIPE AND HATCH STRIPE MARKINGS MUST BE YELLOW IN COLOR, PAINT TYPE MUST BE LOW VOC WATERBORNE OR LOW VOC SOLVENT.



**TRACKWAY WALKWAY**  
NTS

03/21/24 | 8:49 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD130.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWING

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

LINE IS 1" AT FULL SCALE

SCALE:	AS NOTED
FILENAME:	STD-KAD130
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

ELEVATED GUIDEWAY  
CENTER MAINTENANCE WALKWAY STRIPING

DRAWING No.:	STD-KAD130
FACILITY ID:	
SHEET No.:	REV:
	0


**GENERAL NOTES:**

1. FOR EMERGENCY GUARD RAIL DIRECT FIXATION TYPICAL SECTION AND DETAIL SEE DWG KAD120.
2. FOR LIMITS OF EMERGENCY GUARD RAILS SEE TRACK CHART DRAWING.
3. WITHIN THE FLARED END, THE EMERGENCY GUARD RAIL SHALL BE FASTENED IN SPACING OF 30" OR LESS. OTHER THAN THE FLARED END, THE EMERGENCY GUARD RAILS SHALL BE FASTENED IN 5'-0" OR LESS.
4. EMERGENCY GAURD RAIL MUST BE INTERRUPTED 2" FROM THE ENDS OF THE PEDESTRIAN CROSSING PANEL.



**PLAN VIEW - EMERGENCY GUARD RAIL INSTALLATION**

SCALE: 1/2" = 1'-0"



**GUARD RAIL BEVEL END CUT DETAIL AT EACH END OF INSTALLATION**


SCALE: 3"=1'-0"

**SECTION B**

SCALE: 3"=1'-0"

**EMERGENCY GUARD RAIL PLATE DETAIL**

NTS



**PLAN VIEW - END OF GUARD RAIL FLARE DETAIL**

NTS

03/21/24 | 8:49 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\CIVIL\STRUCT\STD-KAD145.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
 FILENAME: STD-KAD145  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**


DIRECT FIXATION EMERGENCY GUARD RAIL INSTALLATION FLARE LAYOUT AND DETAILS

DRAWING No.:	<b>STD-KAD145</b>
FACILITY ID:	
SHEET No.:	REV: 2






- NOTE:**
1. TERMINAL CLEANOUT SHALL BE PROVIDED AT UPSTREAM END OF ALL UNDERDRAINS.
  2. CLEANOUTS SHALL BE LOCATED AT 300 LF (MAX) SPACING.


**UNDERDRAIN CLEANOUT DETAIL**  
NTS



**TYPICAL TRACK UNDERDRAIN DETAIL**  
NTS



**CLEANOUT COVER AND RING DETAIL**  
NTS



**UNDERDRAIN PIPE CONNECTION TO DRAIN PIPE**  
NTS


03/21/24 | 8:49 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD251.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: NTS  
FILENAME: STD-KAD251  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS**  
TRACKWORK  
UNDERDRAIN DETAILS


DRAWING No.:	STD-KAD251
FACILITY ID:	
SHEET No.:	REV: 0

**GENERAL NOTES:**


- SUBMIT STEEL ANGLE FRAME AND GRATING SHOP DRAWINGS TO RESIDENT ENGINEER FOR APPROVAL PRIOR TO FABRICATION. FRAME AND GRATE SHALL BE GALVANIZED STEEL.
- BOLT GRATES TO FRAME.
- SLOT BOTTOM OF BOOT AT CENTER OF DRAIN TO ALLOW BOOT VOIDS DRAINAGE. SLOT SHALL BE 6" LONG BY 4" WIDE AT GAUGE SIDE. SEAL WITH ELASTOMERIC GROUT OR SEALANT THE OPEN CAVITIES OF THE RAIL BOOT IN THE DOWNSTREAM SIDE OF THE SLOT. REMOVE 6" LENGTH OF RUBBER EXTRUSION FLANGEWAY FORMER TO DRAIN THE TRACK FLANGEWAY.




**TRACK DRAIN DETAIL**  
NTS



**SECTION B**  
NTS



**SECTION A**  
NTS



**SECTION C**  
NTS


03/21/24 | 8:49 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD252.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 NEW STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEM GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-KAD252  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

EMBEDDED TRACK CONSTRUCTION  
ROAD INTERSECTIONS TRACK SLAB TRACK DRAIN  
(115RE)


DRAWING No.:	<b>STD-KAD252</b>
FACILITY ID:	
SHEET No.:	REV: 2



**SECTION A**  
SCALE: 3/4" = 1'-0"




**TYPICAL TRACK DRAIN AND TRACKWAY DRAIN LOCATION PLAN**  
SCALE: 1/2" = 1'-0"




**NOTE:**  
TOP OF DRAIN ALONG PLATFORMS SHALL BE SET AT A MIN. OF 3/4" BELOW TOP OF RAIL. CONCRETE SURFACE SHALL BE GRADED LOCALLY AROUND DRAIN.

**TRACKWAY DRAIN AT PLATFORM DETAIL**  
SCALE: 1" = 1'-0"



**PLATFORM AND AERIAL DRAIN DETAIL 1**  
SCALE: 1" = 1'-0"



**TRACKWAY DRAIN DETAIL 2**  
SCALE: 1" = 1'-0"

03/21/24 | 8:49 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD255.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGFS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

	SCALE:	AS NOTED
	FILENAME:	STD-KAD255
	CONTRACT No.:	RTA/LR -
	DATE:	2/2024


<b>SOUND TRANSIT STANDARD DRAWINGS</b>	
TRACKWORK	
EMBEDDED TRACK CONSTRUCTION TRACK SLAB DRAINAGE DETAILS DOUBLE MAINLINE TRACKS (115 RE)	

DRAWING No.:	<b>STD-KAD255</b>
FACILITY ID:	
SHEET No.:	REV:
	2




**GENERAL NOTES:**


1. SEE CONDUIT PLANS FOR LOCATION OF BLOCKOUTS. ADJUST LOCATIONS OF CONDUITS AND BLOCKOUTS IN FIELD TO AVOID INTERFERENCE WITH RAIL SUPPORTS.
2. BLOCKOUT DIMENSION IS FROM EITHER FIELD OR GAUGE SIDE OF RAILHEAD OR FLANGEWAY CUP WITH 115 RE RAIL.
3. DISCONTINUE RAIL BOOT THROUGH BLOCKOUT. HOWEVER PROVIDE 1 INCH OVERLAP INTO THE BLOCKOUT.
4. MINIMUM DEPTH FOR 2 INCH CONDUIT BLOCKOUT IS TO THE BASE OF RAIL OR TOP OF FIRST POUR, WHICHEVER IS DEEPER.
5. IF ROUTING CONFLICTS REQUIRE A VERTICAL STUB UP OF THE 3" CONDUIT THEN INCREASE BLOCKOUT DEPTH TO 1 FOOT.
6. CONDUITS SHALL BE CAPPED AND A NYLON PULLROPE INSERTED PRIOR TO ANY CONCRETE POURS. AFTER RAIL INSTALLATION COMPLETE, MANDREL THE CONDUIT AND RE-CAP LEAVING PULLROPE FOR FOLLOW-ON SYSTEMS CONTRACTOR.
7. AFTER INSTALLATION IS COMPLETE, FILL BLOCKOUT WITH TEMPORARY WOOD BLOCKS TO LEVEL FLUSH WITH ROAD SURFACE. CUT AND PLACE WOOD AS NECESSARY TO PROTECT CONDUIT STUB.
8. ELASTOMERIC GROUT PLACEMENT AND WELDED RAIL CONNECTIONS SHALL BE PERFORMED BY THE FOLLOW-ON SYSTEMS CONTRACTOR.



**RAIL CONNECTION BLOCKOUT PLAN VIEW**  
SCALE: 3/4" = 1'-0"



**RAIL CONNECTION BLOCKOUT WITH 2" CONDUIT SECTION**  
SCALE: 3" = 1'-0" **A**



**RAIL CONNECTION BLOCKOUT WITH 3" CONDUIT SECTION**  
SCALE: 3" = 1'-0" **B**

03/26/24 | 7:02 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD260.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD260
CONTRACT No.:	RTA/LR -
DATE:	X/2023

<b>SOUND TRANSIT STANDARD DRAWING TRACKWORK</b>	
EMBEDDED TRACK CONSTRUCTION SYSTEM RAIL CONNECTION BLOCKOUTS SECTIONS AND DETAILS (115RE)	

DRAWING No.:	STD-KAD260
FACILITY ID:	
SHEET No.:	REV: 2

- GENERAL NOTES:**
1. GEOMETRIC DISTANCES BASED ON 4'-8 1/2" GAUGE. GEOMETRIC DISTANCES BASED ON TANGENT PITO TO PITO. TURNOUTS ARE BASED ON AREMA PLAN.
  2. AN INCREASE OF 1.0 FOOT IN TRACK CENTERS CAUSES AN INCREASE OF N/2 AND N IN THE "D" AND "Z" DISTANCES RESPECTIVELY.
  3. ALL DATA EXCEPT "G", "K" AND "M" ALSO APPLY TO SINGLE CROSSOVERS.
  4. FOR ALL SINGLE CROSSOVERS ON BALLASTED AND DF TRACKS CONNECTING TRACKS WITH CENTERS EQUAL TO OR GREATER THAN 15'-0", SHALL BE DESIGNED AS TWO TURNOUTS WITH A TANGENT TRACK CONNECTION BETWEEN THE TURNOUTS.



**GEOMETRIC SCHEMATIC - SINGLE OR DOUBLE CROSSOVER**  
NTS

TURNOUT DATA TABLE											
TURNOUT NUMBER	FROG ANGLE F	SWITCH LENGTH & TYPE	LEAD C	PS TO PITO A	PITO TO 1/2" PF B	CENTERLINE RADIUS R	SWITCH			FROG	
							POINT ANGLE FROM TAN	HEEL ANGLE	RADIUS	TOE LENGTH	HEEL LENGTH
5	11°25'16"	13.00 CV	44.5417	20.7917	23.7500	188.10	1°41'31"	2°54'00"	616.55	4.5000	6.3333
5 EQL	11°25'16"	13.00 CV	44.5417	20.6731	23.8686	352.80	0°50'45"	2°54'00"	1233.10	4.5000	6.3333
6 (15.75' T)	9°31'38"	13.00 CV	49.7500	21.2491	28.5009	283.88	1°41'31"	2°54'00"	616.55	5.6875	11.6823
6 (14.00' T)	9°31'38"	13.00 CV	49.7500	21.2491	28.5009	283.88	1°41'31"	2°54'00"	616.55	5.6875	13.2083
8	7°09'10"	19.50 CV	69.0000	31.0000	38.0000	482.09	1°04'24"	1°59'15"	1222.17	6.2500	9.4167
10	5°43'29"	19.50 CV	78.9167	31.4167	47.5000	806.09	1°04'24"	1°59'15"	1222.17	7.4167	11.3333

(DIMENSIONS IN FEET UNLESS OTHERWISE NOTED)

CROSSOVER DATA TABLE								
TRACK CENTERS T	TURNOUT NUMBER	SWITCH LENGTH & TYPE	OVERALL LENGTH Z	CROSSING DATA		OTHER DATA		
				K	M	D	N	G
14.00	6	13.00' CV	125.9149	19°03'16"	28.4462	62.9575	5.9584	-1.0156
15.75	6	13.00' CV	136.3420	19°03'16"	28.4462	68.1710	5.9584	4.1979
14.00	8	19.50' CV	173.5608	14°18'20"	37.8132	86.7804	7.9686	-1.1262
15.75	8	19.50' CV	187.5059	14°18'20"	37.8132	93.7529	7.9686	5.8463
14.00	10	19.50' CV	202.4856	11°26'58"	47.2018	101.2428	9.9752	-1.2748
15.75	10	19.50' CV	219.9421	11°26'58"	47.2018	109.9711	9.9752	7.4522

(DIMENSIONS IN FEET UNLESS NOTED OTHERWISE)

03/22/24 | 11:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD300.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	2/2024

SCALE: NTS  
FILENAME: STD-KAD300  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
TRACKWORK  
TURNOUT AND CROSSOVER DATA

DRAWING No.:	STD-KAD300
FACILITY ID:	
SHEET No.:	REV: 2




**PLAN VIEW**


**PLATE No. 1G AND 2G**  
NTS



**PLATE No. 0G**  
NTS




**TYPICAL FROG GAUGE PLATE**  
NTS




**TYPICAL FROG GAUGE PLATE**  
NTS

**GENERAL NOTES:**

- RIGHT HAND INSULATED GAUGE PLATE No. 1G AND 2G SHOWN, LEFT HAND PLATE IS OPPOSITE.
- GAUGE PLATES NO. 1 AND 2 ARE DESIGNED TO ACCOMMODATE SWITCH MACHINE CONNECTION ON EITHER END. DIMENSIONS MUST BE HELD TO SPECIFIED TOLERANCES.
- ALL SPECIAL TRACKWORK FASTENING PLATES SHALL BE INSULATED.
- GAUGE PLATES FOR FROG INSTALLATION SHALL INCLUDE WELD ON SHOULDERS FOR GUARD RAIL HOLD DOWN ASSEMBLY.



**FROGS**



**SWITCHES**

**GAUGE PLATE IDENTIFICATION STAMPING**

03/21/24 | 8:52 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD305.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	2/2024

SCALE: NTS  
 FILENAME: STD-KAD305  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024

**SOUND TRANSIT  
 STANDARD DRAWINGS  
 TRACKWORK**  
 SPECIAL TRACKWORK  
 GAUGE PLATES  
 BALLASTED




DRAWING No.:	<b>STD-KAD305</b>
FACILITY ID:	
SHEET No.:	REV: 1

TABLE A SPECIAL TRACKWORK DF FASTENER LENGTH	
TYPE	L
H2	32 1/2"
H3	38 1/4"
H4	48"
H8	66"
10GR1 OR 8GR1	VARIES
10GR2 OR 10GR2	VARIES

BILL OF MATERIAL	
QTY	DESCRIPTION
1	SPECIAL TRACKWORK DF FASTENER BODY (VULCANIZE BONDED W/ ELASTOMER)
A/R	RESILIENT RAIL CLIP (SEE NOTE 4)
A/R	LOCK BOLTS, NUTS AND WASHER
A/R	EPOXY-COATED ANCHOR INSERT
A/R	ANCHOR BOLT
A/R	ADJUSTABLE CLIP HOLDER (SEE NOTE 6)
A/R	BRACES
A/R	BRACE COVER PLATES
A/R	GALVANIZED STEBRACE COVER PLATES/EL HEIGHT ADJUSTMENT SHIMS OF 1/16", 1/8", 3/16" AND 1/4" THICKNESS (SEE NOTES 2 & 3)
A/R	EPOXY GROUT (FOR ALT. 1 INSTALLATION ONLY)


**GENERAL NOTES:**

1. AT THE OPTION OF THE INSTALLATION CONTRACTOR, ANCHOR INSERT SHALL BE INSTALLED BY EITHER THE DRILL AND GROUT METHOD OR CAST-IN-PLACE WITH SECOND POUR CONCRETE.
2. THE HEIGHT-ADJUSTMENT SHIMS SHALL PROVIDE 1/4 INCH MINIMUM HORIZONTAL PROJECTION BEYOND ALL SIDES OF THE FASTENER AT ANY INSTALLED POSITION.
3. TOTAL NUMBER OF SHIMS PLACED UNDER RAIL FASTENER BODY FOR HEIGHT ADJUSTMENT SHALL BE LIMITED TO A MAXIMUM OF TWO SHIMS AND A MAXIMUM TOTAL THICKNESS OF 1/2".
4. WHERE DF RAIL FASTENERS ARE LOCATED UNDER RAIL JOINTS, INSTALL PANDROL TYPE "E-2063" RAIL CLIPS OR APPROVED EQUALS.
5. BOLT HOLES DIAMETER AND NUMBER OF ANCHOR BOLTS REQUIRED FOR INSTALLATION SHALL BE AS RECOMMENDED BY THE SUPPLIER OF DF FASTENERS.
6. FIXED CLIPS ARE REQUIRED AT LOCATIONS THAT SPRING CLIP HOLDER OR SPRING CLIP WILL NOT FIT, THIS WILL OCCUR AT BOLTED JOINTS AND NARROW AREAS BETWEEN RAILS. CONTRACTOR WILL BE RESPONSIBLE TO LOCATE AREAS WHERE THESE INSTALLATIONS WILL OCCUR.
7. SHIM'S SLOTTED HOLES SHAPE AND SIZE SHALL BE AS RECOMMENDED BY THE SUPPLIER OF DF FASTENERS.




**DRILL AND GROUT METHOD  
INSTALLATION ALTERNATIVE 1 DETAIL** 1  
NTS

**CAST-IN-PLACE  
INSTALLATION ALTERNATIVE 2 DETAIL** 2  
NTS



**ELEVATION INSERT PLACEMENT TOLERANCE**  
NTS



**SHIM DETAIL**  
NTS

03/21/24 | 8:52 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD306.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE


SCALE: NTS  
FILENAME: STD-KAD306  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**


SPECIAL TRACKWORK  
RAIL FASTENER DETAILS  
DIRECT FIXATION

DRAWING No.:	<b>STD-KAD306</b>
FACILITY ID:	
SHEET No.:	REV:
	2


03/21/24 | 8:52 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD310.DWG




**9'-5" TEE GUARD RAIL**  
SCALE: 1" = 1'-0"




**SECTION A**  
SCALE: 6" = 1'-0"




**SECTION B**  
SCALE: 6" = 1'-0"



**SECTION C**  
SCALE: 6" = 1'-0"



**RAIL END BEVEL**  
SCALE: 6" = 1'-0"



**GUARD RAIL PLATE**  
(FOR BALLASTED TRACK ONLY)  
SCALE: 3" = 1'-0"

BILL OF MATERIAL	
9'-5" GUARDRAIL COMPLETE	
QTY	DESCRIPTION
1	9'-5" TEE RAIL DESIGN GUARDRAIL
1 EA	END BLOCKS, LEFT AND RIGHT HAND
1	ADJUSTABLE SEPARATOR BLOCK WITH SHIMS
4	BOLTS 1 3/8" DIA x 9" GRADE 8 WITH SQUARE HEAD, SQUARE NUTS, SPRING WASHERS, HEADLOCKS, AND "D" WASHERS
6	GUARDRAIL PLATES
24	7/8" DIA x 7" WASHERHEAD LAG SCREW
12	SPRING CLIPS
24	DOUBLE COIL SPRING WASHER (EXTRA WIDE)
24	2 1/4" OD x 0.938" ID x 0.160" STEEL WASHER
24	GLASS REINFORCED NYLON COLLAR THIMBLE

FOR BALLASTED TRACK ONLY

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD310  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT**  
STANDARD DRAWINGS  
TRACKWORK

9'-5" ADJUSTABLE GUARD RAIL


DRAWING No.:	STD-KAD310
FACILITY ID:	
SHEET No.:	REV:
	2




**13'-0" TEE GUARD RAIL**  
SCALE: 1" = 1'-0"




**SECTION A**  
SCALE: 6" = 1'-0"




**SECTION B**  
SCALE: 6" = 1'-0"



**SECTION C**  
SCALE: 6" = 1'-0"



**RAIL END BEVEL**  
SCALE: 6" = 1'-0"



**GUARD RAIL PLATE**  
(FOR BALLASTED TRACK ONLY)  
SCALE: 3" = 1'-0"

BILL OF MATERIAL		DESCRIPTION	QTY
13'-0" GUARDRAIL COMPLTE			
1		13'-0" TEE GUARDRAIL, PREMIUM RAIL	
1 EA		END BLOCKS, LEFT AND RIGHT HAND	
2		ADJUSTABLE SEPARATOR BLOCK WITH SHIMS	
6		BOLTS 1 3/8" DIA x 9" GRADE 8 WITH SQUARE HEAD, SQUARE NUTS, SPRING WASHERS, HEADLOCKS, AND "D" WASHERS	
6		GUARDRAIL PLATES	FOR BALLASTED TRACK ONLY
24		7/8" DIA x 7" WASHERHEAD LAG SCREW	
12		SPRING CLIPS	
24		DOUBLE COIL SPRING WASHER (EXTRA WIDE)	
24		2 1/4" OD x 0.938" ID x 0.160" STEEL WASHER	
24		GLASS REINFORCED NYLON COLLAR THIMBLE	

03/21/24 | 8:52 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD311.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD311
CONTRACT No.:	RTA/LR -
DATE:	2/2024


<b>SOUND TRANSIT</b>	
STANDARD DRAWINGS	
TRACKWORK	
13'-0" ADJUSTABLE GUARD RAIL	

DRAWING No.:	STD-KAD311
FACILITY ID:	
SHEET No.:	REV:
	2


03/21/24 | 8:52 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD312.DWG




**16'-6" TEE GUARD RAIL**  
SCALE: 1" = 1'-0"




**SECTION A**  
SCALE: 6" = 1'-0"




**SECTION B**  
SCALE: 6" = 1'-0"



**SEPERATOR BLOCK**  
**SECTION C**  
SCALE: 6" = 1'-0"



**RAIL END BEVEL**  
SCALE: 6" = 1'-0"



**GUARD RAIL PLATE**  
(FOR BALLASTED TRACK ONLY)  
SCALE: 3" = 1'-0"

BILL OF MATERIAL	
16'-6" GUARDRAIL COMPLETE	
QTY	DESCRIPTION
1	16'-6" TEE RAIL DESIGN GUARD RAIL
1 EA	END BLOCKS, LEFT AND RIGHT HAND
3	ADJUSTABLE SEPARATOR BLOCK WITH SHIMS
8	BOLTS 1 3/8" DIA x 9" GRADE 8 WITH SQUARE HEAD, SQUARE NUTS, SPRING WASHERS, HEADLOCKS, AND "D" WASHERS
9	GUARDRAIL PLATES
32	7/8" DIA x 7" WASHERHEAD LAG SCREW
18	SPRING CLIPS
32	DOUBLE COIL SPRING WASHER (EXTRA WIDE)
32	2 1/4" OD x 0.938" ID x 0.160" STEEL WASHER
32	GLASS REINFORCED NYLON COLLAR THIMBLE

FOR BALLASTED TRACK ONLY

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: AS NOTED  
 FILENAME: STD-KAD312  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024


**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
 TRACKWORK  
 16'-6" ADJUSTABLE GUARD RAIL

DRAWING No.:	<b>STD-KAD312</b>
FACILITY ID:	
SHEET No.:	REV:
	2




- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION OR THICK WEB SECTION.
  - RAIL END DRILLING, BAR PUNCHING AND TRACK BOLTS SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX HOLE JOINT BARS.
  - ALL STOCK, SWITCH POINT, AND CLOSURE RAIL SHALL BE FABRICATED FROM HEAD HARDENED RAIL.
  - FOR ADDITIONAL DETAILS OF GAUGE PLATES SEE DRAWING STD-KAD305.
  - RAIL ENDS FOR JOINTED TRACK SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03 WITH DRILLED RAIL ENDS.
  - FOR RH TURNOUT, LH POINT AND RH STOCK RAILS ARE CURVED, RH POINT AND LH STOCK RAILS ARE STRAIGHT. FOR LH TURNOUT, RH POINT AND LH STOCK RAILS ARE CURVED, LH POINT AND RH STOCK RAILS ARE STRAIGHT.
  - RAIL CLIPS OMITTED FROM CENTER OF PLATES S3.
  - FINAL SWITCH PLATE NUMBERING, SPACING AND DIMENSIONS SHALL BE AS PER TURNOUT FABRICATION DRAWINGS.


**13'-0" CURVED SPLIT SWITCH**  
SCALE: 3/4" = 1'-0"




**OUTSIDE PLATE**




**INSIDE PLATE**



**TANGENT SIDE PLATES**  
(SEE NOTE 7)



**CURVED SIDE PLATES**  
(SEE NOTE 7)



**PLATES 8 THRU 10**

**SIDE VIEW (TYP)**

**HEEL PLATES**  
SCALE: 1" = 1'-0"

BILL OF MATERIAL	
13'-0" CURVED INSULATED SPLIT SWITCH	
QTY	DESCRIPTION
1 EA	13'-0" CURVED SWITCH POINTS, LEFT AND RIGHT HAND, COMPLETE WITH 1-CURVED AND 1-STRAIGHT WITH 1 1/4" REINFORCING BAR GAUGE SIDE OR THICK WEB SECTION AND SWITCH POINT STOP. (POINT DETAIL 5100 PER AREMA STANDARD PLAN No. 221-08) SEE NOTE 6.
1	32'-6" BENT AND CURVED UNDERCUT STOCK RAIL RH OR LH SEE NOTE 6
1	39'-0" STRAIGHT UNDERCUT STOCK RAIL RH OR LH SEE NOTE 6
2	INSULATED VERTICAL SWITCH RODS WITH TYPE "MJ" CLIPS, No.1 ROD WITH BASKET FOR 1 1/4" OPERATING ROD
1 EA	FIVE BOLT RH & LH HEEL BLOCK ASSEMBLIES COMPLETE
1 EA	INSULATED GAUGE PLATES 0G, 1G, AND 2G COMPLETE WITH ADJUSTABLE BRACES
4	BRACE SLIDE PLATES No. 1 COMPLETE WITH ADJUSTABLE BRACES
6	PLAIN SLIDE PLATES No. 1-P
1 EA	2-TIE HEEL PLATE 2RL AND 2RR FOR RH TURNOUT OR 2LL AND 2LR FOR LH TURNOUT

FOR BALLASTED TRACK ONLY

03/21/24 | 8:52 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD315.DWG

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

2	2/2024	2024 REVISED STANDARD DRAWINGS
1	8/2019	REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013	NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: AS NOTED  
FILENAME: STD-KAD315  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
TRACKWORK  
13'-0" CURVED SPLIT SWITCH  
BALLASTED


DRAWING No.:	<b>STD-KAD315</b>
FACILITY ID:	
SHEET No.:	REV: 2





**13'-0" CURVED SPLIT SWITCH**  
SCALE: 1/2" = 1'-0"

DIRECT FIXATION  
STANDARD RESTRAINING  
RAIL FASTENER DETAILS  
(SEE STD-KAD100)



**GENERAL NOTES:**

- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION OR THICK WEB SECTION.
- ALL STOCK, SWITCH POINT AND CLOSURE RAILS ARE FABRICATED FROM HIGH STRENGTH RAIL.
- FOR RH TURNOUT, LH POINT AND RH STOCK RAILS ARE CURVED; RH POINT AND LH STOCK RAILS ARE STRAIGHT. FOR LH TURNOUT, RH POINT AND LH STOCK RAILS ARE CURVED; LH POINT AND RH STOCK RAILS ARE STRAIGHT.
- THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES, AND MAY BE REVISED BY THE CONTRACTOR. THE FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR.
- DIMENSION OF STOCK RAIL EXTENSION FROM POINT OF SWITCH WILL VARY DEPENDING ON LOCATION OF INSULATED JOINT ON EACH SIDE OF THE TURNOUT.
- REBAR DETAILS SHOWN ARE FOR CONCRETE PLINTH SIZED AND DESIGNED FOR TWO SPECIAL TRACKWORK DF FASTENERS. REBARS AND DOWELS DETAILS WILL BE TYPICAL FOR ALL LARGER CONCRETE PLINTHS WITH MORE THAN TWO SPECIAL TRACKWORK DF FASTENERS.

BILL OF MATERIAL	
13'-0" CURVED INSULATED SPLIT SWITCH	
QTY	DESCRIPTION
1 EA	13'-0" SWITCH POINTS, MADE FROM 44'-3 7/8" (CURVED) AND 44'-0 9/16" (STRAIGHT) LONG RAIL, RH AND LH COMPLETE WITH 1-CURVED AND 1-STRAIGHT WITH 1 1/4" REINFORCING BAR GAUGE SIDE OR THICK WEB SECTION (POINT DETAIL 5100 PER AREMA STANDARD PLAN No. 221-08), SEE NOTE 4.
1 EA	39'-0" LONG UNDERCUT STOCK RAILS RH AND LH 1-CURVED AND 1-STRAIGHT
3	INSULATED VERTICAL SWITCH RODS, No. 1 TO No. 3 WITH TYPE "MJ" CLIPS
2	FLOATING HEEL BLOCKS
4	SWITCH POINT STOPS
A/R	STANDARD SPECIAL TRACKWORK FASTENERS
A/R	SPECIAL TRACKWORK FASTENER

03/21/24 | 8:52 AM | HARRISBK  
C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD316.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD WDGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: DATE: REVIEWED BY: DATE: 2/2024

SCALE: AS NOTED  
FILENAME: STD-KAD316  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

13'-0" CURVED SPLIT SWITCH  
DIRECT FIXATION TRACK

DRAWING No.: **STD-KAD316**  
FACILITY ID:  
SHEET No.: REV: 2

03/27/24 | 7:02 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD320.DWG

uncontrolled document from soundtransit.org





**19'-6\"/>**

- GENERAL NOTES:**
- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION OR THICK WEB SECTION.
  - 19'-6\"/>
  - ALL STOCK, SWITCH POINT AND CLOSURE RAILS SHALL BE FABRICATED FROM HEAD HARDENED RAIL.
  - FOR DETAILS OF GAUGE PLATES SEE DRAWING KAD305.
  - FOR RH TURNOUT, LH POINT AND RH STOCK RAILS ARE CURVED; RH POINT AND LH STOCK RAILS ARE STRAIGHT. FOR LH TURNOUT, RH POINT AND LH STOCK RAILS ARE CURVED; LH POINT AND RH STOCK RAILS ARE STRAIGHT.
  - SWITCH PLATE NUMBERING IS AS FOLLOWS: "8" OR "10" TURNOUT NUMBER, "S" SWITCH, "2" THROUGH "13" FOR POSITION FROM HEEL OF SWITCH TO END OF LONG PLATES, "R" FOR RIGHT HAND TURNOUT (OR "L" FOR LEFT HAND TURNOUT), "R" FOR RIGHT SIDE OF SWITCH (OR "L" FOR LEFT SIDE OF SWITCH) IF APPROPRIATE.
  - ON THIS DRAWING, SWITCH PLATES ARE NUMBERED AND ILLUSTRATED FOR RIGHT HAND SWITCHES. LEFT HAND SWITCH PLATES FABRICATED TO OPPOSITE HAND AND DIMENSIONS DETERMINED BY MODIFYING TABLE AS FOLLOWS: SUBSTITUTE SUFFIXES "LL" FOR "RR" AND "LR" FOR "RL" ON RISER PLATES AND LONG LEVEL PLATES AND "L" FOR "R" ON SHORT LEVEL PLATES.
  - BOLTED RAIL STOPS ARE APPLICABLE TO RIGHT OR LEFT HAND TURNOUT. "X" DENOTES THAT HAND OF TURNOUT IS IMMATERIAL. HOWEVER, SIDE OF SWITCH IS SIGNIFICANT, HENCE "L" AND "R".
  - FOR INSTALLATION OF 19'-6\"/>

SWITCH PLATE DATA								
	PLATE No.	A	B	C	D	L	X OR H	
NO. 10 TURNOUT	RISER PLATES	10S2RL & 10S2RR	12.11	12.39	6.48	6.76	28	0.00
		10S3RL & 10S3RR	12.99	13.29	7.36	7.66	28	0.06
		10S4RL & 10S4RR	13.93	14.25	8.30	8.62	30	0.12
		10S5RL & 10S5RR	14.93	15.27	9.30	9.64	30	0.19
		10S6R	15.99	16.35	10.36	10.72	32	
	LEVEL PLATES	10S7R	17.11	17.49	11.47	11.86	32	
		10S8R	18.32	18.69	12.69	13.06	34	
		10S9R	19.52	19.95	13.89	14.32	34	
		10S10R	20.80	21.25	15.15	15.60	35	11"
		10S11R	22.11	22.60	16.50	16.95	37	12 1/4"
NO. 8 TURNOUT	RISER PLATES	8S2RL & 8S2RR	12.11	12.39	6.48	6.76	28	0.00
		8S3RL & 8S3RR	13.02	13.34	7.39	7.72	28	0.06
		8S4RL & 8S4RR	14.03	14.39	8.40	8.76	30	0.12
		8S5RL & 8S5RR	15.14	15.54	9.51	9.90	30	0.19
		8S6R	16.36	16.78	10.73	11.15	32	
	LEVEL PLATES	8S7R	17.67	18.13	12.04	12.49	34	
		8S8R	19.08	19.57	13.45	13.94	34	
		8S9RL	20.54	21.06	14.90	15.42	35	
		8S9RR	20.66	21.18	15.02	15.55	35	
		8S10RL	22.14	22.70	16.50	17.06	37	11 1/4"
8S10RR	22.28	22.84	16.64	17.20	37	11 1/4"		
8S11RL	23.85	24.44	18.21	18.80	39	12 1/4"		
8S11RR	24.00	24.60	18.36	18.96	39	12 1/4"		
8S12RL	25.65	26.28	20.01	20.63	41	13"		
8S12RR	25.82	26.45	20.81	20.81	41	13"		

MEASUREMENTS ARE IN INCHES SEE NOTES 6 & 7

BILL OF MATERIALS		
QTY	DESCRIPTION	
1 EA	19'-6\"/>	
1 EA	39'-0\"/>	
4	INSULATED VERTICAL SWITCH RODS, No. 1 TO No. 4 WITH TYPE "MJ" CLIPS	
1 EA	INSULATED GAUGE PLATES 0G, 1G AND 2G COMPLETE WITH ADJUSTABLE BRACES	
10	BRACE SLIDE PLATES No.1 COMPLETE WITH ADJUSTABLE BRACES	
10	PLAIN SLIDE PLATES No.1-P	
2	FLOATING HEEL BLOCKS	
2	SWITCH POINT STOPS	
1 EA	RISER PLATES No. 2L, 3L, 4L, 5L, 2R, 3R, 4R AND 5R	
2 EA	TURNOUT PLATES No. 6 THRU 13	
1 EA	PLATE STOPS 3L, 3R, 4L, 4R, 5L, & 5R	
12	3/4" X 2 1/4" MACHINE BOLTS WITH SPRING WASHERS	
1 EA	RISER PLATES No. 2L, 3L, 4L, 5L, 2R, 3R, 4R AND 5R	
2 EA	TURNOUT PLATES No. 6 THRU 12	
1 EA	PLATE STOPS 3L, 3R, 4L, 4R, 5L, & 5R	
12	3/4" X 2 1/4" MACHINE BOLTS WITH SPRING WASHERS	



BOLTED RAIL STOP DATA					
	STOP NO.	A	B	C	D
NO. 10 TO	10S3XL 10S3XR	1.73	2.04	0.25 0.44	0.44 0.25
	10S4XL 10S4XR	2.67	3.00	0.25 0.37	0.37 0.25
	10S5XL 10S5XR	3.67	4.02	0.25 0.31	0.31 0.25
NO. 8 TO	8S3XL 8S3XR	1.7700	2.09	0.25 0.44	0.44 0.25
	8S4XL 8S4XR	2.78	3.14	0.25 0.37	0.37 0.25
	8S5XL 8S5XR	3.89	4.28	0.25 0.31	0.31 0.25

MEASUREMENTS ARE IN INCHES SEE NOTE 8

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
			2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

19'-6\"/>

DRAWING No.: **STD-KAD320**  
 FACILITY ID:  
 SHEET No.: REV: 2




**19'-6" CURVED SPLIT SWITCH**  
SCALE: 1/2" = 1'-0"

TYPICAL FOR SPECIAL TRACKWORK PLINTH CONCRETE LAYOUT. PLINTH CONCRETE TO PROJECT 3" BEYOND FASTENER EDGES ON ALL SIDES EXCEPT AT SWITCH ROD OPENING AS SHOWN

STANDARD SPECIAL TRACKWORK DF PLATES (SEE DWG STD-KAD100)

**GENERAL NOTES:**

- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION OR THICK WEB SECTION.
- 19'-6" SWITCH TO BE INSTALLED AT No. 8 OR No. 10 FULLY WELDED TURNOUTS.
- ALL STOCK, SWITCH POINT AND CLOSURE RAILS ARE FABRICATED FROM HIGH STRENGTH RAIL.
- FOR RH TURNOUT, LH POINT AND RH STOCK RAILS ARE CURVED; RH POINT AND LH STOCK RAILS ARE STRAIGHT. FOR LH TURNOUT, RH POINT AND LH STOCK RAILS ARE CURVED; LH POINT AND RH STOCK RAILS ARE STRAIGHT.
- THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES, AND MAY BE REVISED BY THE CONTRACTOR. THE FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR.
- DIMENSION OF STOCK RAIL EXTENSION FROM POINT OF SWITCH WILL VARY DEPENDING ON LOCATION OF INSULATED JOINT ON EACH SIDE OF THE TURNOUT.
- REBARS DETAILS SHOWN ARE FOR CONCRETE PLINTH SIZED AND DESIGNED FOR TWO SPECIAL TRACKWORK DF FASTENERS. REBARS AND DOWELS DETAILS WILL BE TYPICAL FOR ALL LARGER CONCRETE PLINTHS WITH MORE THAN TWO SPECIAL TRACKWORK DF FASTENERS.



BILL OF MATERIAL	
19'-6" CURVED INSULATED SPLIT SWITCH	
QTY	DESCRIPTION
1 EA	19'-6" SWITCH POINTS, MADE FROM 37'-4" LONG RAIL, RH AND LH COMPLETE WITH 1-CURVED AND 1-STRAIGHT WITH 1/2" & 1 1/4" THICK REINFORCING BAR OR THICK WEB SECTION (POINT DETAIL 5100 PER AREMA STANDARD PLAN No. 221-08), SEE NOTE 4.
1 EA	39'-0" LONG UNDERCUT STOCK RAILS RH AND LH 1-CURVED AND 1-STRAIGHT
4	INSULATED VERTICAL SWITCH RODS, No. 1 TO No. 4 WITH TYPE "MJ" CLIPS
4	SWITCH POINT STOPS
A/R	STANDARD SPECIAL TRACKWORK FASTENERS
A/R	SPECIAL TRACKWORK FASTENER

03/21/24 | 8:52 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\CIVIL-STRUCTURE\STD-KAD321.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DWGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD321  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**

19'-6" CURVED SPLIT SWITCH DIRECT FIXATION TRACK


DRAWING No.: **STD-KAD321**  
FACILITY ID:  
SHEET No.: REV:

**GENERAL NOTES:**

1. FOR REINFORCING BAR DETAILS SEE AREMA PLAN 325-12.
2. ALL SPECIAL TRACKWORK TURNOUT PLATES MUST BE INSULATED.
3. SOME OR ALL SWITCH POINTS MAY BE FURNISHED IN 115 TW (THICK WEB) RAIL INSTEAD OF STANDARD 115 RE. THICK WEB RAIL SHALL BE BETHLEHEM STEEL BSCO. 115 TW RAIL SECTION (AS SHOWN) OR APPROVED EQUAL.
4. HEEL BLOCK - CAST STEEL, CLASS B, HARD. 115 TW (THICK WEB) RAIL INSTEAD OF STANDARD 115 RE. THICK WEB RAIL SHALL BE BETHLEHEM STEEL BSCO. 115 TW RAIL SECTION (AS SHOWN) OR APPROVED EQUAL.




**HEEL JOINT ASSEMBLY**  
NTS



**BRACE SLIDE PLATE NO. 1**  
SCALE: 3" = 1'-0"

**PLAIN SLIDE PLATE NO. 1P**  
SCALE: 3" = 1'-0"



**SECTION A**  
NTS

03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD325.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-


SCALE: AS NOTED	
FILENAME: STD-KAD325	
CONTRACT No.:	
RTA/LR -	
DATE:	
2/2024	

<b>SOUND TRANSIT</b> <b>STANDARD DRAWINGS</b> TRACKWORK MISCELLANEOUS SWITCH DETAILS	
--	--


DRAWING No.:	<b>STD-KAD325</b>
FACILITY ID:	
SHEET No.:	REV:
	2

03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD350.DWG

uncontrolled document from soundtransit.org



**NO. 5 TURNOUT PLAN**  
SCALE: 1/4" = 1'-0"



**RAIL LAYOUT DIAGRAM**  
SCALE: 1/8" = 1'-0"

- GENERAL NOTES:**
- DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL.
  - RAIL AND COMPONENTS SHALL CONFORM TO 115RE RAIL SECTION.
  - ALL RAILS (AS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM) SHALL BE HIGH STRENGTH RAIL.
  - LEFT HAND TURNOUT SHALL BE OPPOSITE TO THAT SHOWN.
  - RAIL END DRILLING SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX HOLE JOINT BARS FOR JOINTED TRACK EXCEPT FOR INSULATED JOINTS WHICH SHALL BE DRILLED PER MANUFACTURER'S RECOMMENDATION.
  - RAIL ENDS SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03 FOR JOINTED TRACK.
  - INSULATED STANDARD PLATES SHALL BE FURNISHED FOR ALL TIES WHERE SPECIAL TRACKWORK PLATES ARE NOT REQUIRED.
  - ALL SPECIAL TRACKWORK FASTENING PLATES SHALL BE INSULATED.
  - NO ALLOWANCE HAS BEEN MADE FOR GAPS OR INSULATED END POSTS IN COMPUTING LENGTHS OF RAILS SHOWN.
  - FINAL LOCATIONS OF (SHOP FABRICATED) BONDED INSULATED JOINTS WILL DEPND ON THE LOCATION OF TURNOUT INSTALLATION. VERIFY FINAL LOCATION OF INSULATED JOINTS WITH THE RESIDENT ENGINEER BEFORE FABRICATION OF TURNOUT.
  - WITHIN THE INDICATED AREA, INCREASE THE LENGTH OF CONCRETE TIE CONTINUOUSLY WITH THE REQUIRED MINIMUM LENGTH OF 25 3/4" FROM THE GAUGE SIDE OF THE MOST OUTSIDE RUNNING RAIL TO THE END OF THE TIE. IN CASE OF SUCH TIE SETTING IS NOT AVAILABLE, INCREASE TIE LENGTH IN A FAMILY STYLE IS ALLOWED.

BILL OF MATERIAL No. 5 BALLASTED TURNOUT		
QTY	DESCRIPTION	DWG No.
1 ASSY.	13'-0" CURVED SPLIT SWITCH COMPLETE	STD-KAD315
1 ASSY.	NO. 5 RBM FROG COMPLETE	STD-KAD351
2 ASSY.	9'-5" ADJUSTABLE GUARD RAILS COMPLETE	STD-KAD310
A/R	STRAIGHT CLOSURE RAIL	-
A/R	CURVED CLOSURE RAIL	-
A/R	STOCK RAILS	-
1 SET	SWITCH TIES	-
A/R	PANDROL NO. 2055 "E" CLIPS, INCL. MOD. "E" CLIPS	-
A/R	INSULATED LAG SCREW ASSEMBLIES	-
A/R	HIGH DENSITY POLYETHLENE PADS (VARIOUS SIZES)	-
8	THERMITE WELD	-
A/R	STANDARD PANDROL TIE PLATES FOR "E" CLIPS (SEE NOTE 7)	-

TURNOUT DATA		
FROG	NUMBER	5
	ANGLE	11° 25' 16"
	TOE LENGTH	4'-6"
	HEEL LENGTH	6'-4"
	TOTAL LENGTH	10'-10"
	TOE SPREAD	10 7/32"
SWITCH	HEEL SPREAD	15 5/8"
	LENGTH OF CURVED SWITCH RAIL	13'-0"
	HEEL SPREAD	6 1/4"
	HEEL ANGLE	2° 54' 00"
TURNOUT CURVE	ANGLE AT POINT	1° 41' 31"
	THICKNESS AT POINT	0"
	SWITCH RAIL RADIUS	616.55'
ACTUAL LEAD		44'-6 1/2"
STRAIGHT CLOSURE RAIL DISTANCE		27'-2"
CURVED CLOSURE RAIL DISTANCE		26'-6 3/8"
TURNOUT CURVE	CENTER LINE RADIUS	188.10'
	DEGREE OF CURVE	30° 40' 49"
TANGENT ADJACENT TOE OF FROG		11 1/2"

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:


SUBMITTED BY: DATE: REVIEWED BY: DATE:

LINE IS 1" AT FULL SCALE


SCALE: AS NOTED  
FILENAME: STD-KAD350  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**  
  
NO. 5 TURNOUT  
BALLASTED  
13'-0" CURVED SPLIT SWITCH

DRAWING No.: **STD-KAD350**  
FACILITY ID:  
SHEET No.: REV: 2



**PLAN**  
SCALE: 3/4" = 1'-0"



**FLARE DETAIL**  
SCALE: 1 1/2" = 1'-0"

**GENERAL NOTES:**

1. FROG RAIL TO BE 115 RE PREMIUM RAIL.
2. FLANGWAYS TO BE 1 5/8" WIDE BY 1 7/8" DEEP.
3. RAIL END DRILLING, BAR PUNCHING AND TRACK BOLTS SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX-HOLE JOINT BARS FOR JOINTED TRACK EXCEPT FOR FROG HEEL LEGS, WHICH SHALL BE 5 HOLE JOINTS.
4. RAIL ENDS SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03.
5. RIGHT HAND FROG SHOWN. LEFT HAND FROG OPPOSITE.
6. FOR ADDITIONAL DETAILS OF GUARD RAILS SEE DRAWING NO. STD-KAD310.
7. THE DESIGN CONFIGURATION AND DIMENSIONS OF FROG AND FROG PLATES ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DESIGN CONFIGURATION AND DIMENSIONS WILL BE BY CONTRACTOR'S FABRICATOR OF TURNOUT, SUBJECT TO APPROVAL BY RESIDENT ENGINEER.
8. ALL SPECIAL TRACKWORK FASTENING PLATES SHALL BE INSULATED.
9. SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 5'-6" SPARE FROG HEEL LENGTH = 7'-4")


BILL OF MATERIAL NO. 5 RAILBOUND MANGANESE FROG	
QTY	DESCRIPTION
1 EA	NO. 5 RAILBOUND MANGANESE FROG COMPLETE (PER AREMA STD PLAN 322-59) MODIFIED AS SHOWN
A/R	FROG PLATES, (5RFI TO 5RFII) (FOR BALLASTED TRACK ONLY)

03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD351.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: DATE: REVIEWED BY: DATE:




SCALE: AS NOTED  
FILENAME: STD-KAD351  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK  
NO. 5 RAILBOUND MANGANESE FROG  
BALLASTED

DRAWING No.: **STD-KAD351**  
FACILITY ID:  
SHEET No.: REV: 2


03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\Standard Drawings\Civil-Struct\STD-KAD355.DWG

uncontrolled document from soundtransit.org



**NO. 5 EQUILATERAL PLAN**

SCALE: 1/4" = 1'-0"



**RAIL LAYOUT DIAGRAM**

NTS

BILL OF MATERIAL PRIMARY CONCRETE SWITCH TIES	
LENGTH	QTY
9'-0"	10
10'-0"	7
11'-0"	3
12'-0"	6 (SEE NOTE 10)
13'-0"	4
14'-0"	3
15'-0"	3
16'-0"	3
17'-0"	2
18'-0"	2
TOTAL	43

BILL OF MATERIAL No. 5 EQUILATERAL BALLASTED TURNOUT		
QTY	DESCRIPTION	DWG No.
1 ASSY	No. 5 EQUILATERAL 13'-0" CURVED SPLIT SWITCH COMPLETE	STD-KAD357
1 ASSY	No. 5 EQUILATERAL RBM FROG COMPLETE	STD-KAD358
2 ASSY	11'-5" ADJUSTABLE GUARD RAILS COMPLETE	STD-KAD410
A/R	CLOSURE RAIL WITH BONDED INSULATED JOINT	-
A/R	CLOSURE RAIL WITHOUT BONDED INSULATED JOINT	-
A/R	STOCK RAIL WITH BONDED INSULATED JOINT	-
A/R	STOCK RAIL WITHOUT BONDED INSULATED JOINT	-
1 SET	SWITCH TIES	-
A/R	PANDROL NO. 2055 "E" CLIPS, INCL. MOD. "E" CLIPS FOR IJ	-
A/R	INSULATED LAG SCREW ASSEMBLIES	-
A/R	HIGH DENSITY POLYETHYLENE PADS (VARIOUS SIZES)	-
8	THERMITE WELD	-
A/R	STANDARD SPECIAL TRACKWORK PLATES (SEE NOTE 7)	-

**GENERAL NOTES:**

- DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL.
- RAIL AND COMPONENTS SHALL CONFORM TO 115RE RAIL SECTION.
- ALL RAILS (AS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM) SHALL BE PREMIUM RAIL.
- RAIL END DRILLING SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX HOLE JOINT BARS FOR JOINTED TRACK EXCEPT FOR INSULATED JOINTS WHICH SHALL BE DRILLED PER MANUFACTURER'S RECOMMENDATION.
- RAIL ENDS SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03 FOR JOINTED TRACK.
- INSULATED STANDARD PLATES SHALL BE FURNISHED FOR ALL TIES WHERE SPECIAL TRACKWORK PLATES ARE NOT REQUIRED.
- ALL SPECIAL TRACKWORK FASTENING PLATES SHALL BE INSULATED.
- NO ALLOWANCE HAS BEEN MADE FOR GAPS OR INSULATED END POSTS IN COMPUTING LENGTHS OF RAILS SHOWN.
- BONDED INSULATED JOINTS ARE NOT REQUIRED IN SOME TURNOUT INSTALLATION. SEE RESPECTIVE CONTRACT'S TRACK CHART DRAWINGS FOR DETAILS.
- HEADBLOCK TIES FOR POWER SWITCH MACHINE SHALL BE 9"X9" IN SECTION AND SHALL BE DAPPED AS REQUIRED FOR SWITCH MACHINE.
- WITHIN THE INDICATED AREA, INCREASE THE LENGTH OF CONCRETE TIE CONTINUOUSLY WITH THE REQUIRED MINIMUM LENGTH OF 25 3/4" FROM THE GAUGE SIDE OF THE MOST-OUTSIDE RUNNING RAIL TO THE END OF THE TIE. IN CASE OF SUCH SETTING IS NOT AVAILABLE, INCREASE TIE LENGTH IN A FAMILY STYLE IS ALLOWED.

**LEGEND:**

- F FIELD FABRICATED
- II INSULATED JOINT
- S SHOP FABRICATED
- II INSULATED JOINT
- I WELDED JOINT

TURNOUT DATA	
NUMBER	5
ANGLE	11° 25' 16"
TOE LENGTH	4'-6"
HEEL LENGTH	6'-4"
TOTAL LENGTH	10'-10"
TOE SPREAD	10 7/32"
HEEL SPREAD	15 5/8"
LENGTH OF CURVED SWITCH RAIL	13'-0"
HEEL SPREAD	6 1/4"
ANGLE AT POINT	0° 50' 46"
THICKNESS AT POINT	0"
SWITCH RAIL RADIUS	1233.10'
ACTUAL LEAD	44'-6 1/2"
STRAIGHT CLOSURE RAIL	27'-0 1/2"
CURVED CLOSURE RAIL	27'- 1 7/16"
CENTER LINE RADIUS	352.80'
DEGREE OF CURVE	16° 14' 25"
CENTRAL ANGLE	4° 15' 38"
TANGENT ADJACENT TOE OF FROG	0"

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GHUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE:	AS NOTED
FILENAME:	STD-KAD355
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 5 EQUILATERAL TURNOUT  
BALLASTED  
13'-0" CURVED EQUILATERAL SPLIT SWITCH

DRAWING No.:	<b>STD-KAD355</b>
FACILITY ID:	
SHEET No.:	REV:
	2


03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD356.DWG



**NO. 5 EQUILATERAL TURNOUT**  
SCALE: 1/4" = 1'-0"

- GENERAL NOTES:**
- RAIL AND COMPONENTS CONFORM TO THE 115RE RAIL SECTION.
  - FINAL LOCATIONS OF BONDED INSULATED JOINTS WILL DEPEND ON THE LOCATION OF TURNOUT INSTALLATION. VERIFY FINAL LOCATION OF INSULATED JOINTS WITH THE RESIDENT ENGINEER BEFORE FABRICATION OF THE TURNOUT.
  - DIMENSIONS OF STOCK RAIL EXTENSION FROM POINT OF SWITCH WILL VARY DEPENDING ON LOCATION OF INSULATED JOINT ON EACH SIDE OF THE TURNOUT.
  - RAIL CANT TRANSITION FROM ZERO CANT TO 1:40 CANT TO BE PERFORMED IN PLINTH. ZERO CANT FASTENERS SHALL BE USED THROUGHOUT THE TRANSITION.

- LEGEND:**
- STANDARD DF FASTENER, NO CANT
  - STANDARD DF FASTENER 1:40 CANT
  - DF SPECIAL TRACKWORK FASTENER



**RAIL LAYOUT DIAGRAM**  
SCALE: 1/8" = 1'-0"

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DWGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_  
REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_


SCALE: AS NOTED  
FILENAME: STD-KAD356  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 5 EQUILATERAL TURNOUT  
13'-0" CURVED EQUILATERAL SPLIT SWITCH  
DIRECT FIXATION


DRAWING No.: **STD-KAD356**  
FACILITY ID:  
SHEET No.: 1 REV: 1





- GENERAL NOTES:**
1. RAIL AND COMPONENTS SHALL COMFORM TO 115 RE RAIL SECTION.
  2. ALL PLATE LAYOUTS AND DIMENSIONS ARE FOR INFORMATION ONLY. FINAL PLATE LAYOUTS AND DIMENSIONS SHALL BE BY CONTRACTOR AND APPROVED BY RESIDENT ENGINEER.
  3. FOR RAIL FASTENER DETAILS IN DIRECT FIXATION TRACK SEE DRAWING STD-KAD306.

**13'-0" EQUILATERAL SPLIT SWITCH TRACK**  
SCALE: 3/4" = 1'-0"



**PLATE STOP DETAILS**  
(SEE NOTE 2)  
NTS


**PLATE DETAILS (BALLASTED)**  
(SEE NOTE 2)  
SCALE: 1 1/2"=1'-0"

BILL OF MATERIAL	
NO. 5 EQ. INSULATED SPLIT SWITCH COMPLETE	
QTY	DESCRIPTION
1-EA	13'-0" SWITCH POINTS. MADE FROM 42'-5 13/16" LONG RAIL RH AND LH COMPLETE WITH REINFORCING BARS. HEEL BLOCK, AND STOP ATTACHED (POINT DETAIL 5100 PER APEMA STANDARD PLAN No. 221-08
1	46'-3/4" LONG UNDERCUT STOCK RAILS. RH AND LH.
2	INSULATED VERTICAL SWITCH RODS, No. 1 ROD WITH BASKET FOR 1 1/4"Ø ROD
1-EA	INSULATED GAUGE PLATE OG, 1GE AND 2GE COMPLETE WITH ADJUSTABLE BRACES.
4	BRACES SLIDE PLATES No. 1 COMPLETE WITH ADJUSTABLE BRACES.
6	PLAN SLIDE PLATES No. 1P
2-EA	TURNOUT PLATES No. 2, 3, 4 AND 5
2-EA	TURNOUT PLATES No. 6, 7, AND 8
A/R	INSULATED LAG SCREW ASSEMBLY.
1-EA	PLATE STOPS 3S AND 4S
6	PLATE STOP G
20	3/4" X 2 1/4" MACHINE BOLTS

03/21/24 | 8:53 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD357.DWG

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


AHJ:		PACKAGE #	
SUBMITTED BY:	DATE:	SCALE:	AS NOTED
REVIEWED BY:	DATE:	FILENAME:	STD-KAD357
		CONTRACT No.:	RTA/LR -
		DATE:	2/2024




**SOUND TRANSIT**  
STANDARD DRAWINGS  
TRACKWORK

NO. 5 EQUILATERAL SWITCH  
13'-0" CURVED SPLIT SWITCH  
BALLASTED

DRAWING No.:	<b>STD-KAD357</b>
FACILITY ID:	
SHEET No.:	REV: 2



**PLAN**  
SCALE: 3/4" = 1'-0"



**FLARE DETAIL**  
SCALE: 1 1/2" = 1'-0"

- GENERAL NOTES:**
1. FROG RAIL TO BE 115 RE PREMIUM RAIL.
  2. FLANGEWAYS TO BE 1 5/8" WIDE BY 1 7/8" DEEP.
  3. RAIL END DRILLING, BAR PUNCHING AND TRACK BOLTS SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX-HOLE JOINT BARS FOR JOINTED TRACK EXCEPT FOR FROG HEEL LEGS, WHICH SHALL BE 5 HOLE JOINTS.
  4. RAIL ENDS SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03.
  5. THE DESIGN CONFIGURATION AND DIMENSIONS OF FROG AND FROG PLATES ARE FOR INFORMATIONAL PURPOSES, FINAL DESIGN CONFIGURATION AND DIMENSIONS WILL BE BY CONTRACTOR'S FABRICATOR OF TURNOUT SUBJECT TO APPROVAL BY RESIDENT ENGINEER.
  6. FOR ADDITIONAL DETAILS OF GUARD RAILS SEE DRAWING STD-KAD310.
  7. SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 5'-6" SPARE FROG HEEL LENGTH = 7'-4")
  8. ALL SPECIAL TRACKWORK FASTENING SHALL BE INSULATED.


BILL OF MATERIAL NO. 5 EQ. INSULATED SPLIT SWITCH COMPLETE	
QTY	DESCRIPTION
1-EA	NO. 5 RAILBOUND MANGANESE FROG COMPLETE (PER AREMA STD PLAN 322-59) MODIFIED AS SHOWN
A/R	FROG PLATES. (SRF1 TO SRF11)

03/21/24 | 8:53 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD358.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	6/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:


SUBMITTED BY:      DATE:      REVIEWED BY:      DATE:



SCALE:  
AS NOTED  
FILENAME:  
STD-KAD358  
CONTRACT No.:  
RTA/LR -  
DATE:  
2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK  
NO. 5 EQUILATERAL RBM FROG  
BALLASTED

DRAWING No.:  
**STD-KAD358**  
FACILITY ID:  
SHEET No.:      REV:  
2




**NO. 6 DF DOUBLE CROSSOVER 15'-9" TC**  
SCALE: 3/16" = 1'-0"

- LEGEND:**
- STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - STANDARD DF FASTENER (1:40 CANT)
  - SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - FIELD FABRICATED INSULATED JOINT
  - SHOP FABRICATED INSULATED JOINT
  - WELDED JOINT

- GENERAL NOTES:**
1. RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  2. ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAILS.
  3. THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS AND CONCRETE PLINTH LAYOUT ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY THE CONTRACTOR AFTER APPROVAL BY THE RESIDENT ENGINEER.
  4. STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL TRACKWORK FASTENERS ARE NOT REQUIRED.
  5. DIMENSION OF STOCK RAIL EXTENSION FROM POINT OF SWITCH WILL VARY DEPENDING ON LOCATION OF INSULATED JOINT ON EACH SIDE OF THE TURNOUT.

No. 6 TURNOUT DATA	
ANGLE	9°31'38"
TOE LENGTH	5'-8 1/4"
HEEL LENGTH	11'-8 3/16"
TOTAL LENGTH	17'-4 7/16"
TOE SPREAD	10 27/32"
HEEL SPREAD	23 13/16"
LENGTH OF SWITCH	13'-0"
HEEL SPREAD	6 1/4"
HEEL ANGLE	2°54'00"
THICKNESS AT POINT	0"
ANGLE AT POINT	1°41'31"
SWITCH RAIL RADIUS	616.55'
ACTUAL LEAD	49'-9"
STRAIGHT CLOSURE RAIL DISTANCE	31'-0 3/4"
CURVED CLOSURE RAIL DISTANCE	31'-4 9/16"
CENTER LINE RADIUS	283.88'
DEGREE OF CURVE	20°10'59"
TANGENT ADJACENT TOE OF FROG	-19 5/8"

No. 6 DOUBLE CROSSOVER - DIRECT FIXATION		
QTY	DESCRIPTION	DWG No.
4 ASSY	13'-0" CURVED SWITCH DF COMPLETE	STD-KAD316
4 ASSY	No. 6 RAIL BOUND MANGANESE FROG DF COMPLETE	STD-KAD361
4 ASSY	9'-5" ADJUSTABLE GUARD RAIL COMPLETE	STD-KAD310
1 ASSY	No. 6 DIAMOND CROSSING DF, 15'-9" TC	STD-KAD365
4 EACH	CLOSURE / SWITCH RAIL WITH BONDED INSULATED JOINTS 44'-3 7/8"	-
4 EACH	CLOSURE / STOCK RAIL WITH BONDED INSULATED JOINTS 48'-2 1/4"	-
4 EACH	CLOSURE / SWITCH RAIL 44'-0 9/16"	-
4 EACH	CONNECTING RAILS 36'-4 3/4"	-
2 EACH	CONNECTING RAILS 13'-5 11/16"	-
4 EACH	STOCK RAILS 39'-0" STRAIGHT	-
A/R	STANDARD DF RAIL FASTENERS	STD-KAD100
A/R	SPECIAL DF TRACKWORK FASTENERS	STD-KAD306
A/R	CWR WITHIN CROSSOVER UNIT	-
12	BONDED INSULATED JOINTS	STD-KAD431
A/R	1/16", 1/8" & 1/4" THICK SHIMS	STD-KAD306
A/R	SECOND-POUR PLINTH CONCRETE AND REINFORCING STEEL WITHIN CROSSOVER UNIT	-
A/R	EPOXY GROUT FOR ANCHOR INSERTS FOR DF RAIL FASTENERS WITHIN CROSSOVER UNIT	-



**RAIL LAYOUT DIAGRAM**  
NTS

03/21/24 | 8:53 AM | HARRISBK | C:\USERS\HARRISBK\GOUND TRANSIT\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD360.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DWGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

<b>AHJ:</b>		<b>PACKAGE #</b>	
DESIGNED BY:		SCALE:	AS NOTED
DRAWN BY:		FILENAME:	STD-KAD360
CHECKED BY:		CONTRACT No.:	RTA/LR -
APPROVED BY:		DATE:	2/2024
SUBMITTED BY:		DATE:	
DATE:		REVIEWED BY:	
DATE:		DATE:	

**SOUND TRANSIT**  
STANDARD DRAWINGS  
TRACKWORK


NO. 6 DOUBLE CROSSOVER  
13'-0" CURVED SPLIT SWITCH  
15'-9" TRACK CENTERS - DIRECT FIXATION

DRAWING No.: **STD-KAD360**

FACILITY ID:

SHEET No.: REV: **2**

- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION. THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL
  - FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY THE CONTRACTOR AFTER APPROVAL BY THE RESIDENT ENGINEER.
  - SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH.



**NO. 6 RAILBOUND MANGANESE FROG ASSEMBLY**  
 (PLATE LAYOUT SHOWN FOR 15'-9" TC CROSSOVER)  
 SCALE: 3/4" = 1'-0"


03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD361.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE



SCALE: 3/4" = 1'-0"  
 FILENAME: STD-KAD361  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024


**SOUND TRANSIT  
 STANDARD DRAWINGS  
 TRACKWORK**

NO. 6 RAILBOUND MANGANESE FROG ASSEMBLY  
 FOR 15'-9" TC DOUBLE CROSSOVER  
 DIRECT FIXATION

DRAWING No.:	<b>STD-KAD361</b>
FACILITY ID:	
SHEET No.:	2

**GENERAL NOTES:**

1. RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
2. THE DESIGN CONFIGURATION, PLINTH LAYOUT AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY THE CONTRACTOR AFTER APPROVAL BY THE RESIDENT ENGINEER.
3. SPARE DIAMOND CROSSING SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH.



**NO. 6 DF DIAMOND CROSSING 15'-9" TC**  
SCALE: 3/8" = 1'-0"


03/21/24 | 8:53 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD365.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: 3/8" = 1'-0"  
 FILENAME: STD-KAD365  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 6 DIAMOND CROSSING  
DIRECT FIXATION  
FOR 15'-9" DOUBLE CROSSOVER

DRAWING No.:	<b>STD-KAD365</b>
FACILITY ID:	
SHEET No.:	REV: 2



**NO. 8 TURNOUT BALLASTED AND WELDED**  
SCALE: 1/4" = 1'-0"



**RAIL LAYOUT DIAGRAM**  
SCALE: 1/8" = 1'-0"

TURNOUT DATA			
FROG	NUMBER	8	
	ANGLE	7°09'10"	
	TOE LENGTH	6'-3"	
	HEEL LENGTH	9'-5"	
	TOTAL LENGTH	15'-8"	
	TOE SPREAD	8 7/8"	
SWITCH	HEEL SPREAD	14 19/32"	
	LENGTH OF SWITCH	19'-6"	
	HEEL SPREAD	6 1/4"	
	CURVED POINT	HEEL ANGLE	1°59'15"
		THICKNESS AT POINT	0"
	STRAIGHT POINT	ANGLE AT POINT	1°04'24"
		SWITCH RAIL RADIUS	1222.17'
		VERTEX DISTANCE	0"
		STOCK RAIL RADIUS	1217.46'
	TURNOUT CURVE	VERTEX DISTANCE	0"
ACTUAL LEAD		69'-0"	
STRAIGHT CLOSURE RAIL DISTANCE		43'-3"	
CURVED CLOSURE RAIL DISTANCE		43'-5 3/8"	
TANGENT ADJACENT TOE OF FROG		-0 5/8"	

BILL OF MATERIAL No. 8 BALLASTED TURNOUT		
QTY	DESCRIPTION	DWG No.
1 ASSY.	19'-6" CURVED SWITCH COMPLETE	STD-KAD320
1 ASSY.	NO. 8 RAILBOUND MANGANESE FROG WITH PLATES	STD-KAD375
2 ASSY.	13'-0" ADJUSTABLE GUARD RAIL WITH PLATES	STD-KAD311
1 EACH	CLOSURE RAILS WITH BONDED INSULATED JOINTS 25'-5 3/16" AND 45'-6" (SEE NOTE 9)	-
1 EACH	CLOSURE RAIL 25'-3 1/4", 19'-0" AND 39'-0"	-
1 SET	CONCRETE SWITCH TIES AS LISTED (SEE NOTE 8)	-
70	STANDARD PANDROL TIE PLATES FOR "e" CLIPS (SEE NOTE 6).	-
13	THERMITE WELDS	-
143	HIGH DENSITY POLYETHYLENE PADS (VARIOUS SIZES)	-
300	PANDROL NO. 2055 'e' CLIPS, INCL. MODIFIED 'e' CLIPS FOR I.J.	-

BILL OF MATERIAL CONCRETE SWITCH TIES	
LENGTH	QTY
9'-0"	16
10'-0"	9
11'-0"	6
12'-0"	6 (SEE NOTE 8)
13'-0"	4
14'-0"	5
15'-0"	4
16'-0"	5
<b>TOTAL</b>	<b>55</b>

- GENERAL NOTES:**
- LEFT HAND TURNOUT SHALL BE OPPOSITE TO THAT SHOWN.
  - RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE FULLY HEAT TREATED OR HEAD HARDENED RAIL.
  - DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD. OR HEAT TREATED) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
  - CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
  - INSULATED STANDARD PLATES SHALL BE FURNISHED FOR ALL TIES WHERE SPECIAL PLATES ARE NOT REQUIRED.
  - ALL SPECIAL TRACKWORK TURNOUT PLATES MUST BE INSULATED
  - HEADBLOCK TIES FOR POWER SWITCH MACHINE SHALL BE 9"X9" IN SECTION AND SHALL BE DAPPED AS REQUIRED FOR SWITCH MACHINE.
  - BONDED INSULATION JOINTS ARE NOT REQUIRED IN SOME TURNOUT INSTALLATION. SEE RESPECTIVE CONTRACT'S TRACK CHART DRAWINGS FOR DETAILS.
  - INCREASE THE LENGTH OF CONCRETE TIE CONTINUOUSLY WITH THE REQUIRED MINIMUM LENGTH OF 25 3/4" FROM THE GAUGE SIDE OF THE MOST OUTSIDE RUNNING RAIL TO THE END OF THE TIE. IN CASE OF SUCH TIE SETTING IS NOT AVAILABLE, INCREASE TIE LENGTH IN A FAMILY STYLE IS ALLOWED.

03/21/24 | 8:53 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD370.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS



DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

	SCALE:	AS NOTED
	FILENAME:	STD-KAD370
	CONTRACT No.:	RTA/LR -
	DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS TRACKWORK</b>	
<b>NO. 8 TURNOUT BALLASTED AND WELDED WITH 19'-6" CURVED SWITCH</b>	

DRAWING No.:	<b>STD-KAD370</b>
FACILITY ID:	
SHEET No.:	REV: 2



TURNOUT DATA		
NUMBER	8	
ANGLE	7°09'10"	
TOE LENGTH	6'-3"	
HEEL LENGTH	9'-5"	
TOTAL LENGTH	15'-8"	
TOE SPREAD	8 7/8"	
HEEL SPREAD	14 19/32"	
LENGTH OF SWITCH	19'-6"	
HEEL SPREAD	6 1/4"	
HEEL ANGLE	1°59'15"	
CURVED POINT	THICKNESS AT POINT	0"
	ANGLE AT POINT	1°04'24"
STRAIGHT POINT	SWITCH RAIL RADIUS	1222.17'
	VERTEX DISTANCE	0"
	THICKNESS AT POINT	0"
TURNOUT CURVE	ANGLE AT POINT	1°04'24"
	STOCK RAIL RADIUS	1217.46'
	VERTEX DISTANCE	0"
ACTUAL LEAD	69'-0"	
STRAIGHT CLOSURE RAIL DISTANCE	43'-3"	
CURVED CLOSURE RAIL DISTANCE	43'-5 3/8"	
TURNOUT CURVE	CENTER LINE RADIUS	482.09'
	DEGREE OF CURVE	11°53'05"
	CENTRAL ANGLE	5°09'55"
TANGENT ADJACENT TOE OF FROG	-0 5/8"	

BILL OF MATERIAL No. 8 DIRECT FIXATION TURNOUT		
QTY	DESCRIPTION	DWG. No.
1 ASSY.	19'-6" CURVED SWITCH COMPLETE	STD-KAD321
1 ASSY.	NO. 8 RAILBOUND MANGANESE FROG DIRECT FIXATION FASTENERS	STD-KAD375
2 ASSY.	13'-0" ADJUSTABLE GUARDRAIL COMPLETE	STD-KAD311
1 EACH	CLOSURE AND STOCK RAILS WITH BONDED INSULATED JOINTS 25'-5 3/16" AND 45'-6" (SEE NOTE 9)	-
1 EACH	CLOSURE RAIL 25'-3 1/4", 19'-0" AND 39'-0" (SEE NOTE 9)	-
A/R	STANDARD SPECIAL TRACKWORK DF FASTENERS	STD-KAD100 + STD-KAD306
A/R	SPECIAL TRACKWORK DF FASTENERS	STD-KAD306
A/R	SPECIAL TRACKWORK CONCRETE PLINTH	STD-KAD321
13	THERMITE WELDS	-

- GENERAL NOTES:**
- LEFT HAND TURNOUT SHALL BE OPPOSITE TO THAT SHOWN.
  - RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAIL.
  - DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD. OR HIGH STRENGTH) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
  - CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS AND CONCRETE PLINTH ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
  - STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL PLATES ARE NOT REQUIRED.
  - FOR NO. 8 DOUBLE CROSSOVER (15'-9" TC) INSTALLATION, FROG HEEL LENGTH AND FROG WING RAIL ARE LONGER SEE KAD473 FOR DETAILS.
  - FINAL LOCATIONS OF (SHOP FABRICATED) BONDED INSULATED JOINTS WILL DEPEND ON THE LOCATION OF TURNOUT INSTALLATION. VERIFY FINAL LOCATION OF INSULATED JOINTS WITH THE RESIDENT ENGINEER BEFORE FABRICATION OF THE TURNOUT.

- LEGEND:**
- STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - STANDARD DF FASTENER (1:40 CANT)
  - SPECIAL TRACKWORK DF FASTENER (NO CANT)

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024	----	----	----	2024 REVISED STANDARD DWGS
1	8/2019	----	----	----	REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013	----	----	----	NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY: ----  
DRAWN BY: ----  
CHECKED BY: ----  
APPROVED BY: ----

SUBMITTED BY: ---- DATE: ---- REVIEWED BY: ---- DATE: ----

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD371  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 8 TURNOUT  
DIRECT FIXATION  
WITH 19'-6" CURVED SWITCH


DRAWING No.: **STD-KAD371**  
FACILITY ID: ----  
SHEET No.: ---- REV: 2

- GENERAL NOTES:**
- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAILS.
  - DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD OR HIGH STRENGTH) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
  - CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS AND CONCRETE PLINTH LAYOUT ARE FOR INFORMATIONAL PURPOSES ONLY, FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY TURNOUT CONTRACTOR AFTER APPROVAL BY THE RESIDENT ENGINEER.
  - STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL TRACKWORK FASTENERS ARE NOT REQUIRED.

- LEGEND:**
- STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - STANDARD DF FASTENER (1:40 CANT)
  - SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - FIELD FABRICATED INSULATED JOINT
  - SHOP FABRICATED INSULATED JOINT
  - FIELD WELD



**NO. 8 DOUBLE CROSSOVER DIRECT FIXATION**  
SCALE: 3/16" = 1'-0"



**RAIL LAYOUT DIAGRAM**  
NTS

BILL OF MATERIAL NO. 6 DOUBLE CROSSOVER - DIRECT FIXATION		
QTY	DESCRIPTION	DWG NO
4 ASSY	19'-6" INSULATED CURVED SWITCH COMPLETE	STD-KAD321
4 ASSY	NO. 8 RAIL BOUND MANGANESE FROG COMPLETE	STD-KAD374
4 ASSY	13'-0" GUARD RAIL COMPLETE	STD-KAD311
1 ASSY	NO. 8 DIAMOND CROSSING	STD-KAD373
1 EACH	CLOSURE AND STOCK RAILS WITH BONDED INSULATED JOINTS 25'-3 3/16" AND 45'-6"	-
1 EACH	CLOSURE RAILS 25'-3 3/16", 19'-0" & 39'-0"	-
A/R	STANDARD DF RAIL FASTENERS	STD-KAD100
A/R	SPECIAL TRACK WORK FASTENERS	STD-KAD306
A/R	CWR WITHIN CROSSOVER UNIT	-
12	BONDED INSULATED JOINTS	-
A/R	1/16", 1/8" & 1/4" THICK SHIMS	-
A/R	SECOND-POUR PLINTH CONCRETE AND REINFORCING STEEL WITHIN CROSSOVER UNIT	-
A/R	EPOXY GROUT FOR ANCHOR INSERTS FOR DF RAIL FASTENERS WITHIN CROSSOVER UNIT	-

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: AS NOTED  
FILENAME: STD-KAD372  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 8 DOUBLE CROSSOVER  
DIRECT FIXATION  
15'-9" TRACK CENTERS

DRAWING No.: **STD-KAD372**  
FACILITY ID:  
SHEET No.: REV: 2

03/21/24 | 8:54 AM | HARRISBK  
C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD372.DWG




03/21/24 | 8:54 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD373.DWG

uncontrolled document from soundtransit.org

**GENERAL NOTES:**

1. RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
2. FOR MAINLINE OR OTHER DESIGNATED TURNOUTS, ENDS SHALL BE LEFT BLANK FOR WELDING.
3. THE DESIGN CONFIGURATION, PLINTH LAYOUT AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.




**NO. 8 DIAMOND CROSSING**  
SCALE: 3/8" = 1'-0"

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE



SCALE: AS NOTED  
FILENAME: STD-KAD373  
CONTRACT No.: RTA/LR -  
DATE: 2/2024



**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 8 DIAMOND CROSSING  
DIRECT FIXATION

DRAWING No.:	<b>STD-KAD373</b>
FACILITY ID:	
SHEET No.:	REV:
	2

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD374.DWG

Uncontrolled document from soundtransit.org



- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
  - FOR YARD OR OTHER DESIGNATED TURNOUTS:
    - A. RAIL END DRILLING, BAR PUNCHING AND TRACK BOLTS SHALL BE IN ACCORDANCE WITH AREMA MANUAL FOR 36" SIX HOLE JOINT BARS FOR BOLTED TRACK.
    - B. RAIL ENDS SHALL BE BEVELED IN ACCORDANCE WITH AREMA PLAN NO. 1005-03
  - FROG PLATE NUMBERING IS AS FOLLOWS: "8" FROG NUMBER "R" RIGHT HAND (OR "L" FOR LEFT HAND TURNOUTS) AND "1" THROUGH "15" FOR POSITION FROM TOE TO HEEL.
  - FOR FROG GUARD RAIL DATA SEE DRAWING STD-KAD311.
  - FOR TRACKWORK FASTENING PLATE AND INSULATION ASSEMBLY SEE DWG KAD306.
  - SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 7'-3" SPARE FROG HEEL LENGTH = 10'-5")

**NO. 8 RAILBOUND MANGANESE FROG**  
SCALE: 3/4" = 1'-0"

BILL OF MATERIAL No. 8 RAILBOUND MANGANESE FROG		
QTY	DESCRIPTION	PROCUREMENT MATERIAL
1	No. 8 RAILBOUND MANGANESE COMPLETE (PER AREMA STD PLAN 617-89) MODIFIED AS SHOWN	
1 SET	PLATES NO. 8RF1 THROUGH 8RF15 (NUMBERED 8LF1 THROUGH 8LF15 FOR LEFT HAND TURNOUT)	
1	FROG GAUGE PLATE PER DRAWING STD-KAD305 8RFG1 FOR RIGHT HAND TURNOUT (8LFG1 FOR LEFT HAND TURNOUT)	


No. 8 FROG PLATE DATA						
PL No.	A	B	C	D	L	H
8RF1	26.061	26.951	20.401	21.291	41	13 1/2"
8RF2	23.443	24.365	17.781	18.703	38	12"
8RF3	21.804	20.800	16.135	15.131	36	NONE
8RF4	18.920	17.916	13.251	12.247	33	NONE
8RF5	16.159	15.155	10.490	9.486	30	NONE
8RF8	15.151	16.155	—	—	30	NONE
8RF9	17.661	18.665	—	—	33	NONE
8RF10	20.171	21.175	—	—	36	NONE
8RF11	13.457	14.461	7.788	8.792	30	NONE
8RF12	15.967	16.971	10.298	11.302	30	NONE
8RF13	18.477	19.481	12.807	13.811	33	NONE
8RF14	21.510	22.516	15.843	16.847	36	—
8RF15	24.524	25.528	18.885	19.889	39	12 1/2"

MEASUREMENTS ARE IN INCHES

STOP No.	A	B
8RF5	4.739	3.986
8RF11	3.042	2.288

MEASUREMENTS ARE IN INCHES

**RAIL STOPS**  
NTS



**FROG PLATE DETAILS**  
NTS

DESIGNED BY:	---	DRAWN BY:	---	CHECKED BY:	---	APPROVED BY:	---	SUBMITTED BY:	---	DATE:	---	REVIEWED BY:	---	DATE:	2/2024	<b>SOUND TRANSIT STANDARD DRAWINGS TRACKWORK</b> NO. 8 RAILBOUND MANGANESE FROG	DRAWING No.: <b>STD-KAD374</b> FACILITY ID:	
	---		---		---		---		---		---		---		---			---
No.	DATE	DSN	CHK	APP	REVISION													2

03/21/24 | 8:54 AM | HARRISBK

C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD374.DWG


**SOUNDTRANSIT**

SCALE: AS NOTED

FILENAME: STD-KAD374

CONTRACT No.: RTA/LR -

DATE: 2/2024



- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
  - FOR MAINLINE OR OTHER DESIGNATED TURNOUTS, ENDS SHALL BE LEFT BLANK FOR WELDING.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY TURNOUT CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
  - FOR DETAIL OF 13'-0" ADJUSTABLE GUARD RAIL SEE DWG STD-KAD311.
  - FOR ADDITIONAL DETAIL OF NO. 8 FROG ON NO. 8 DOUBLE CROSSOVER INSTALLATION SEE DWG STD-KAD372.
  - SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 7'-3" SPARE FROG HEEL LENGTH = 10'-5")

**NO. 8 RAILBOUND MANGANESE FROG**  
SCALE: 3/4" = 1'-0"

BILL OF MATERIAL	
NO. 8 RAILBOUND MANGANESE FROG	
QTY	DESCRIPTION - PROCUREMENT MATERIAL
1 ASSY	No. 8 RAILBOUND MANGANESE STEEL FROG (PER AREMA STD PLAN 617-89 MODIFIED AS SHOWN)
A/R	MODEL H3 SPECIAL FASTENERS
A/R	MODEL H4 SPECIAL FASTENERS

03/21/24 | 8:54 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCTURE STD-KAD375.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024	----	----	----	2024 REVISED STANDARD DRAWINGS
1	8/2019	----	----	----	REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013	----	----	----	NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	2/2024

LINE IS 1" AT FULL SCALE

SCALE: 3/4" = 1'-0"  
FILENAME: STD-KAD375  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
TRACKWORK  
NO. 8 RAILBOUND MANGANESE FROG  
DIRECT FIXATION

DRAWING No.:	<b>STD-KAD375</b>
FACILITY ID:	
SHEET No.:	REV: 2






**NO. 8 WELDED BOLTLESS MANGANESE FROG**

SCALE: 1/2" = 1'-0"

**GENERAL NOTES:**

1. RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
2. FOR GUARD RAIL DATA REFER TO DWG STD-KAD311.
3. PROVIDE WHEEL FALSE FLANGE WEAR RAMP AT RAIL HEAD TO SUIT WHEEL TREAD WIDTH.
4. FILL UNDERSIDE VOIDS OF FROG CASTING WITH TWO COMPONENT POLYURETHANE HAVING AN 85 SHORE A DUROMETER. MACHINE EXCESS FILL MATERIAL TO PROVIDE A FLAT FROG SURFACE.

BILL OF MATERIAL - FROG		
NO 8 WELDED BOLTLESS MANGANESE FROG COMPLETE		
ITEM NO	QTY	DESCRIPTION
1	1	NO 8 - 115RE WELDED BOLTLESS MANGANESE FROG CASTING
2	2	TOE RAIL
3	3	HEEL RAIL
4	1 SET	FASTENERS NO H2 THROUGH H4
5	AS REQUIRED	POLYURETHANE FILLER




03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD376.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: DATE: REVIEWED BY: DATE:

LINE IS 1" AT FULL SCALE




SCALE: 3/4" = 1'-0"  
FILENAME: STD-KAD376  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**


NO. 8 WELDED BOLTLESS MANGANESE FROG DIRECT FIXATION TRACK

DRAWING No.:	STD-KAD376
FACILITY ID:	
SHEET No.:	REV: 1



**NO. 10 TURNOUT BALLASTED AND WELDED**

SCALE: 1/4" = 1'-0"



**RAIL LAYOUT DIAGRAM**

SCALE: 1/8" = 1'-0"

TURNOUT DATA		
NUMBER		10
ANGLE		5°43'29"
TOE LENGTH		7'-5"
HEEL LENGTH		11'-4"
TOTAL LENGTH		18'-9"
TOE SPREAD		8 3/8"
HEEL SPREAD		14 1/8"
LENGTH OF SWITCH		19'-6"
HEEL SPREAD		6 1/4"
HEEL ANGLE		1°59'15"
FROG		
THICKNESS AT POINT		0"
ANGLE AT POINT		1°04'24"
SWITCH RAIL RADIUS		1222.17'
VERTEX DISTANCE		0"
SWITCH		
THICKNESS AT POINT		0"
ANGLE AT POINT		1°04'24"
STOCK RAIL RADIUS		1217.46'
VERTEX DISTANCE		0"
ACTUAL LEAD		78'-11"
STRAIGHT CLOSURE RAIL DISTANCE		52'-0"
CURVED CLOSURE RAIL DISTANCE		52'-2"
TURNOUT CURVE		
CENTER LINE RADIUS		806.09'
DEGREE OF CURVE		7°06'45"
CENTRAL ANGLE		3°44'14"
TANGENT ADJACENT TOE OF FROG		-6 13/16"

BILL OF MATERIAL NO. 10 BALLASTED TURNOUT		
QTY	DESCRIPTION	DWG NO.
1 ASSY.	19'-6" CURVED SWITCH COMPLETE	STD-KAD320
1 ASSY.	NO. 10 RAIL BOUND MANGANESE FROG COMPLETE	STD-KAD406
2 ASSY.	16'-6" GUARD RAIL WITH PLATES & ADJ. RAIL BRACES	STD-KAD312
1 EACH	CLOSURE RAILS WITH BONDED INSULATED JOINTS 34'-2 1/2" AND 36'-0" (SEE NOTE 9)	-
1 EACH	CLOSURE RAILS 28'-0", 34'-0 1/4", 39'-0", 39'-0"	-
1 SET	CONCRETE SWITCH TIES AS LISTED (SEE NOTE 8)	-
90	SINGLE RAIL TIE PLATES FOR PANDROL "e" CLIPS (SEE NOTE 6).	-
14	THERMITE WELDS	-
170	HIGH DENSITY POLYETHYLENE PADS (VARIOUS SIZES)	-
368	PANDROL NO. 2055 'e' CLIPS INCL. MODIFIED 'e' CLIPS FOR I.J.	-

**GENERAL NOTES:**

- LEFT HAND TURNOUT SHALL BE OPPOSITE TO THAT SHOWN.
- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
- ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE FULLY HEAT TREATED OR HEAD HARDENED.
- DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD OR HEAT TREATED) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
- CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
- INSULATED SINGLE RAIL PLATES SHALL BE FURNISHED FOR 6. ALL TIES WHERE SPECIAL PLATES ARE NOT REQUIRED.
- ALL SPECIAL TRACKWORK TURNOUT PLATES MUST BE INSULATED.
- HEADBLOCK TIES FOR POWER SWITCH MACHINE SHALL BE 9"x9" IN SECTION AND SHALL BE DAPPED AS REQUIRED FOR SWITCH MACHINE.
- BONDED INSULATED JOINTS ARE NOT REQUIRED IN SOME TURNOUT. INSTALLATION. SEE RESPECTIVE CONTRACT'S TRACK CHART DRAWINGS FOR DETAILS.
- INCREASE THE LENGTH OF CONCRETE TIE CONTINUOUSLY WITH THE REQUIRED MINIMUM LENGTH OF 25 3/4" FROM THE GAUGE SIDE OF THE MOST OUTSIDE RUNNING RAIL TO THE END OF THE TIE. IN CASE OF SUCH TIE SETTING IS NOT AVAILABLE, INCREASE TIE LENGTH IN A FAMILY STYLE IS ALLOWED.

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD400.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD400  
CONTRACT No.: RTA/LR -  
DATE: 2/2024



**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 10 TURNOUT  
WITH 19'-6" CURVED SWITCH  
BALLASTED AND WELDED

DRAWING No.: **STD-KAD400**  
FACILITY ID:  
SHEET No.: REV: 2

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD401.DWG

uncontrolled document from soundtransit.org



BILL OF MATERIAL No. 10 DIRECT FIXATION TURNOUT		
QTY	DESCRIPTION	DWG No.
1 ASSY.	19'-6" INSULATED CURVED SWITCH COMPLETE	STD-KAD321
1 ASSY.	NO. 10 RAIL BOUND MANGANESE FROG COMPLETE	STD-KAD406
2 ASSY.	16'-6" GUARD RAIL COMPLETE WITH PLATES.	STD-KAD312
1 EACH	CLOSURE RAILS WITH BONDED INSULATED JOINTS 34'-2 1/2" AND 36'-0"	-
1 EACH	CLOSURE RAILS 28'-0", 34'-0 1/4", 39'-0", 39'-0"	-
A/R	SPECIAL TRACKWORK DF FASTENERS	STD-KAD100 & STD-KAD306
A/R	STANDARD DF FASTENERS	STD-KAD100
14	THERMITE WELDS	-
A/R	SPECIAL TRACKWORK CONCRETE PLINTH	STD-KAD321

TURNOUT DATA			
FROG	NUMBER	10	
	ANGLE	5°43'29"	
	TOE LENGTH	7'-5"	
	HEEL LENGTH	11'-4"	
	TOTAL LENGTH	18'-9"	
	TOE SPREAD	8 3/8"	
SWITCH	HEEL SPREAD	14 1/8"	
	LENGTH OF SWITCH	19'-6"	
	HEEL SPREAD	6 1/4"	
	HEEL ANGLE	1°59'15"	
	CURVED POINT	THICKNESS AT POINT	0"
		ANGLE AT POINT	1°04'24"
STRAIGHT POINT	SWITCH RAIL RADIUS	1222.17'	
	VERTEX DISTANCE	0"	
TURNOUT CURVE	THICKNESS AT POINT	0"	
	ANGLE AT POINT	1°04'24"	
	STOCK RAIL RADIUS	1217.46'	
	VERTEX DISTANCE	0"	
ACTUAL LEAD	78'-11"		
STRAIGHT CLOSURE RAIL DISTANCE	52'-0"		
CURVED CLOSURE RAIL DISTANCE	52'-2"		
CENTER LINE RADIUS	806.09'		
DEGREE OF CURVE	7°06'45"		
CENTRAL ANGLE	3°44'14"		
TANGENT ADJACENT TOE OF FROG	-6 13/16"		

- GENERAL NOTES:**
- LEFT HAND TURNOUT SHALL BE OPPOSITE TO THAT SHOWN.
  - RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAIL.
  - DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD. OR HIGH STRENGTH) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
  - CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS AND CONCRETE PLINTH LAYOUT ARE FOR INFORMATIONAL PURPOSES ONLY, FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY TURNOUT CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
  - STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL TRACKWORK FASTENERS ARE NOT REQUIRED.
  - FOR NO. 10 DOUBLE CROSSOVER (15'-9" TC) INSTALLATION FROG WHEEL LENGTH AND FROG WING RAIL ARE LONGER SEE STD-KAD404 AND STD-KAD405 FOR DETAILS.

- LEGEND:**
- STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
  - STANDARD DF FASTENER (1:40 CANT)
  - SPECIAL TRACKWORK DF FASTENER (NO CANT)

<b>AHJ:</b>		<b>PACKAGE #</b>	
DESIGNED BY:		SCALE:	AS NOTED
DRAWN BY:		FILENAME:	STD-KAD401
CHECKED BY:		CONTRACT No.:	RTA/LR -
APPROVED BY:		DATE:	2/2024
SUBMITTED BY:		DATE:	
DATE:		REVIEWED BY:	
DATE:		DATE:	

LINE IS 1" AT FULL SCALE

**SOUND TRANSIT**

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 10 TURNOUT  
WITH 19'-6" CURVED SWITCH  
DIRECT FIXATION


DRAWING No.: **STD-KAD401**

FACILITY ID:

SHEET No.: REV: 2


No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

UNIT LENGTH 218'-6 13/16"



**No. 10 SINGLE CROSSOVER**

SCALE: 3/16" = 1'-0"



**RAIL LAYOUT DIAGRAM**

SCALE: 1/8" = 1'-0"

**GENERAL NOTES:**

1. RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
2. ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM SHALL BE HIGH STRENGTH HEAD HARDENED RAILS.
3. DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL, STD OR HIGH STRENGTH, BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
4. CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
5. INSULATED SINGLE RAIL PLATES SHALL BE FURNISHED FOR ALL TIES WHERE SPECIAL PLATES ARE NOT REQUIRED.
6. ALL SPECIAL TRACKWORK TURNOUT PLATES MUST BE INSULATED.
7. HEADBLOCK TIES FOR POWER SWITCH MACHINE SHALL BE 9"X9" IN SECTION AND SHALL BE DAPPED AS REQUIRED FOR SWITCH MACHINE.
8. FINAL LOCATIONS OF BONDED INSULATED JOINTS WILL DEPEND ON THE LOCATION OF TURNOUT INSTALLATION. VERIFY FINAL LOCATION OF INSULATED JOINTS WITH THE RESIDENT ENGINEER BEFORE FABRICATION OF THE TURNOUT.
9. SWITCH MACHINE SIDE OF TRACK AND SPACING FROM TRACK CENTERLINE VARIES PER LOCATION.
10. WITHIN THE INDICATED AREA, INCREASE THE LENGTH OF CONCRETE TIE CONTINUOUSLY WITH THE REQUIRED MINIMUM LENGTH OF 25 3/4" FROM THE GAUGE SIDE OF THE MOST OUTSIDE RUNNING RAIL TO THE END OF THE TIE. IN CASE OF SUCH TIE SETTING IS NOT AVAILABLE, INCREASE TIE LENGTH IN A FAMILY STYLE IS ALLOWED.

BILL OF MATERIAL NO. 10 SINGLE CROSSOVER - BALLASTED		
QTY	DESCRIPTION	
2 ASSY	19'-6" CURVED SWITCH COMPLETE	STD-KAD321
2 ASSY	No. 10 RBM FROG COMPLETE	STD-KAD406
4 ASSY	16'-6" GUARD RAIL COMPLETE	STD-KAD312
A/R	CLOSURE RAILS WITH BONDED INSULATED JOINTS	-
A/R	CLOSURE RAILS	-
A/R	STOCK RAILS	-
1 SET	CONCRETE SWITCH TIES AS LISTED, SEE NOTE 8	-
A/R	SINGLE RAIL TIE PLATES FOR PANDROL "e" CLIPS OR APPROVED EQUAL, SEE NOTE 6.	-
A/R	THERMITE WELDS	-
A/R	HIGH DENSITY POLYETHYLENE PADS, VARIOUS SIZES	-
A/R	PANDROL No. 2055 'e' CLIPS INCL MODIFIED 'e' CLIPS FOR IJ OR APPROVED EQUAL	-

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\Standard Drawings\Civil-Struct\STD-KAD402.DWG

	DESIGNED BY:						
	DRAWN BY:						
	CHECKED BY:						
	APPROVED BY:						
1	2/2024						2024 REVISED STANDARD DRAWINGS
0	8/2019						NEW - CIVIL DIRECTIVE AND STANDARD DWGS
No.	DATE	DSN	CHK	APP	REVISION		

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED

FILENAME: STD-KAD402

CONTRACT No.: RTA/LR -

DATE: 2/2024

**SOUND TRANSIT**

**STANDARD DRAWINGS**

TRACKWORK

NO. 10 TURNOUT DIRECT FIXATION


19'-6" CURVED SPLIT SWITCH

DRAWING No.: **STD-KAD402**

FACILITY ID:

SHEET No.: REV: 1

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD404.DWG




**LEGEND:**

	STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
	STANDARD DF FASTENER (1:40 CANT)
	SPECIAL TRACKWORK DF FASTENER (NO CANT)
	FIELD FABRICATED INSULATED JOINT
	SHOP FABRICATED INSULATED JOINT

- GENERAL NOTES:**
- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAILS.
  - DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD OR HIGH STRENGTH) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
  - CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS AND CONCRETE PLINTH LAYOUT ARE FOR INFORMATIONAL PURPOSES ONLY, FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
  - STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL TRACKWORK FASTENERS ARE NOT REQUIRED.
  - FOR DETAILS OF TRANSITIONING OF RAIL CANT SEE STD-KAD401.

**NO. 10 DOUBLE CROSSOVER DIRECT FIXATION PLAN**  
SCALE: 3/16" = 1'-0"



BILL OF MATERIAL		
NO. 10 DOUBLE CROSSOVER - DIRECT FIXATION		
QTY	DESCRIPTION	DWG NO
4 ASSY	19'-6" CURVED SWITCH COMPLETE	STD-KAD321
4 ASSY	NO. 10 RAIL BOUND MANGANESE FROG COMPLETE	STD-KAD406
4 ASSY	16'-6" ADJUSTABLE GUARD RAIL COMPLETE	STD-KAD312
1 ASSY	NO. 10 DIAMOND CROSSING	STD-KAD405
1 EA	CLOSURE RAILS WITH BONDED INSULATED JOINTS 34'-2 1/2" AND 36'-0"	-
1 EA	CLOSURE RAILS 28'-0", 34'-0 1/4" & 39'-0"	-
1 EA	STOCK RAILS 28'-0" & 39'-0"	-
A/R	STANDARD DF RAIL FASTENERS	STD-KAD100
A/R	SPECIAL TRACKWORK FASTENERS	STD-KAD306
A/R	CWR WITHIN CROSSOVER UNIT	-
12	BONDED INSULATED JOINTS	STD-KAD431
A/R	1/16", 1/8" & 1/4" THICK SHIMS	-
A/R	SECOND-POUR PLINTH CONCRETE AND REINFORCING STEEL WITHIN CROSSOVER UNIT	-
A/R	EPOXY GROUT FOR ANCHOR INSERTS FOR DF RAIL FASTENERS WITHIN CROSSOVER UNIT	-

<b>AHJ:</b>		<b>PACKAGE #</b>	
DESIGNED BY:		SCALE:	AS NOTED
DRAWN BY:		FILENAME:	STD-KAD404
CHECKED BY:		CONTRACT NO.:	RTA/LR -
APPROVED BY:		DATE:	2/2024
SUBMITTED BY:		DATE:	
DATE:		REVIEWED BY:	
DATE:		DATE:	


No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DRAWING No.:		<b>STD-KAD404</b>
FACILITY ID:		
SHEET No.:	REV:	2

**SOUND TRANSIT**  
STANDARD DRAWINGS  
TRACKWORK  
NO. 10 DOUBLE CROSSOVER  
DIRECT FIXATION  
15'-9" TRACK CENTERS



- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
  - FOR MAINLINE OR OTHER DESIGNATED TURNOUTS, ENDS SHALL BE LEFT BLANK FOR WELDING.
  - THE DESIGN CONFIGURATION, PLINTH LAYOUT AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.



**NO. 10 DIAMOND CROSSING**  
SCALE: 3/8" = 1'-0"


03/21/24 | 8:54 AM | HARRISBK | C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD405.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: 3/8" = 1'-0"  
 FILENAME: STD-KAD405  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 10 DIAMOND CROSSING  
DIRECT FIXATION

DRAWING No.:	<b>STD-KAD405</b>
FACILITY ID:	
SHEET No.:	REV:
	2

- GENERAL NOTES:**
- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
  - FROG PLATE NUMBERING LEGEND:  
 "10" FROG NUMBER  
 "R" OR "L" - RIGHT OR LEFT HAND TURNOUT  
 "F" - FROG  
 "1" THRU "16" - SEQUENTIAL POSITION OF PLATES FROM TOE THROUGH HEEL.
  - FOR FROG GUARD RAIL DATA SEE DWG STD-KAD312.
  - ALL SPECIAL TRACKWORK FASTENING PLATES SHALL BE INSULATED.
  - SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 8'-5" SPARE FROG HEEL LENGTH = 12'-4").







**NO. 10 RAILBOUND MANGANESE FROG**

SCALE: 3/4" = 1'-0"

BILL OF MATERIAL	
No. 10 RAILBOUND MANGANESE FROG COMPLETE	
QTY	DESCRIPTION
1	No. 10 RAILBOUND MANGANESE STEEL FROG COMPLETE (PER AREMA STANDARD PLAN No. 618-03) MODIFIED AS SHOWN
1-SET	PLATES NO. 10RF1 THROUGH 10RF16 (NUMBERED 10LF1 THROUGH 10LF16 FOR LEFT HAND TURNOUT)
3	FROG GAUGE PLATES NUMBERED 10RFG1 THROUGH 10RFG3 (10LFG1 THROUGH 10LFG3 FOR LEFT HAND TURNOUT) PER DWG STD-KAD305

No. 10 FROG PLATE DATA						
PL No.	A	B	C	D	L	H
10RF1	24.42	25.15	18.77	19.50	39	12 1/2"
10RF2	22.10	22.85	16.45	17.20	37	11 1/2"
10RF3	20.695	19.893	15.042	14.240	35	NONE
10RF4	18.289	17.487	12.636	11.834	33	NONE
10RF5	14.079	13.277	8.426	7.624	29	NONE
10RF6	11.974	11.172	—	—	27	NONE
10RF7	13.742	15.189	—	—	29	NONE
10RF8	15.873	15.782	—	—	33	NONE
10RF9	16.736	17.538	—	—	33	NONE
10RF10	18.791	19.593	—	—	35	NONE
10RF11	13.690	14.492	8.037	8.839	29	NONE
10RF12	15.745	16.547	10.092	10.894	31	NONE
10RF13	17.800	18.602	12.147	12.949	33	NONE
10RF14	20.206	21.008	14.553	15.355	35	NONE
10RF15	21.84	22.64	16.19	16.99	37	11 1/2"
10RF16	25.05	25.85	19.40	20.20	41	13 1/2"

MEASUREMENTS ARE IN INCHES



STOP No.	A	B
10FG1	4.200	4.800
10F5	2.097	2.697
10F11	2.496	3.096

03/21/24 | 8:54 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCTURE\STD-KAD406.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY: \_\_\_\_\_

DRAWN BY: \_\_\_\_\_

CHECKED BY: \_\_\_\_\_

APPROVED BY: \_\_\_\_\_

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

SCALE: AS NOTED

FILENAME: STD-KAD406

CONTRACT No.: RTA/LR -

DATE: 2/2024


**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
 TRACKWORK

NO. 10 RAILBOUND MANGANESE FROG

DRAWING No.: **STD-KAD406**

FACILITY ID: \_\_\_\_\_

SHEET No.: \_\_\_\_\_ REV: **2**



- GENERAL NOTES:**
- RAIL AND COMPONENTS SHALL CONFORM TO THE 115 RE RAIL SECTION.
  - FOR MAINLINE OR OTHER DESIGNATED TURNOUTS, ENDS SHALL BE LEFT BLANK FOR WELDING.
  - THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL FASTENERS ARE FOR INFORMATIONAL PURPOSES ONLY. FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY TURNOUT CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
  - FOR DETAIL OF 16'-6" ADJUSTABLE GUARD RAIL, SEE DRAWING STD-KAD312.
  - FOR ADDITIONAL DETAIL OF NO. 10 FROG ON NO. 10 DOUBLE CROSSOVER INSTALLATION SEE DWG. KAD404 AND KAD405.
  - SPARE FROG SHALL BE PROVIDED WITH 12" LONGER TOE LENGTH AND 12" LONGER HEEL LENGTH. (SPARE FROG TOE LENGTH = 8'-5" SPARE FROG HEEL LENGTH = 12'-4")

**NO. 10 RAILBOUND MANGANESE FROG**  
SCALE: 3/4" = 1'-0"

No. 10 RAILBOUND MANGANESE FROG BILL OF MATERIAL	
QTY	DESCRIPTION / PROCUREMENT MATERIAL
1	No. 10 RAILBOUND MANGANESE COMPLETE (PER AREMA STD PLAN 618-89)
A/R	SPECIAL TRACKWORK FASTENERS (H2)
A/R	SPECIAL TRACKWORK FASTENERS (H3)
A/R	SPECIAL TRACKWORK FASTENERS (H4)


03/21/24 | 8:55 AM | HARRISBK | DRAWINGS UPDATE 2023 STANDARD DRAWINGS CIVIL-STRUCT STD-KAD407.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	4/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: 3/4" = 1'-0"  
FILENAME: STD-KAD407  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 10 RAILBOUND MANGANESE FROG  
DIRECT FIXATION TRACK

DRAWING No.:	<b>STD-KAD407</b>
FACILITY ID:	
SHEET No.:	REV: 2



**No. 10 TURNOUT DIRECT FIXATION - RIGHT HAND**  
SCALE: 3/16" = 1'-0"



**RAIL LAYOUT DIAGRAM**  
SCALE: 1/8" = 1'-0"

**PLATES LEGEND**

- STANDARD SPECIAL TRACKWORK DF FASTENER (NO CANT)
- STANDARD DF FASTENER (1:40 CANT)
- SPECIAL TRACKWORK DF FASTENER (NO CANT)

TURNOUT DATA			
FROG	NUMBER	10	
	ANGLE	5°43'29"	
	TOE LENGTH	8'-5"	
	HEEL LENGTH	10'-11"	
	TOTAL LENGTH	19'-4"	
	TOE SPREAD	10 1/8"	
SWITCH	HEEL SPREAD	1'-1 5/8"	
	LENGTH OF SWITCH RAIL	37'-4"	
	HEEL SPREAD	6 1/4"	
	HEEL ANGLE	1°59'15"	
	CURVED POINT	THICKNESS AT POINT	0"
		ANGLE AT POINT	1°04'24"
STRAIGHT POINT	SWITCH RAIL RADIUS	1222.17'	
	VERTEX DISTANCE	0"	
	THICKNESS AT POINT	0"	
	ANGLE AT POINT	1°04'24"	
TURNOUT CURVE	STOCK RAIL RADIUS	1217.46'	
	VERTEX DISTANCE	0"	
	ACTUAL LEAD	78'-11"	
	STRAIGHT CLOSURE RAIL DISTANCE	33'-2"	
	CURVED CLOSURE RAIL DISTANCE	33'-3 1/2"	
TURNOUT CURVE	CENTER LINE RADIUS	806.09'	
	DEGREE OF CURVE	7°06'45"	
	CENTRAL ANGLE	3°44'14"	
TANGENT ADJACENT TOE OF FROG		-1' 3 1/8"	

**NOTES:**

- RAIL AND COMPONENTS CONFORM TO THE 115 RE RAIL SECTION.
- ALL RAILS INDICATED BY SOLID LINES IN RAIL LAYOUT DIAGRAM ARE HIGH STRENGTH RAIL.
- DASHED LINES IN RAIL LAYOUT DIAGRAM INDICATE CONTINUOUS WELDED RAIL (STD. OR HIGH STRENGTH) BEYOND TURNOUT RAIL. RAIL INDICATED BY DASHED LINES ARE NOT INCLUDED IN THE BILL OF MATERIAL ON THIS DRAWING.
- CLOSURE RAIL LENGTHS ALLOW 7/8" FOR EACH THERMITE WELD. THE DESIGN CONFIGURATION AND DIMENSIONS OF DF RAIL
- FASTENERS AND CONCRETE PLINTH LAYOUT ARE FOR INFORMATIONAL PURPOSES ONLY, FINAL DETAILS, DIMENSIONS AND BILL OF MATERIAL WILL BE BY CONTRACTOR AFTER APPROVAL BY RESIDENT ENGINEER.
- STANDARD SPECIAL TRACKWORK DIRECT FIXATION FASTENERS SHALL BE FURNISHED WHERE SPECIAL TRACKWORK FASTENERS ARE NOT REQUIRED.
- RAIL TO BE INSTALLED WITHOUT CANT BETWEEN TURNOUTS T3 AND T4 POINTS OF SWITCH.

No. 10 DIRECT FIXATION TURNOUT		
BILL OF MATERIAL		
QTY	DESCRIPTION	DWG No.
1 ASSY.	19'-6" INSULATED CURVED SWITCH COMPLETE	STD-KAD321
1 ASSY.	NO. 10 WELDED BOLTLESS MANGANESE FROG COMPLETE	STD-KAD416
2 ASSY.	16'-6" ADJUSTABLE GUARD RAIL COMPLETE WITH PLATES	STD-KAD312
1 EACH	CLOSURE RAILS WITH BONDED INSULATED JOINTS 33'-3 1/2" AND 36'-0"	-
1 EACH	CLOSURE RAILS 28'-0", 33'-2", 39'-0", 39'-0"	-
A/R	SPECIAL TRACKWORK DF FASTENERS	SEE SPECIFICATIONS
A/R	STANDARD DF FASTENERS	SEE SPECIFICATIONS
14	THERMITE WELDS	-
A/R	SPECIAL TRACKWORK CONCRETE PLINTH	SEE SPECIFICATIONS

03/21/24 | 8:55 AM | HARRISBK

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	
DATE:	2/2024
DSN:	
CHK:	
APP:	
REVISION:	2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD415
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

NO. 10 TURNOUT  
DIRECT FIXATION WITH 19'-6" CURVED SWITCH


DRAWING No.:	STD-KAD415
FACILITY ID:	
SHEET No.:	0




- NOTES:**
1. RAIL AND COMPONENTS CONFORM TO THE 115RE RAIL SECTION.
  2. FOR GUARD RAIL DATA REFER TO DWG STD-KAD312.
  3. PROVIDE WHEEL FALSE FLANGE WEAR RAMP AT RAIL HEAD TO SUIT WHEEL TREAD WIDTH.
  4. FILL UNDERSIDE VOIDS OF FROG CASTING WITH TWO COMPONENT POLYURETHANE HAVING AN 85 SHORE A DUROMETER. MACHINE EXCESS FILL MATERIAL TO PROVIDE A FLAT FROG SURFACE.
  5. SPARE FROG SHALL BE PROVIDED WITH 24\"/>

NO 10 WELDED BOLTLESS MANGANESE FROG COMPLETE		
BILL OF MATERIAL - FROG		
ITEM #	QTY	DESCRIPTION
①	1	NO 10 - 115RE WELDED BOLTLESS MANGANESE FROG CASTING
②	2	TOE RAIL
③	2	HEEL RAIL
④	1 SET	FASTENERS NO H2 THROUGH H4
⑤	AS REQUIRED	POLYURETHANE FILLER


**No. 10 WELDED BOLTLESS MANGANESE FROG**  
SCALE: 1/2" = 1'-0"



**SECTION AT THROAT A**  
SCALE: 3" = 1'-0"



**SECTION AT 5/8\"/>**



**SECTION C**  
SCALE: 3" = 1'-0"


03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\CIVIL-STRUCT\STD-KAD416.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_  
REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

LINE IS 1" AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-KAD416  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
TRACKWORK

NO. 10 DIRECT FIXATION  
WELDED BOLTLESS MANGANESE FROG  
DETAILS


DRAWING No.: <b>STD-KAD416</b>
FACILITY ID:
SHEET No.: 0




**BALLASTED / EMBEDDED TRACK TRANSITION PLAN**  
SCALE: 3/8" = 1'-0"



**SECTION B**  
SCALE: 1" = 1'-0"



**TRANSITION BETWEEN BALLASTED TRACK AND EMBEDDED TRACK INSTALLATIONS**  
SCALE: 3/8" = 1'-0"



**SECTION C**  
SCALE: 1" = 1'-0"

**GENERAL NOTES:**

1. FOR TRANSITION SLAB DETAILS, REFER TO CIVIL DRAWINGS.
2. FOR BALLASTED TRACK SECTION AND DETAILS, SEE TYPICAL TRACK SECTIONS DRAWINGS.
3. FOR PIPE OUTLETS IN BALLASTED TRACKS, REFER TO CIVIL DRAWINGS.
4. TRANSITION SLAB'S REINFORCEMENT SHALL BE ELECTRICALLY BONDED TO TRACK SLAB REINFORCEMENT.

03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD500.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-KAD500  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**

TRANSITION SLAB EMBEDDED TRACK TO BALLASTED TRACK (115RE)


DRAWING No.:	<b>STD-KAD500</b>
FACILITY ID:	
SHEET No.:	REV: 2

**GENERAL NOTES:**


1. FOR DIRECT FIXATION SECTION AND DETAILS, SEE DWGS STD-KAD120 AND STD-KAD121 AND THE TRACK CHARTS DRAWINGS.
2. FOR BALLASTED SECTION AND DETAILS, SEE TRACKWORK DRAWINGS AND THE TRACK CHARTS DRAWINGS.
3. FOR PIPE OUTLETS IN BALLASTED TRACK, REFER TO DRAINAGE DRAWINGS AND TYPICAL TRACK UNDERDRAIN DETAILS.
4. INTERFACE BETWEEN THE TRANSITION SLAB SHALL BE 90 DEGREES AS MEASURED FROM THE CENTERLINE OF TRACK.
5. PROVIDE GROUNDING AND BONDING FOR TRANSITION SLAB AS PER NEC REQUIREMENTS.
6. IN CURVES SUPERELEVATED TRACK, THE TOP OF BALLAST RETAINER MUST FOLLOW THE BALLAST SURFACE AND BE 1" BELOW BASE OF RAIL
7. DIRECT FIXATION RACK DRAINAGE TO BE COLLECT PRIOR TO TRANSITION TO BALLASTED TRACK. SLOPE TRACK INVERT SLAB TO DRAIN INLETS. SEE CONTRACT DRAWINGS




**BALLASTED/DIRECT FIXATION TRACK PLAN**  
SCALE: 3/8" = 1'-0"



**SECTION - TRANSITION SLAB BETWEEN BALLASTED AND DIRECT FIXATION TRACK**  
SCALE: 3/8" = 1'-0"



**SECTION B**  
SCALE: 1" = 1'-0"



**SECTION C**  
SCALE: 1" = 1'-0"

03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD501.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH., SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD501
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

TRANSITION SLAB DETAILS  
BALLASTED TRACK TO DIRECT FIXATION TRACK

DRAWING No.:	<b>STD-KAD501</b>
FACILITY ID:	
SHEET No.:	REV: 2


**GENERAL NOTES:**

1. FOR DIRECT FIXATION TRACK SLAB DETAILS REFER TO STRUCTURAL DRAWINGS.
2. FOR DIRECT FIXATION TRACK DETAILS, SEE DRAWINGS STD-KAD120 AND STD-KAD121.
3. FOR EMBEDDED TRACK DETAILS, SEE TRACKWORK DRAWINGS.
4. EXTEND RAIL BOOT 4" BEYOND FACE OF SECOND POUR CONCRETE PAVEMENT INFILL.
5. INTERFACE BETWEEN THE TRANSITION SLAB SHALL BE 90 DEGREES AS MEASURED FROM THE CENTERLINE OF TRACK.




**TRANSITION EMBEDDED TO DIRECT FIXATION TRACK PLAN**

SCALE: 3/8" = 1'-0"



**SECTION**

SCALE: 1/2" = 1'-0"



03/21/24 | 8:55 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD503.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

LINE IS 1" AT FULL SCALE



SCALE: AS NOTED
FILENAME: STD-KAD503
CONTRACT No.: RTA/LR -
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS**  
TRACKWORK

TRANSITION SLAB  
DIRECT FIXATION TRACK TO EMBEDDED TRACK  
(115RE)


DRAWING No.: <b>STD-KAD503</b>
FACILITY ID:
SHEET No.: 2




- GENERAL NOTES:**
- FOR LIMITS OF RESTRAINING RAIL SEE TRACK CHART DRAWINGS.
  - SEPARATOR AND END BLOCK SHIMS ARE TO BE FABRICATED FOR THE APPROPRIATE FLANGEWAY WIDTH.
  - SEPARATOR BLOCKS ARE 4" LONG, AT 60" MAXIMUM SPACING O.C.
  - RESTRAINING RAIL JOINT BARS ARE 24" LONG, 4 HOLES.
  - RESTRAINING RAIL DRILLING IS 3 1/2" FROM END OF RAIL 1 7/16" DIA., AT 3 1/32" A.B.R.
  - THREE (3) SHIMS WILL BE PROVIDED WITH EACH SEPARATOR AND END BLOCK TO PROVIDE 1 5/8" FLANGEWAY WITH NEW RAILS.
  - RESTRAINING RAIL IS PRE-DRILLED FOR INSTALLATION OF SEPARATOR BLOCKS. CONTRACTOR SHALL FIELD DRILL RUNNING RAIL TO MATCH HOLES IN RESTRAINING RAIL.
  - FOR RESTRAINING RAIL TYPICAL PRECURVING DETAIL SEE DWG STD-KAD015.
  - CONCRETE TIE SPACING SHALL BE 27" OR LESS ON BALLASTED TRACK CONSTRUCTION.
  - RESTRAINING RAIL TAPERED END IS NOT REQUIRED ON EMBEDDED TRACK CONSTRUCTION.




**RESTRRAINING RAIL LAYOUT PLAN**  
NTS



**SEPARATOR BLOCK ASSEMBLY - SECTION A**  
NTS



**RESTRRAINING RAIL JOINT ASSY - SECTION B**  
NTS



**END BLOCK - SECTION C**  
NTS

03/21/24 | 8:55 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD505.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


SCALE: NTS	
FILENAME: STD-KAD505	
CONTRACT No.:	
RTA/LR -	
DATE:	2/2024

<b>SOUND TRANSIT</b> <b>STANDARD DRAWINGS</b> TRACKWORK RESTRAINING RAIL DETAILS	
DRAWING No.:	<b>STD-KAD505</b>
FACILITY ID:	
SHEET No.:	REV: 2

DRAWING No.:	<b>STD-KAD505</b>
FACILITY ID:	
SHEET No.:	REV: 2



**36" BONDED INSULATED JOINT BAR**  
NTS




MAXIMUM JOINT BAR ENVELOPE EXCLUDING BOLTS (BOLTS ARE 1" DIA x 6" MAX)


**SECTION A**  
NTS

**GENERAL NOTES:**


1. JOINT BAR DIMENSIONS ARE FOR 115RE RAIL. FOR ADDITIONAL INFORMATION ON THE OTHER RAIL SECTION AND JOINT BARS. SEE AREMA MANUAL VOL 1 CH. 4.
2. ALL STANDARD JOINTS FOR 115RE RAIL SHALL USE 1"x5-1/2" ELLIPTICAL-NECKED TRACK BOLTS, COMPLETE WITH NUTS AND WASHERS.
3. THE APPLIED BOLT TENSION SHALL BE BETWEEN 20,000 LBS AND 30,000 LBS PER BOLT.
4. ALL HOLES DRILLED WITH A DRILL BIT (OR SIMILAR METHOD SHALL BE GROUND AND FILED SMOOTH SO AS TO KEEP NO ROUGH EDGES BEFORE ASSEMBLING A BONDED INSULATED JOINT. MAKE SURE RAIL AND JOINT BARS ARE CLEAN AND FREE OF METAL FILINGS.
5. SPRING CLIPS SHALL BE MODIFIED AS REQUIRED TO AVOID CONTACT BETWEEN RAIL CLIP AND JOINT BAR FOR INSULATED JOINTS.
6. FOR BALLASTED AND DIRECT FIXATION TRACK CONSTRUCTION SUSPENDED ALL BONDED INSULATED JOINTS BETWEEN TIES OR DIRECT FIXATION FASTENERS, AS APPLICABLE.
7. FOR EMBEDDED TRACK CONSTRUCTION BONDED INSULATED JOINT AND RAIL SHALL BE ENCASED IN ELASTOMERIC GROUT FOR THE FULL LENGTH AS SHOWN HEREIN.
8. SEE SPECIFICATIONS FOR RAIL GAP DURING INSTALLATION.
9. RAIL HOLES FOR STANDARD JOINT BARS SHALL BE 1-1/4" DIAMETER.




**36" STANDARD JOINT BAR**  
NTS




**SECTION B**  
NTS




**INSULATED JOINT ON DF TRACK DETAIL**  
SCALE: 1/2" = 1'-0"



**EMBEDDED 36" BONDED INSULATED JOINT**  
NTS



**SECTION C**  
NTS



**INSULATED JOINT ON BALLASTED TRACK DETAIL**  
SCALE: 1/2" = 1'-0"

03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD506.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-KAD506
CONTRACT No.:	RTA/LR -
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS TRACKWORK</b>	
INSULATED AND STANDARD JOINT DETAILS	
DRAWING No.:	STD-KAD506
FACILITY ID:	
SHEET No.:	REV:
	2


**GENERAL NOTES:**

1. THE BUMPING POST ASSEMBLY SHALL BE CONNECTED TO THE RUNNING RAIL BY THE USE OF RAIL CLAMPS AND BE SUITABLE FOR INSTALLATION IN BALLASTED TRACK CONSTRUCTION.




**BUMPING POST BALLASTED TRACK**  
SCALE: 3/4" = 1'-0"

BILL OF MATERIAL PER POST	
QUANTITY	DESCRIPTION
1	BUMPING POST ASSEMBLY COMPLETE
1	ANTI-CLIMBER ADAPTER
AS REQD	250 KCMIL CABLE
AS REQD	3/4" Ø GROUND ROD
AS REQD	EXOTHERMIC WELDING



**SECTION A**  
SCALE: 3/4" = 1'-0"



**TYPICAL ANTI-CLIMBER DETAIL 1**  
SCALE: 6" = 1'-0"

03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD510.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2109				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	3/4" = 1'-0"
FILENAME:	STD-KAD510
CONTRACT No.:	RTA/LR -
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS</b>	
TRACKWORK	
BUMPING POST BALLASTED TRACK (115RE)	

DRAWING No.:	<b>STD-KAD510</b>
FACILITY ID:	
SHEET No.:	REV:
	2


03/21/24 | 8:55 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD511.DWG




**GENERAL NOTES:**  
 1. THE BUMPING POST ASSEMBLY SHALL BE CONNECTED TO THE RUNNING RAIL BY THE USE OF RAIL CLAMPS AND BE SUITABLE FOR INSTALLATION IN DIRECT FIXATION TRACK CONSTRUCTION.

BILL OF MATERIAL PER POST	
QUANTITY	DESCRIPTION
1	BUMPING POST ASSEMBLY COMPLETE
1	ANTI-CLIMBER ADAPTER

**BUMPING POST - DIRECT FIXATION TRACK**  
 SCALE: 1" = 1'-0"



**SECTION A**  
 SCALE: 3/4" = 1'-0"



**TYPICAL ANTI-CLIMBER DETAIL 1**  
 SCALE: 6" = 1'-0"

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: AS NOTED  
 FILENAME: STD-KAD511  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS TRACKWORK**  
 BUMPING POST DIRECT FIXATION TRACK (115RE TEE RAIL)

DRAWING No.:	<b>STD-KAD511</b>
FACILITY ID:	
SHEET No.:	REV: 2




**115 RE / Ri 59N COMPROMISE RAIL**  
 (LEFT HAND SHOWN, RIGHT HAND OPPOSITE)  
 SCALE: 3" = 1'-0"

**LEFT HAND**



Ri-59N GIRDER RAIL 115 RE TEE RAIL

**RIGHT HAND**



**TRANSITION RAIL**  
 SCALE: 3" = 1'-0"


03/21/24 | 8:56 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD520.DWG

No.	DATE	DSN	CHK	APP	REVISION
2	2/2024				2024 REVISED STANDARD DRAWINGS
1	8/2019				REVISED - CIVIL DIRECTIVE AND STANDARD DWGS
0	6/2013				NEW - CIVIL, ARCH, SYSTEMS GUIDANCE DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	2/2024

LINE IS 1" AT FULL SCALE








SCALE: 3" = 1'-0"  
 FILENAME: STD-KAD520  
 CONTRACT No.: RTA/LR -  
 DATE: 2/2024

**SOUND TRANSIT  
 STANDARD DRAWINGS  
 TRACKWORK**

COMPROMISE RAIL 115RE / RI 59N


DRAWING No.:	STD-KAD520
FACILITY ID:	
SHEET No.:	REV: 2

**PAVING LEGEND**


-  BALLAST
-  CONCRETE
-  SUBBALLAST
-  ASPHALT CONCRETE
-  PAVEMENT MARKING, RED COLOR STRIPED BOX

**GENERAL NOTES:**


1. DO NOT CAST CONCRETE AGAINST BALLAST.
2. RESTORE ANY DISTURBED TRACK BALLAST AND TEMP PRIOR TO LAYING DOWN PAVEMENT.




**PAVEMENT MARKING PLAN** (2)  
SCALE: 1" = 20'




**REINFORCED CONCRETE SLAB PLAN** (1)  
SCALE: 1" = 30'  
Y01-CXP001



**LRV RAMP ZONE** (A)  
SCALE: 1" = 20'



**REINFORCED CONCRETE SLAB SECTION** (B)  
SCALE: 1" = 10'



**RAIL FLANGEWAY** (C)  
SCALE: 1" = 5'


03/21/24 | 2:38 PM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-KAD550.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWING

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-KAD550  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
TRACKWORK**

PAVING AND PAD DETAILS  
CONCRETE SLAB FOR LRV UNLOADING SUPPORT

DRAWING No.:	<b>STD-KAD550</b>
FACILITY ID:	
SHEET No.:	REV: 0




**GENERAL CONSTRUCTION SIGN** **A**  
NTS



LETTERS SHALL BE HELVETICA MEDIUM, AND SHALL BE BLUE, BACKGROUND SHALL BE WHITE.

**ENGINEER'S FIELD OFFICE SIGN** **B**  
NTS

- NOTES:**
- DIGITAL IMAGE GRAPHIC FILES FOR CONSTRUCTION SIGNS ARE TO BE SECURED FROM SOUND TRANSIT AND SIGN PLACEMENT ON THE SITE TO BE IN CONSULTATION WITH SOUND TRANSIT PRIOR TO PLACEMENT.
  - FOR NUMBER OF SIGN SEE SPECIAL PROVISIONS.
  - IMAGE PROVIDED BY SOUND TRANSIT SHALL BE PRINTED ONTO 3M EXTERIOR GRADE, SELF-ADHESIVE, UVB PROTECTED VINYL OR EQUAL.



- NOTES:**
- ALL WOOD TO BE PRE-TREATED.
  - DISTANCE BETWEEN FRAME BRACES SHOULD NOT BE MORE THAN 2'-0".
  - ENGINEER'S FIELD OFFICE SIGN SHALL BE MOUNTED SIMILARLY TO GENERAL CONSTRUCTION SIGN, EXCEPT THAT FIELD OFFICE SIGN MAY BE WALL-HUNG.
  - WALL-HUNG SIGNS SHALL BE SECURED AT BOTTOM AS WELL AS TOP.

**SIGN ASSEMBLY DETAIL** **1**  
NTS

03/21/24 | 8:12 AM | HARRISBK  
C:\USERS\HARRISBK\SOJND TRANSIT\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CMD001.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE & STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

SCALE: NTS	
FILENAME: STD-CMD001	
CONTRACT No.:	
RTA/LR -	
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS CIVIL</b>	
PROJECT CONSTRUCTION SITE PROJECT SIGN	

DRAWING No.:	<b>STD-CMD001</b>
FACILITY ID:	
SHEET No.:	REV: 1



uncontrolled document from soundtransit.org




**STANDARD FENCE - CHAIN LINK MESH**  
NTS

STEEL POST SCHEDULE	
USE AND SELECTION	MINIMUM OUTSIDE DIMENSIONS (NOMINAL)
	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS	
TUBULAR - ROUND	4.00" OD
LINE POSTS	
TUBULAR - ROUND	2.875" OD
TOP, BOTTOM & BRACE RAILS	
TUBULAR - ROUND	1.66" OD
TUBULAR - SQUARE	1.50" SQ
H-SECTION	1.625" X 1.5"
C-SECTION (ROLL-FORMED)	1.625" X 1.5"


- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 13 FOR STANDARD CHAIN LINK FENCE MATERIALS DETAILS.
  - CONSTRUCTION WIRE TIES, RAILS, POSTS, AND BRACES ON THE SECURE SIDE OF THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE OF THE SECURE AREA.
  - FENCE FABRIC SHALL BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.




**ROUND POST DETAIL**  
NTS




**TRUSS AND ROD DETAIL**  
NTS




**TOP OR RAIL BRACE ATTACHMENT**  
NTS



**TENSION BAND DETAIL**  
NTS



**PLAN VIEWS**



**SIDE VIEW**

**END OR GATE POST DETAIL**  
NTS

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD101.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_ REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_


SCALE: AS NOTED  
FILENAME: STD-CSD101  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS CIVIL**  
STANDARD FENCE CHAIN LINK MESH


DRAWING No.: <b>STD-CSD101</b>
FACILITY ID:
SHEET No.: 0



03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Civil\Standards and Requirements\Projects - Drawings\Update 2023\Standard Drawings\Civil-Struct\STD-CSD102.DWG




**STANDARD FENCE - CHAIN LINK VEHICLE GATE** A  
NTS




**STANDARD FENCE - CHAIN LINK PED SWING GATE** B  
NTS


- NOTES:**
1. THIS STANDARD DRAWING ILLUSTRATES THE DETAILS FOR STANDARD CHAIN LINK FENCE GATES - VEHICLE GATE AND PEDESTRIAN ACCESS GATE.
  2. SEE SPECIFICATIONS SECTION 32 31 13 FOR STANDARD CHAIN LINK FENCE MATERIALS DETAILS.
  3. CONSTRUCTION WIRE TIES, RAILS, POSTS, AND BRACES ON THE SECURE SIDE OF THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE OF THE SECURE AREA.
  4. FENCE FABRIC SHALL BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  5. MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  6. SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  7. SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD101 FOR GROUNDING DETAILS.




**TRUSS AND ROD DETAIL** 1  
NTS



**PLAN VIEWS**



**TOP OR RAIL BRACE ATTACHMENT** 2  
NTS



**SIDE VIEW**

**END OR GATE POST DETAIL** 3  
NTS

STEEL POST SCHEDULE	
USE AND SELECTION	MINIMUM OUTSIDE DIMENSIONS (NOMINAL)
	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS	
TUBULAR - ROUND	4.00" OD
LINE POSTS	
TUBULAR - ROUND	2.875" OD
TOP, BOTTOM & BRACE RAILS	
TUBULAR - ROUND	1.66" OD
TUBULAR - SQUARE	1.50" SQ
H-SECTION	1.625" X 1.5"
C-SECTION (ROLL-FORMED)	1.625" X 1.5"

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

LINE IS 1" AT FULL SCALE


SCALE: AS NOTED  
FILENAME: STD-CSD102  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
CIVIL  
STANDARD FENCE  
CHAIN LINK FENCE GATES


DRAWING No.:	<b>STD-CSD102</b>
FACILITY ID:	
SHEET No.:	REV: 0

**NOTES:**

1. SEE SPECIFICATIONS SECTION 32 31 56 FOR STEEL PICKET FENCE REQUIREMENTS.
2. POSTS ARE CENTERED ON WALL, UNLESS OTHERWISE NOTED.
3. POST SHALL BE INSTALLED INTERNAL TO SECURE SOUND TRANSIT PROPERTY, TO BE VERIFIED BY THE DOR.
4. MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
5. SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
6. SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.



**STANDARD FENCE - STEEL PICKET FENCE** A  
NTS



**STANDARD FENCE - STEEL PICKET SWING GATE** 1  
NTS

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD103.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024	-	-	-	2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

SCALE:	AS NOTED
FILENAME:	STD-CSD103
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
CIVIL

STANDARD FENCE  
STEEL PICKET FENCE AND SWING GATE



DRAWING No.:	<b>STD-CSD103</b>
FACILITY ID:	
SHEET No.:	REV: 0








**SECURITY FENCE - CHAIN LINK MESH**  
NTS

STEEL POST SCHEDULE	
USE AND SELECTION	MINIMUM OUTSIDE DIMENSIONS (NOMINAL)
	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS	
TUBULAR - ROUND	4.00" OD
LINE POSTS	
TUBULAR - ROUND	2.875" OD
TOP, BOTTOM & BRACE RAILS	
TUBULAR - ROUND	1.66" OD
TUBULAR - SQUARE	1.50" SQ
H-SECTION	1.625" X 1.5"
C-SECTION (ROLL-FORMED)	1.625" X 1.5"

- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 13 FOR SECURITY CHAIN LINK FENCE MATERIALS DETAILS.
  - CONSTRUCTION WIRE TIES, RAILS, POSTS, AND BRACES ON THE SECURE SIDE OF THE THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE OF THE SECURE AREA.
  - FENCE FABRIC SHALL BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.



**ROUND POST DETAIL 1**  
NTS



**END OR GATE POST DETAIL 5**  
NTS

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\CIVIL-STANDARD DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD104.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:


SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_ REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

SCALE: AS NOTED  
FILENAME: STD-CSD104  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS CIVIL**  
SECURITY FENCE CHAIN LINK MESH

DRAWING No.:	<b>STD-CSD104</b>
FACILITY ID:	
SHEET No.:	REV: 0

03/21/24 | 8:13 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\PROJECTS - DRAWINGS\UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD105.DWG




**SECURITY FENCE - CHAIN LINK VEHICLE GATE**  
NTS A




**SECURITY FENCE - CHAIN LINK PED SWING GATE**  
NTS B


- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 13.53 FOR SECURITY CHAIN LINK FENCE DETAILS.
  - CONSTRUCTION WIRE TIES, RAILS, POSTS, AND BRACES ON THE SECURE SIDE OF THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE OF THE SECURE AREA.
  - FENCE FABRIC SHALL BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.




**TRUSS AND ROD DETAIL**  
NTS 1



**PLAN VIEWS**



**TOP OR RAIL BRACE ATTACHMENT**  
NTS 2



**SIDE VIEW**

**END OR GATE POST DETAIL**  
NTS 3

STEEL POST SCHEDULE	
USE AND SELECTION	MINIMUM OUTSIDE DIMENSIONS (NOMINAL)
	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS	
TUBULAR - ROUND	4.00" OD
LINE POSTS	
TUBULAR - ROUND	2.875" OD
TOP, BOTTOM & BRACE RAILS	
TUBULAR - ROUND	1.66" OD
TUBULAR - SQUARE	1.50" SQ
H-SECTION	1.625" X 1.5"
C-SECTION (ROLL-FORMED)	1.625" X 1.5"

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_  
REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

SCALE: AS NOTED  
FILENAME: STD-CSD105  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
CIVIL**

SECURITY FENCE  
CHAIN LINK FENCE GATES


DRAWING No.: **STD-CSD105**  
FACILITY ID:  
SHEET No.: REV: 0

**NOTES:**

1. SEE SPECIFICATIONS SECTION 32 31 56 FOR STEEL PICKET FENCE REQUIREMENTS.
2. POSTS ARE CENTERED ON WALL, UNLESS OTHERWISE NOTED.
3. POST SHALL BE INSTALLED INTERNAL TO SECURE SOUND TRANSIT PROPERTY, TO BE VERIFIED BY THE DOR.
4. MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
5. SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
6. SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.



**SECURITY FENCE - STEEL PICKET FENCE**  
NTS (A)



**SECURITY FENCE - STEEL PICKET SWING GATE**  
NTS (1)

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD106.DWG

DESIGNED BY:					
DRAWN BY:					
CHECKED BY:					
APPROVED BY:					
0	2/2024	----	----	----	2024 NEW STANDARD DRAWINGS
No.	DATE	DSN	CHK	APP	REVISION

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-




SCALE:	AS NOTED
FILENAME:	STD-CSD106
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT**  
**STANDARD DRAWINGS**  
CIVIL

SECURITY FENCE  
STEEL PICKET FENCE GATES

DRAWING No.:	<b>STD-CSD106</b>
FACILITY ID:	
SHEET No.:	REV: 0

- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 56 FOR STEEL PICKET FENCE REQUIREMENTS.
  - POST SHALL BE INSTALLED INTERNAL TO SECURE SOUND TRANSIT PROPERTY, TO BE VERIFIED BY THE DOR.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS



03/21/24 | 8:13 AM | HARRISBK | DRAWINGS UPDATE 2023 | STANDARD DRAWINGS | CIVIL-STRUCT | STD-CSD107.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_ REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

LINE IS 1" AT FULL SCALE


SCALE: AS NOTED  
FILENAME: STD-CSD107  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
CIVIL**

HIGH SECURITY FENCE  
STEEL PICKET FENCE

DRAWING No.: <b>STD-CSD107</b>	
FACILITY ID:	
SHEET No.:	REV: 0

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD108.DWG



- NOTES:**
- FENCE MESH SHALL BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: DATE: REVIEWED BY: DATE:

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-CSD108  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS CIVIL**  
HIGH SECURITY FENCE WELDED MESH FENCE

DRAWING No.: **STD-CSD108**  
FACILITY ID:  
SHEET No.: REV: 0

- NOTES:**
- POSTS ARE CENTERED ON WALL, UNLESS OTHERWISE NOTED.
  - SEE SPECIFICATIONS SECTION 32 31 56 FOR DECORATIVE PICKET FENCE DETAILS, DECORATIVE PICKET FENCE GATE AND METAL MESH FENCE DETAILS.
  - SEE SPECIFICATIONS SECTION 32 31 13 FOR CHAIN LINK FENCE DETAILS.
  - SLEEVE SHALL BE SCHEDULE 40 PVC. SEE SLEEVE SIZE TABLE FOR SLEEVE SIZES.
  - FENCE TYPE ACCOMMODATES SLOPES UP TO 36" IN 8'-0". INFILL PANELS TO BE VERTICAL WITH TOP/BOTTOM CUT TO SLOPE REQUIRED.
  - FOR STEPPED CONDITIONS, STEP CURBS/WALLS ON 8'-0" MODULE TO WORK WITH FENCE POST MODULE OF 8', UNO.
  - POST SHALL BE INSTALLED INTERNAL TO THE SECURED SOUND TRANSIT PROPERTY, TO BE VERIFIED BY THE ENGINEER.

POST SLEEVE SCHEDULE	
POST SIZE	SLEEVE SIZE
4" DIAMETER	5" DIAMETER *
2 7/8" DIAMETER	4" DIAMETER
3" SQUARE	6" DIAMETER *

\* SEE DETAIL 1 /STD-SED142 FOR ADDITIONAL REINFORCEMENT.



**DECORATIVE PICKET / METAL MESH FENCE**  
SCALE: 3/4" = 1'-0"

03/21/24 | 8:13 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD109.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024	----	----	----	2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	2/2024

LINE IS 1" AT FULL SCALE

SCALE: AS NOTED  
FILENAME: STD-CSD109  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS  
CIVIL**

PEDESTRIAN FENCING  
STEEL PICKET FENCE


DRAWING No.:	STD-CSD109
FACILITY ID:	
SHEET No.:	REV: 0




03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD110.DWG



**THROW PROTECTION FENCE - FRONT VIEW**  
NTS





**THROW PROTECTION FENCE - SIDE VIEW**  
NTS



**MOUNTING/ANCHOR DETAILS**  
NTS

POST AND RAIL SPECIFICATIONS			
POST	PIPE	ROLL FORMED	
	NOM SIZE SCH 40 ID	SECTION	WEIGHT LB/FT
VERTICAL POST	3 1/2" DIA	(Y)	5.10
BRACE POST	1 1/2" DIA	(Z)	1.85



**FENCE ATTACHMENT DETAILS**  
NTS

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:



SUBMITTED BY: DATE: REVIEWED BY: DATE:

SCALE: AS NOTED  
FILENAME: STD-CSD110  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
CIVIL**  
THROW PROTECTION FENCING  
DETAILS


DRAWING No.: **STD-CSD110**  
FACILITY ID:  
SHEET No.: REV: 0

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD111.DWG




**BASE PLATE** 1  
NTS


- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 56 FOR INTER-TRACK FENCE MATERIALS AND SIZE REQUIREMENTS.
  - SEE SPECIFICATIONS SECTION 26 05 26 FOR FENCE AND GATE GROUNDING REQUIREMENTS.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.




**T-JUNCTION** 2  
NTS




**TYPICAL END SECTION** 3  
NTS



**TYPICAL MID OR BOTTOM RAIL** 4  
NTS



**TYPICAL SPLICE** 5  
NTS



**TERMINAL POST** 6  
NTS

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-CSD111
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS  
CIVIL**

INTER-TRACK FENCE  
LINK LIGHT RAIL








DRAWING No.:	<b>STD-CSD111</b>
FACILITY ID:	
SHEET No.:	REV: 0



**SOUNDER INTER-TRACK FENCE - CHAIN LINK MESH**  
NTS

- NOTES:**
- SEE SPECIFICATIONS SECTION 32 31 13.53 FOR CHAIN LINK FENCE MATERIALS DETAILS.
  - CONSTRUCTION WIRE TIES, RAILS, POSTS, AND BRACES ON THE SECURE SIDE OF THE FENCE ALIGNMENT. CHAIN-LINK FABRIC SHALL BE PLACED ON THE SIDE OPPOSITE OF THE SECURE AREA.
  - FENCE FABRIC MUST BE BLACK VINYL COATED. POSTS, RAILS, AND HARDWARE SHALL BE BLACK POWDER COATED.
  - MOUND TOP OF CONCRETE BASE 1" ABOVE SURROUNDING GRADE.
  - SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.

STEEL POST SCHEDULE	
USE AND SELECTION	MINIMUM OUTSIDE DIMENSIONS (NOMINAL)
	FABRIC WIDTH 108" AND OVER
CORNER, END & PULL POSTS	
TUBULAR - ROUND	4.00" OD
LINE POSTS	
TUBULAR - ROUND	2.875" OD
TOP, BOTTOM & BRACE RAILS	
TUBULAR - ROUND	1.66" OD
TUBULAR - SQUARE	1.50" SQ
H-SECTION	1.625" X 1.5"
C-SECTION (ROLL-FORMED)	1.625" X 1.5"



03/21/24 | 8:14 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\CIVIL-STANDARD DRAWINGS\2023\STANDARD DRAWINGS\CSD112.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:


SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_ REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

SCALE: AS NOTED  
FILENAME: STD-CSD112  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS**  
CIVIL  
INTER-TRACK FENCE SOUNDER


DRAWING No.: <b>STD-CSD112</b>
FACILITY ID:
SHEET No.: 0

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD113.DWG



NOTE:  
SINGLE SIGN INSTALLATION TO UTILIZE 4 ALUMINUM BACKING BARS AS ABOVE.

**FENCE MOUNT SIGN DETAIL** (1)  
NTS



NOTE:  
MOUNT WITH 4 - 8 SST SHEET METAL SCREWS

**GATE MOUNT SIGN DETAIL** (2)  
NTS

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

LINE IS 1" AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-CSD113  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT  
STANDARD DRAWINGS**  
CIVIL  
SIGNAGE MOUNTING ON CHAINLINK  
FENCE & GATE


DRAWING No.:	STD-CSD113
FACILITY ID:	
SHEET No.:	REV: 0




**PEDESTRIAN CROSSING SWING GATE INSTALLATION** (1)  
NTS



**SECTION AT GATE POST** (4)  
NTS



**PEDESTRIAN CROSSING SWING GATE ELEVATION** (5)  
NTS



**GATE HINGE DETAIL** (6)  
NTS


- NOTES:**
- RECESS BASEPLATE. ANCHOR TO CONCRETE FOUNDATION. FINISH TO MATCH ADJACENT SURFACES. FILL RECESS WITH CONCRETE. SEE SPECIFICATION SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS.
  - FINISH TO BE SHOP OR FACTORY APPLIED. FINISH ON ALL EXPOSED METAL SHALL BE GALVANIZED WITH ST CHARCOAL GRAY POWDER COAT FINISH.
  - GATES SHALL SWING OPEN AWAY FROM TRACKWAY AND RETURN TO THE CLOSED POSITION THROUGH SPRING HINGE. GATES SHALL TAKE LESS THAN 5 POUNDS OF PRESSURE TO OPEN. HINGES ON GATES MUST PROVIDE ENOUGH TENSION TO CONSISTENTLY CLOSE GATE COMPLETELY. COORDINATE WITH SOUND TRANSIT PASSENGER EXPERIENCE DEPARTMENT TO HAVE THEIR STAFF MONITOR DURING INSTALLATION.
  - DAMPER SHALL BE ADDED TO EACH GATE. DAMPER SHALL FACILITATE FULL OPENING AND SHALL NOT INHIBIT FULL CLOSING OF GATE.
  - 6" WHITE LETTERS ON RED NON-SLIP THERMOPLASTIC BACKGROUND BONDED TO PAVEMENT.
  - FOR PEDESTRIAN SWING GATE, FURNISH AND INSTALL A PUSH TO EXIT SIGN ON THE TRACK SIDE OF THE SWING GATE AND A LOOK BOTH WAYS SIGN ON THE SIDE OF THE SWING GATE FACING AWAY FROM THE TRACKS.
  - GATE HINGE ASSEMBLY MUST BE MADE OF STEEL OR ALUMINUM.
  - SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD201.DWG


DESIGNED BY:					
DRAWN BY:					
CHECKED BY:					
APPROVED BY:					
0	2/2024				2024 NEW STANDARD DRAWINGS
No.	DATE	DSN	CHK	APP	REVISION

DESIGNED BY:		SCALE:	AS NOTED
DRAWN BY:		FILENAME:	STD-CSD201
CHECKED BY:		CONTRACT No.:	RTA/LR -
APPROVED BY:		DATE:	2/2024
SUBMITTED BY:		DATE:	
DATE:		REVIEWED BY:	
REVIEWED BY:		DATE:	

<b>SOUND TRANSIT STANDARD DRAWINGS CIVIL</b>		DRAWING No.:	<b>STD-CSD201</b>
PEDESTRIAN CROSSING SWING GATE DETAILS		FACILITY ID:	
		SHEET No.:	REV:
			1




**PEDESTRIAN ESCAPE ROUTE SWING GATE 1**  
NTS




**PEDESTRIAN ESCAPE ROUTE SWING GATE INSTALLATION 2**  
NTS

**NOTES:**


- RECESS BASEPLATE. ANCHOR TO CONCRETE FOUNDATION. FINISH TO MATCH ADJACENT SURFACES. FILL RECESS WITH CONCRETE. SEE SPECIFICATION SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS.
- FINISH TO BE SHOP OR FACTORY APPLIED. FINISH ON ALL EXPOSED METAL SHALL BE GALVANIZED WITH ST CHARCOAL GRAY POWDER COAT FINISH.
- GATES SHALL SWING OPEN AWAY FROM TRACKWAY AND RETURN TO THE CLOSED POSITION THROUGH SPRING HINGE. GATES SHALL TAKE LESS THAN 5 POUNDS OF PRESSURE TO OPEN. HINGES ON GATES MUST PROVIDE ENOUGH TENSION TO CONSISTENTLY CLOSE GATE COMPLETELY. COORDINATE WITH SOUND TRANSIT PASSENGER EXPERIENCE DEPARTMENT TO HAVE THEIR STAFF MONITOR DURING INSTALLATION. PROVIDE NOTIFICATION OF INSTALLATION TO SOUND TRANSIT STAFF PER CONTRACT SPECIFICATION.
- DAMPER SHALL BE ADDED TO EACH GATE. DAMPER SHALL FACILITATE FULL OPENING AND SHALL NOT INHIBIT FULL CLOSING OF GATE.
- FOR ESCAPE ROUTE PEDESTRIAN SWING GATE, FURNISH AND INSTALL A PUSH TO EXIT SIGN ON THE TRACK SIDE OF THE SWING GATE AND A DO NOT ENTER SIGN ON THE SIDE OF THE SWING GATE FACING AWAY FROM THE TRACKS.
- GATE HINGE ASSEMBLY MUST BE MADE OF STEEL OR ALUMINUM.
- SEE SOUND TRANSIT STANDARD DETAIL SHEET JGD-101 FOR GROUNDING DETAILS.




**VIEW FROM THE TRACK SIDE 3**  
NTS



**VIEW FROM THE PUBLIC ROW SIDE 4**  
NTS



**FOUNDATION 5**  
NTS



**HANDLE DETAIL 6**  
NTS

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\CIVIL-STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD202.DWG

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	
DATE:	2/2024
DSN:	
CHK:	
APP:	
REVISION:	2024 NEW STANDARD DRAWINGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

DATE:	
REVIEWED BY:	
DATE:	2/2024

SCALE:	AS NOTED
FILENAME:	STD-CSD202
CONTRACT No.:	RTA/LR -
DATE:	2/2024


<b>SOUND TRANSIT STANDARD DRAWINGS CIVIL</b>	
PEDESTRIAN ESCAPE ROUTE SWING GATE DETAILS	
DRAWING No.:	STD-CSD202
FACILITY ID:	
SHEET No.:	REV: 0

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD203.DWG




\*Width may vary according to lane width


**RAILROAD PAVEMENT MARKING**  
SCALE: NTS



- NOTES:**
1. NOT ALL PAVEMENT MARKINGS ARE SHOWN.
  2. SEE CIVIL DESIGN REQUIREMENTS MANUAL SET 120 - AT-GRADE CROSSINGS FOR PAVEMENT MARKINGS REQUIREMENTS.
  3. SEE LATEST VERSION OF MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) FOR PAVEMENT MARKING DETAILS INFORMATION.



**(DUAL STOP HERE MARKER WITH  
DETECTABLE WARNING SURFACE)**  
SCALE: NTS



No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

LINE IS 1" AT FULL SCALE		SCALE: AS NOTED
		FILENAME: STD-CSD203
		CONTRACT No.: RTA/LR -
		DATE: 2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS</b> CIVIL PAVEMENT MARKING DETAILS	
DRAWING No.:	STD-CSD203
FACILITY ID:	
SHEET No.:	REV: 0

03/21/24 | 8:14 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD204.DWG

uncontrolled document from soundtransit.org



DO NOT STOP TRACKS  
R8-8  
24 X 30



STOP HERE WHEN FLASHING  
R8-10  
24 X 36



STOP HERE ON RED  
R10-6  
24 X 36



GRADE CROSSING (CROSSBUCK)  
R15-1  
48 X 9



NUMBER OF TRACKS (PLAQUE)  
R15-2P  
27 X 18



LOOK  
R15-8  
36 X 18



NO MOTOR VEHICLES ON TRACKS SYMBOL  
R15-6  
24 X 24



EXAMPLE OF EMERGENCY NOTIFICATION SIGN  
I13-1



GRADE CROSSING ADVANCE WARNING  
W10-1  
36 DIA.



USE CROSSWALK LEFT  
R9-3B

NO PEDESTRIAN CROSSING (SYMBOL)  
R9-3



USE CROSSWALK RIGHT  
R9-3B

NO PEDESTRIAN CROSSING (SYMBOL)  
R9-3



NO PEDESTRIAN CROSSING (SYMBOL)  
R9-3  
18 X 18



LINK LOOK BOTH WAYS  
30 X 30  
W82-1(CA)



SOUNDER LOOK BOTH WAYS  
30 X 30  
CUSTOM


**NOTES:**

- ALL SIGN DIMENSIONS ARE IN INCHES.
- SEE LATEST VERSION OF MANUAL ON UNIFORM TRAFFIC CONTROL AND DEVICES (MUTCD) FOR SIGNAGE DETAILS.



LOW GROUND CLEARANCE (PLAQUE)  
W10-5P  
30 X 24

LOW GROUND CLEARANCE  
W10-5  
36 X 36




STORAGE SPACE XX FEET BETWEEN HIGHWAY & TRACKS BEHIND YOU  
W10-11B  
30 X 36



ROUGH CROSSING (PLAQUE)  
W10-15P  
30 X 24




NO TRAIN HORN (PLAQUE)  
W10-9P  
30 X 24




DO NOT CROSS RAILROAD TRACKS...  
CUSTOM



DANGER HIGH SPEED TRAINS CAN TRAVEL IN BOTH DIRECTIONS  
CUSTOM




GRADE CROSSING AND INTERSECTION ADVANCE WARNING  
W10-2  
36 X 36



GRADE CROSSING AND INTERSECTION ADVANCE WARNING  
W10-3  
36 X 36



GRADE CROSSING AND INTERSECTION ADVANCE WARNING  
W10-4  
36 X 36



GRADE CROSSING AND INTERSECTION ADVANCE WARNING  
W10-11  
36 X 36



SKEWED CROSSING  
W10-12  
36 X 36



NO TRAIN HORN  
W10-9  
36 X 36

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:  
DRAWN BY:  
CHECKED BY:  
APPROVED BY:

SUBMITTED BY: \_\_\_\_\_ DATE: \_\_\_\_\_ REVIEWED BY: \_\_\_\_\_ DATE: \_\_\_\_\_

LINE IS 1" AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-CSD204  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS CIVIL**  
AT-GRADE CROSSING SIGNAGE LINK & SOUNDER


DRAWING No.: **STD-CSD204**  
FACILITY ID:  
SHEET No.: 0 REV: 0



03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD205.DWG




**LRT TYPE 1 SIGNAL MOUNT DETAIL**  
SCALE: NTS




**TWO-SIDED LED PEDESTRIAN WARNING SIGN**  
SCALE: NTS

TWO SIDED PART-TIME RESTRICTION ACTIVATED BLANK-OUT PEDESTRIAN WARNING LED SIGN.  
THE ARROW HAS 44 RED LED'S.  
TRAIN & TRACK IMAGE HAS 179 YELLOW/AMBER LED'S.  
BLACK NON-REFLECTIVE BACKGROUND PLATE WITH A POLYCARBONATE PROTECTIVE LENS.  
HOUSED IN A DOUBLE FACED 8" DEEP CABINET WITH 3" VISORS.




**FLASHING LED TRAIN APPROACHING SIGN  
ALTERNATING WITH NO LEFT TURN SIGN**  
SCALE: NTS




**FLASHING LED TRAIN APPROACHING SIGN  
ALTERNATING WITH NO U-TURN SIGN**  
SCALE: NTS

PART TIME RESTRICTION ACTIVATED BLANK-OUT WARNING LED SIGNS - MUTCD W10-7 AND R3-2.  
TRACK & TRAIN - YELLOW/AMBER LED'S.  
HEADLIGHTS - WHITE LED'S.  
BLACK NON-REFLECTIVE BACKGROUND PLATE WITH A POLYCARBONATE PROTECTIVE LENS.  
HOUSED IN A HINGED 8" DEEP CABINET WITH 7" VISORS.



**TWO-SIDED LED PEDESTRIAN WARNING SIGN  
ANOTHER TRAIN COMING**  
SCALE: NTS

TWO SIDED PART-TIME RESTRICTION ACTIVATED BLANK-OUT PEDESTRIAN WARNING LED SIGN.  
THE ARROW HAS 44 RED LED'S.  
TRAIN & TRACK IMAGE HAS 179 YELLOW/AMBER LED'S.  
BLACK NON-REFLECTIVE BACKGROUND PLATE WITH A POLYCARBONATE PROTECTIVE LENS.  
HOUSED IN A DOUBLE FACED 7" DEEP CABINET WITH 13.5" VISORS.



**FLASHING LED TRAIN APPROACHING SIGN  
ALTERNATING WITH NO U-TURN SIGN**  
SCALE: NTS

PART TIME RESTRICTION ACTIVATED BLANK-OUT WARNING LED SIGNS - MUTCD W10-7 AND R3-4.  
TRACK & TRAIN - YELLOW/AMBER LED'S.  
HEADLIGHTS - WHITE LED'S.  
BLACK NON-REFLECTIVE BACKGROUND PLATE WITH A POLYCARBONATE PROTECTIVE LENS.  
HOUSED IN A HINGED 8" DEEP CABINET WITH 7" VISORS.

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-CSD205
CONTRACT No.:	RTA/LR -
DATE:	2/2024


**SOUND TRANSIT  
STANDARD DRAWINGS**  
CIVIL  
TRAIN DYNAMIC SIGN  
DETAILS

DRAWING No.:	STD-CSD205
FACILITY ID:	
SHEET No.:	REV: 0

uncontrolled document from soundtransit.org

**NOTES:**

- CONDUIT BEND SHALL BE FACTORY ELBOWS. CONNECT TO DUCTBANK STUB-UP AT POLE FOUNDATION OR STUB-OUT ON GUIDEWAY.
- SEE SPECIFICATION 34 41 13 FOR FIELD DRILLING REPAIR PROCEDURES.



**DETAIL NOTES:**

- GALVANIZED WELDED POLE PLATE AFTER FABRICATION IN ACCORDANCE WITH AASHTO M111.
- MOUNTING SHALL BE AS FOLLOWS:
  - FIELD DRILL (4) 7/16" DIA. HOLES IN WEB OF OCS POLE TO MATCH HOLE PATTERN FROM LRT SIGNAL MOUNT POLE PLATES.
  - INSTALL (4) 3/8" DIA. X 1 1/2" HEX HEAD STAINLESS STEEL BOLTS (ASTM A193 GRADE B8) WITH PLAIN WASHERS, LOCK WASHER AND HEX NUT.

03/21/24 | 8:14 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD206.DWG

DESIGNED BY:					SUBMITTED BY:					DATE:					REVIEWED BY:					DATE:				
DRAWN BY:					DATE:					REVIEWED BY:					DATE:									
CHECKED BY:					DATE:					REVIEWED BY:					DATE:									
APPROVED BY:					DATE:					REVIEWED BY:					DATE:									
2024 NEW STANDARD DRAWINGS					2/2024					2/2024					2/2024									
No.	DATE	DSN	CHK	APP	REVISION											DRAWING No.: <b>STD-CSD206</b>								
															FACILITY ID:									
															SHEET No.: 0									





**SOUND TRANSIT**  
STANDARD DRAWINGS  
CIVIL  
SIGNAL ASSEMBLY ON OCS POLES  
DETAILS



SCALE: AS NOTED  
FILENAME: STD-CSD206  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**NOTES:**

1. BOLLARDS PROTECTING BUILDING OPENINGS SHALL BE LOCATED SUCH THAT THE CENTER OF THE BOLLARD TO BE 16" FROM OUTSIDE FACE OF BUILDING, AND THE OUTSIDE EDGE OF BOLLARD TO BE IN LINE WITH THE DOOR OPENING.
2. BOLLARDS PROTECTING THE OUTSIDE CORNER OF A BUILDING SHALL BE LOCATED SUCH THAT THE CENTER OF THE BOLLARD TO BE 16" FROM CORNER OF BUILDING, MEASURE AT A DIAGONAL FROM THE BUILDING.
3. BOLLARDS PROTECTING FIRE HYDRANTS TO BE LOCATED IN ACCORDANCE WITH THE AHJ REQUIREMENTS.
4. BOLLARDS PROTECTING ABOVE GROUND ELECTRICAL OR COMMUNICATION EQUIPMENT SHALL BE PLACED SUCH THAT THE EDGE OF THE BOLLARD IS 18" FROM EDGE OF CONCRETE EQUIPMENT PAD, PARALLEL WITH FACE OF CABINET.
5. SEE SPECIFICATIONS SECTION 03 30 00 FOR CAST-IN-PLACE CONCRETE REQUIREMENTS FOR FOUNDATION.
6. SEE ARCHITECTURE REQUIREMENTS FOR BOLLARD PAINT.
7. CATALOG CUTS OF ALL BOLLARDS AND MATERIALS MUST BE SUBMITTED FOR APPROVAL BY SOUND TRANSIT ENGINEER PRIOR TO PURCHASE.



**BOLLARD (W/ CONCRETE FOUNDATION) - TYPE 1** A  
NTS



**BOLLARD (ATTACHED TO BUILDING FOUNDATION) - TYPE 2** A  
NTS

03/22/24 | 11:11 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-CSD301.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS

DESIGNED BY:
DRAWN BY:
CHECKED BY:
APPROVED BY:

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
---------------	-------	--------------	-------

LINE IS 1" AT FULL SCALE


SCALE: AS NOTED  
FILENAME: STD-CSD301  
CONTRACT No.: RTA/LR -  
DATE: 2/2024

**SOUND TRANSIT STANDARD DRAWINGS**  
CIVIL  
BOLLARDS DETAILS


DRAWING No.: <b>STD-CSD301</b>
FACILITY ID:
SHEET No.: 0

**GENERAL NOTES:**

- PROVIDE EMERGENCY RAILING AT ALL ELEVATED STRUCTURE PERIMETER LOCATIONS EXCEPT WHERE ACOUSTIC PANELS ARE REQUIRED.
- ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS IN THE LATEST VERSION OF THE SOUND TRANSIT STANDARD SPECIFICATIONS, LATEST VERSION.
- THESE DETAILS ESTABLISH GENERAL CONFIGURATION FOR DESIGN OF EMERGENCY RAILING. THE DETAILS DO NOT ENCOMPASS GEOMETRY AT ALL LOCATIONS. IT HAS BEEN PROVIDED TO CONTRACTOR FOR GENERAL DETAILING INFORMATION ONLY.
- CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF EMERGENCY RAILING LAYOUT/CONFIGURATIONS FOR ITS FULL LENGTH.
- ALL MEMBER'S SIZES, DIMENSIONS, AND NUMBERS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM ALL THE NUMBERS BY CALCULATION FOR THE SPECIFIC PROJECT.
- MATERIAL SPECIFICATIONS:
  - W- AND WT-SHAPES: ASTM A992
  - PLATES: ASTM A36
  - PIPES: ASTM A53
  - ANCHOR BOLTS:
    - HEAVY HEX HEADED ANCHOR BOLTS: ASTM F1554 GRADE 55
    - HEX NUTS: ASTM A563
    - WASHERS: ASTM F436
- ALL STEEL SHALL BE GALVANIZED OR RECEIVE A HIGH PERFORMANCE COAT (HPC) PAINT IN ACCORDANCE WITH THE CONTRACT SPECIFICATIONS, UNLESS NOTED OTHERWISE.
- THE CONTRACTOR SHALL REPAIR ALL GALVANIZED STEEL SURFACES DAMAGED BY FIELD OPERATIONS, BY PAINTING THE DAMAGED AREAS CONFORMING TO ASTM A780/A780M.
- CUTTING SHALL BE DONE BY SAWING OR MILLING AND ALL CUTS SHALL BE TRUE AND SMOOTH.
- WELDING SHALL BE DONE IN ACCORDANCE WITH AWS D1.1. SIZE OF FILLET WELDS SHALL BE 5/16" MINIMUM, EXCEPT WHERE NOTED.
- MAXIMUM SPACING OF EMERGENCY RAILING STANCHIONS SHALL BE 8'-0". ADJUST SPACING OF STANCHIONS AT EXPANSION JOINTS AND OCS POLE SUPPORTS.
- ALL VERTICAL ELEMENTS SHALL BE INSTALLED PLUMB. PROVIDE TURNBUCKLES AT A NOMINAL 60' SPACING.
- MATCH EMERGENCY RAILING EXPANSION JOINTS WITH TRACK SLAB EXPANSION JOINTS.
- PRETENSION IN EACH CABLE SHALL NOT BE SMALLER THAN 120 LBS BUT NOT HIGHER THAN 150 LBS.
- ANCHOR BOLTS ARE DESIGNED TO BE COMPATIBLE WITH FUTURE INSTALLATION OF ACOUSTIC PANELS WITH A HEIGHT UP TO 8'-4" ABOVE TOP OF LOW RAIL AND WITH STANCHIONS SPACED NO GREATER THAN 4'-0" APART.
- STANDPIPE LOCATION AND MOUNTING DETAILS ARE FOR ILLUSTRATION ONLY.
- WHERE STAINLESS STEEL INTERFACES WITH CARBON STEEL, PROVIDE A WEAR SURFACE OR BARRIER TO INHIBIT GALVANIC CORROSION BY PREVENTING CONTACT OF THE TWO MATERIALS WHERE IT OCCURS.



**TYPICAL AERIAL GUIDEWAY EMERGENCY RAILING ELEVATION**  
SCALE: 1/4" = 1'-0"



**LARGE SCALE ELEVATION 1**  
SCALE: 1" = 1'-0"


03/21/24 | 7:57 AM | HARRISBK  
C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-SWD100.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024	-	-	-	2024 REVISED STANDARD DRAWINGS
0	8/2019	-	-	-	NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

LINE IS AT FULL SCALE




SCALE: AS NOTED  
FILENAME: STD-SWD100  
CONTRACT No.: RTA/LR -  
DATE: 2/2024


**SOUND TRANSIT STANDARD DRAWINGS**  
STRUCTURAL  
AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM  
1 OF 5

DRAWING No.:	<b>STD-SWD100</b>
FACILITY ID:	
SHEET No.:	REV: 1


03/21/24 | 7:57 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\Technical Standards and Requirements Projects - Drawings Update 2023\Standard Drawings\CIVIL-STRUCT\STD-SWD101.DWG




**EMERGENCY RAILING STANCHION**  
SCALE: 3" = 1'-0"  
\*SHALL BE DESIGNED BY THE DESIGNER




**VIEW**  
SCALE: 3" = 1'-0"




**DETAIL**  
SCALE: 3" = 1'-0"  
STD-SWD100




**DETAIL**  
SCALE: 3" = 1'-0"  
STD-SWD100



**TYPICAL EMERGENCY RAILING SECTION**  
SCALE: 1" = 1'-0"  
STD-SWD100



**SECTION**  
SCALE: 1 1/2" = 1'-0"  
STD-SWD100



**COUPLING NUTS & ANCHOR BOLTS AT FUTURE STANCHION**  
SCALE: 3" = 1'-0"  
STD-SWD100

- GENERAL NOTES:**
1. WIRE ROPE SHALL BE INITIALLY TENSIONED TO 150 LBS. TENSIONING SEQUENCE FOR EACH SEGMENT OF AERIAL GUIDEWAY (EXP JT TO EXP JT) SHALL BE TOP WIRE ROPE TO BOTTOM WIRE ROPE. AT INTERMEDIATE STANCHIONS WITH TURNBUCKLES, TENSIONING SEQUENCE SHALL BE PERFORMED SO THAT THE STANCHION HAS A MAXIMUM OF 150 LBS OF UNEVEN LOADING.
  2. DURING TENSIONING, THE STANCHIONS SHALL BE MONITORED FOR DEFLECTION. TENSIONING SHOULD BE STOPPED IF DEFLECTION OF THE STANCHION IS OBSERVED.
  3. ALL MEMBER'S SIZES, DIMENSIONS, AND NUMBERS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM ALL THE NUMBERS BY CALCULATION FOR THE SPECIFIC PROJECT.
  4. 3'-6" SHALL BE MEASURED FROM ABOVE ADJACENT WALKING SURFACE OR ABOVE THE VEHICLE FLOOR, WHICHEVER IS HIGHER, TO THE TOP OF THE 2 5/8" DIA HOLE.

Uncontrolled document from soundtransit.org

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024	-	-	-	2024 REVISED STANDARD DRAWINGS
0	08/2019	-	-	-	NEW - CIVIL DIRECTIVE AND STANDARDS DWGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE: AS NOTED	FILENAME: STD-SWD101
CONTRACT No.: RTA/LR -	DATE: 2/2024


<b>SOUND TRANSIT STANDARD DRAWINGS STRUCTURAL</b>	
AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM	
2 OF 5	

DRAWING No.: <b>STD-SWD101</b>
FACILITY ID:
SHEET No.: 1



**TYPICAL AERIAL GUIDEWAY ACOUSTIC PANEL ELEVATION**

SCALE: 1/4" = 1'-0"



**LARGE SCALE ELEVATION**

SCALE: 1" = 1'-0"

**NOTE:**  
ANCHOR RODS AND STIRRUPS ARE NOT SHOWN FOR CLARITY. SEE DRAWING STD-SWD103 FOR DETAILS.

\*SEE MEP PLANS FOR STANDPIPE MOUNTING HOLE LOCATIONS

**GENERAL NOTES:**

1. THESE DETAILS ESTABLISH GENERAL CONFIGURATION FOR DESIGN OF ACOUSTIC BARRIER. THE DETAILS DO NOT ENCOMPASS GEOMETRY AT ALL LOCATIONS. IT HAS BEEN PROVIDED TO CONTRACTOR FOR GENERAL DETAILING INFORMATION ONLY. CORRESPONDING ACOUSTIC PANELS SHALL MEET ALL CRITERIA IN ACCORDANCE WITH CORRESPONDING CONTRACT SPECIFICATION.
2. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF ACOUSTIC BARRIER LAYOUT / CONFIGURATIONS FOR ITS FULL LENGTH.
3. ALL ACOUSTIC PANEL STANCHIONS SHALL BE INSTALLED PLUMB.
4. ALL STEEL SHALL BE GALVANIZED OR RECEIVE A HIGH PERFORMANCE COAT (HPC) PAINT IN ACCORDANCE WITH THE CONTRACT SPECIFICATIONS, UNLESS NOTED OTHERWISE.
5. THE STANDPIPE SYSTEM AND THE ACOUSTIC PANEL SYSTEM SHALL BE ATTACHED TO THE STANCHION IN SUCH A WAY AS TO ALLOW FOR THE REMOVAL OF ONE SYSTEM WITHOUT IMPACTING OR REQUIRING THE REMOVAL OF THE OTHER.
6. THIS STANDARD ACOUSTICAL PANEL STANCHION SYSTEM IS DESIGNED FOR ACOUSTIC PANELS WITH A HEIGHT UP TO 8'-4" ABOVE TOP OF LOW RAIL AND WITH A WEIGHT UP TO 25 PSF.
7. ALL MEMBER'S SIZES, DIMENSIONS, AND NUMBERS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM ALL THE NUMBERS BY CALCULATION FOR THE SPECIFIC PROJECT.

03/21/24 | 7:56 AM | HARRISBK C:\USERS\HARRISBK\Sound Transit\TECHNICAL STANDARDS AND REQUIREMENTS PROJECTS - DRAWINGS UPDATE 2023\STANDARD DRAWINGS\CIVIL-STRUCT\STD-SWD102.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGVS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	






SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-SWD102
CONTRACT No.:	RTA/LR -
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS STRUCTURAL</b>	
AERIAL GUIDEWAY EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM	
3 OF 5	

DRAWING No.:	STD-SWD102
FACILITY ID:	
SHEET No.:	REV: 1

**GENERAL NOTES:**  
 1. ALL MEMBER'S SIZES, DIMENSIONS, AND NUMBERS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM ALL THE NUMBERS BY CALCULATION FOR THE SPECIFIC PROJECT.



03/21/24 | 7:56 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCTURE\STD-SWD103.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	


SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-SWD103
CONTRACT No.:	RTA/LR -
DATE:	2/2024

**SOUND TRANSIT  
 STANDARD DRAWINGS  
 STRUCTURAL**

AERIAL GUIDEWAY  
 EMERGENCY RAILING/ACOUSTIC BARRIER SYSTEM  
 4 OF 5

DRAWING No.:	STD-SWD103
FACILITY ID:	
SHEET No.:	REV:
	1




**EMERGENCY RAILING LAYOUT AT RAIL LUBRICATOR SUPPORT PLAN**

SCALE: 1" = 1'-0"


**GENERAL NOTE:**

1. ALL MEMBER'S SIZES, DIMENSIONS, AND NUMBERS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM ALL THE NUMBERS BY CALCULATION FOR THE SPECIFIC PROJECT.




**ELEVATION A**

SCALE: 3/4" = 1'-0"




**EMERGENCY ACCESS THROUGH EMERGENCY RAILING**

SCALE: 3/4" = 1'-0"




**EMERGENCY RAILING LAYOUT AT INTERIOR CORNER**

SCALE: 1 1/2" = 1'-0"




**PLAN - EMERGENCY RAILING TERMINATION**

SCALE: 1 1/2" = 1'-0"



**DETAIL 1**

SCALE: 3" = 1'-0"



**SECTION B**

SCALE: 1 1/2" = 1'-0"

NOTE: ANCHOR BOLTS SHALL BE THREADED 125% BOLT DIAMETERS IN LENGTH INTO EACH END OF COUPLING NUT

03/21/24 | 7:56 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-SWD104.DWG

No.	DATE	DSN	CHK	APP	REVISION
1	2/2024				2024 REVISED STANDARD DRAWINGS
0	8/2019				NEW - CIVIL DIRECTIVE AND STANDARD DWGS

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


SCALE:	AS NOTED
FILENAME:	STD-SWD104
CONTRACT No.:	RTA/LR -
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS STRUCTURAL</b>	
AERIAL GUIDEWAY EMERGENCY RAILING/Acoustic BARRIER SYSTEM	
5 OF 5	


DRAWING No.:	STD-SWD104
FACILITY ID:	
SHEET No.:	REV:
	1




03/21/24 | 7:56 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-SWD200.DWG




**TYPICAL SECTION**  
NOT TO SCALE




**PLAN**  
NTS



**TYPICAL ELEVATION**  
NTS



**END SECTION A**  
NTS



**SECTION B**  
NTS

POST SLEEVE TO MIN. 3" ABOVE BARRIER BOTTOM. SLEEVE DIAMETER MUST BE NO GREATER THAN 4" TO ACCOMMODATE POST SLEEVE WHICH MAY BE GROUTED INTO BARRIER PER CONTRACT DRAWINGS.

**NOTES:**

- ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE SOUND TRANSIT STANDARD SPECIFICATIONS AND DESIGN REQUIREMENTS, LATEST VERSIONS.
- ALL MEMBER SIZES AND DIMENSIONS ON THE DRAWING ARE FOR REFERENCE ONLY EXCEPT REBAR AND SPACING SHOWN ARE CONSIDERED DESIGN MINIMUM. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM BY CALCULATION FOR THE SPECIFIC PROJECT.
- LOCATION AND QUANTITY OF BALLAST BARRIERS TO BE SHOWN IN THE CONTRACT DRAWINGS.
- CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF BALLAST BARRIERS INCLUDING POST SLEEVES.
- POST SLEEVES SHALL BE LOCATED A MINIMUM OF 3'-0" FROM BARRIER ENDS.
- MATERIAL SPECIFICATIONS:  
 CONCRETE:  $f_c = 4,000$  PSI  
 REINFORCEMENT: ASTM A615 GR. 60  
 NON-EPOXY COATED UNLESS NOTED OTHERWISE
- BARRIER CONFIGURATION IS BASED ON WSDOT CONCRETE BARRIER TYPE F.
- LIFTING AND TRANSPORTATION METHODS TO BE DETERMINED BY CONTRACTOR.

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWINGS


DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:


SCALE: AS NOTED	
FILENAME: STD-SWD200	
CONTRACT No.:	
DATE:	2/2024

<b>SOUND TRANSIT STANDARD DRAWINGS STRUCTURAL BALLAST BARRIER DETAILS</b>	
DRAWING No.:	STD-SWD200
FACILITY ID:	
SHEET No.:	REV: 0


03/21/24 | 7:57 AM | HARRISBK | C:\USERS\HARRISBK\DRAWINGS\STANDARD DRAWINGS\CIVIL-STRUCT\STD-SVD101-102.DWG



**ELEVATION**  
SCALE: 3/8" = 1'-0"



**PLAN VIEW** A  
SCALE: 1/2" = 1'-0"



**DETAIL** 1  
SCALE: 3" = 1'-0"

**NOTES:**

1. PROVIDE A MINIMUM OF TWO ACCESS HATCHES AT ALL COLUMN SILO LOCATIONS.
2. ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF THE SOUND TRANSIT STANDARD SPECIFICATIONS AND DESIGN REQUIREMENTS, SET 721 BRIDGES AND ELEVATED STRUCTURES, LATEST VERSIONS.
3. THESE DETAILS ESTABLISH GENERAL CONFIGURATION FOR ALLOWANCE OF ACCESS HATCHES FOR COLUMN SILO INSPECTION. THE DETAILS DO NOT ENCOMPASS GEOMETRY AT ALL LOCATIONS. IT HAS BEEN PROVIDED TO CONTRACTOR FOR GENERAL DETAILING INFORMATION ONLY.
4. EACH ACCESS HATCH PANEL SHALL BE SIZED AS TO NOT EXCEED 80 LBS EACH.
5. CONTRACTOR SHALL SUBMIT SHOP DRAWINGS OF ACCESS HATCHES AND COLUMN SILO INFORMATION .
6. ALL MEMBER SIZES AND DIMENSIONS ON THE DRAWING ARE FOR REFERENCE ONLY. THE ENGINEER OF RECORD SHALL VERIFY AND CONFIRM BY CALCULATION FOR THE SPECIFIC PROJECT.
7. MATERIAL SPECIFICATIONS: SEE SOUND TRANSIT STANDARD SPECIFICATION 05 12 00 STRUCTURAL STEEL FRAMING.
8. ALL STEEL SHALL BE GALVANIZED IN ACCORDANCE WITH THE CONTRACT SPECIFICATIONS, UNLESS NOTED OTHERWISE
9. THE CONTRACTOR SHALL REPAIR ALL GALVANIZED STEEL SURFACES DAMAGED BY FIELD OPERATIONS, BY PAINTING THE DAMAGED AREAS CONFORMING TO ASTM A780/A780M
10. WELDING SHALL BE DONE IN ACCORDANCE WITH AWS D1.1. SIZE OF FILLET WELDS SHALL BE 5/16" MINIMUM, EXCEPT WHERE NOTED.
11. COLUMN SILOS WITH A CONCRETE FILL AND INNER STEEL SHELL ANNULUS SHALL MAINTAIN THE 2'-7" CLEAR ANNULAR SPACE FOR INSPECTION. IF AN INNER SHELL IS NOT SPECIFIED, THE LADDER RUNGS MUST ANCHOR INTO THE CONCRETE. ATTACHMENTS MUST BE DESIGNED TO RESIST LOADS SPECIFIED IN WAC296-56-60209
12. FOR SILO DIAMETER AND FINISHED GRADE ELEVATION, SEE CONTRACT DRAWINGS.

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWING

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:

SCALE:	AS NOTED
FILENAME:	STD-SVD101-102
CONTRACT No.:	RTA/LR -
DATE:	2/2024






**SOUND TRANSIT  
STANDARD DRAWINGS  
STRUCTURAL**

AERIAL GUIDEWAY STRUCTURE  
COLUMN INSPECTION SILO DETAILS  
1 OF 2

DRAWING No.:	<b>STD-SVD101</b>
FACILITY ID:	
SHEET No.:	REV: 0

**NOTES:**

- INDIVIDUAL LADDER RUNG SIZES AND SPACING SHALL CONFORM TO ANSI A14.3-2008
- 7" DIMENSION SHALL BE MEASURED FROM INSIDE FACE OF THE SHAFT TO CENTERLINE OF RUNG.
- INSTALL NUT SO THAT HATCH OPENS FREELY. TACK-WELD NUT TO BOLT.




03/21/24 | 7:57 AM | HARRISBK C:\USERS\HARRISBK\DRAWINGS\CIVIL-STRUCTURE\STD-SVD101-102.DWG

No.	DATE	DSN	CHK	APP	REVISION
0	2/2024				2024 NEW STANDARD DRAWING

DESIGNED BY:	
DRAWN BY:	
CHECKED BY:	
APPROVED BY:	

SUBMITTED BY:	DATE:	REVIEWED BY:	DATE:
-	-	-	-

SCALE: AS NOTED	 <b>SOUNDTRANSIT</b>
FILENAME: STD-SVD101-102	
CONTRACT No.: RTA/LR -	
DATE: 2/2024	

<b>SOUND TRANSIT STANDARD DRAWINGS STRUCTURAL</b>	
AERIAL GUIDEWAY STRUCTURE COLUMN INSPECTION SILO DETAILS 2 OF 2	

DRAWING No.:	<b>STD-SVD102</b>
FACILITY ID:	
SHEET No.:	REV:
	0